

Series 8500

Gemini Locking Systems



ACSI

2720 Clark Avenue
St. Louis, MO 63103
(314) 652-5588
(314) 652-2090 FAX

www.acsi-inc.com

1-800-753-5558


Series 8500 | Gemini Locking Systems

ACSI Series 8500 Gemini Locking System provides safety and security for stairtower doors or controlled areas where both locking and latching are required. The Gemini system allows remote electric locking or unlocking while conforming to life-safety codes. The system consists of two components: a Gemini modified mortise lockset and a frame mounted Gemini operator.

Features

- UL Listed Gemini mortise lock - no special door prep
- UL Listed Gemini operator located in the frame
- Ability to work with a wide range of mortise lock manufacturers:
 - Arrow
 - Corbin Russwin
 - Schlage
- Fail Safe (Power Lock)
 - Outside trim is locked when power is applied and unlocked when power is removed (storeroom function when energized). Lockset will unlock in the event of a power failure (passage function).
- Fail Secure (Power Unlock)
 - Outside trim is unlocked when power is applied and locked when power is removed. Lockset will lock in the event of a power failure.
- 24VDC or 24VAC/DC
- Optional quick connect cable
- Continuous duty rated
- Heavy-duty stainless steel housing
- Security monitoring available
- Interface with life-safety systems
- Mechanical key override
 - When key cylinders are provided in the locks, the latch bolt may be momentarily retracted with key even though electrically locked. **Note:** Locks that are electrically unlocked may not be locked via the key cylinder.
- Easy installation: Gemini operator fits easily into 2" face frames. Only one wiring termination.

Series 8500 Typical Installation



Series 8500 | Gemini Locking Systems

How to Order

| 1 GEMINI OPERATOR | 2 LOCK TYPE | 3 CONTROL MODE | 4 OPERATING VOLTAGE | 5 QUICK CONNECT CABLE | 6 SECURITY MONITORING | 7 FINISH | 8 HANDING | 9 LOCK PART # |
|-------------------------|----------------|----------------------|---------------------------|-----------------------------|-----------------------------|-------------|--------------|------------------|
| 8500 | M1 | PL | 24VDC | QC | CLS | 26D | LH | L9070 |
| 8500F | M2 | PUL | 24VAC/DC | | OLS | | RH | |
| | | | | | | | LHR | |
| | | | | | | | RHR | |

Example:

| GEMINI OPERATOR | LOCK TYPE | CONTROL MODE | OPERATING VOLTAGE | QUICK CONNECT CABLE | SECURITY MONITORING | FINISH | HANDING | LOCK PART # |
|--------------------|-----------|-----------------|----------------------|------------------------|------------------------|--------|---------|-------------|
| 8500 | M1 | PL | 24VDC | QC | CLS | 26D | LH | L9070 |

1. Gemini Operator

LIST PRICE

| | | |
|-------|---|--------------|
| 8500 | The standard Gemini operator is designed for 2" face frame applications and fits a standard ANSI 4-7/8" frame prep. | \$840 |
| 8500F | Also designed for 2" face frame applications, this operator is supplied with an oversized strikeplate for easy installation in retrofit applications. | \$860 |

6. Security Monitoring

LIST PRICE

| | | |
|-----|---|--------------|
| CLS | Closed Loop Secure – Monitor • When lock is secure (latch in strike-operator in locked position), monitor loop is a closed circuit. The circuit opens if security is breached. | \$200 |
| OLS | Open Loop Secure – Monitor • When lock is secure (latch in strike-operator in locked position), monitor loop is an open circuit. The circuit closes if security is breached. | \$200 |

Note: Leave this space blank if not required.

2. Lock Type

LIST PRICE

| | | |
|----|--|-------------|
| M1 | Mortise lock with one side (lever or knob) locked | STD |
| M2 | Mortise lock with both sides (lever and knob) locked | \$40 |

7. Finish

LIST PRICE

Specify US standard architectural hardware finish as required. **STD**

8. Handing

LIST PRICE

| | | |
|-----|--------------------|------------|
| LH | Left Hand | STD |
| RH | Right Hand | STD |
| LHR | Left Hand Reverse | STD |
| RHR | Right Hand Reverse | STD |

3. Control Mode

LIST PRICE

| | | |
|-----|----------------------------|--------------|
| PL | Power Lock (Fail Safe) | STD |
| PUL | Power Unlock (Fail Secure) | \$200 |

4. Operating Voltage

LIST PRICE

| | |
|----------|-------------|
| 24VDC | STD |
| 24VAC/DC | \$38 |

9. Lock Part Number

LIST PRICE

Distributors supply ACSI with mortise locks for modification. **STD**
Please supply the lock manufacturer's full part number.

Example: L9070, 2055, BM17

Note: Refer to the last page of this catalog section for a complete listing of locks required by ACSI.

5. Quick Connect Cable

LIST PRICE

| | | |
|----|--|-------------|
| QC | An optional quick connect cable 10' in length with stripped wires at one end for splicing into an electrical box or power supply and with a connector on one end for quick connect to the Gemini operator is automatically supplied with a matching connector. | \$70 |
|----|--|-------------|

Note: Leave this space blank if not required.

Accessories

LIST PRICE

| | | |
|-----------|--------------------------|-------------|
| 302-03-02 | Gemini Mortar Guard, 15" | \$44 |
|-----------|--------------------------|-------------|

1-800-753-5558

Series 8500 | Gemini Locking Systems

Gemini Lock Modification Listing (Indicates Locksets that are UL Listed)

Note: If you do not find the lock of your choice listed, please consult with our factory engineering staff. We may request that you send a sample for further evaluation.

| Arrow | Corbin Russwin | Schlage |
|-------|----------------|---------|
| AM17 | 2055 | L9050 |
| BM17 | | L9070 |
| | | L9080* |

*L9080 must be supplied with extra spring cage to compensate for lever sag of outside trim.

Gemini Comparison Chart

| ACSI-Gemini | SDC HiTower |
|--------------------|-------------|
| Fail Safe | |
| 8500-M1-PL | 7550, 7540 |
| 8500-M2-PL | 7530 |
| 8500-M1 or M2-PL* | 7510, 7520 |
| Fail Secure | |
| 8500-M1-PUL | 7570 |
| 8500-M2-PUL | 7560 |

*Please consult the factory for proper part number.

| ACSI | Description | SDC |
|-----------|--------------------------------|-----------|
| CLS, OLS | Monitoring | 9A, 69A |
| QC | Quick Connect Cable | SC-10 |
| 302-03-02 | Mortar Guard for 2" Face Frame | 7500-EB-S |

Electrical Specifications

Gemini Operator

- 24VAC/DC, 600mA

Monitoring Contact Rating

- 0.5A @ 30VDC

