Cylinders & IC Products - Cylinders

Mortise Cylinders:



General Specifications:

Body – Brass, 1-5/32" (29.37mm) diameter. Six pin tumbler cylinder.

Furnished – Standard with cylinder collar. Length -1-1/8" (28.57mm), 1-1/4" (31.75mm),

1-1/2" (38mm), 2" (51mm).

Scalp – Brass, Bronze, Stainless steel.

Keyway - "A" keyway standard. Arrow sectional keyways available. Optional Schlage C keyway available.

Finish:

US3, US4, US10, US10B, US32, US32D.

Cylindrical Lock Cylinders:



General Specifications:

Body – Solid brass pin tumbler 6 chambers. Pinned 5 for Grade 2 Locksets. Pinned 6 for Grade 1 locksets and all hotel locksets.

Keyway - "A" keyway standard. Arrow sectional keyways available. Optional Schlage C keyway available.

Finish:

US4, US26D.

Rim Cylinders:



General Specifications:

Body – Brass, 1-5/32" (29.37mm) diameter. Six pin cylinder. Furnished - With back plate, 2 Screws (2" door max.), tailpiece and cylinder collar. **Scalp** – Brass, Bronze, Stainless steel.

Keyway – "A" keyway standard. Arrow sectional keyways

available. Optional Schlage C keyway available.

Finish:

US3, US4, US10, US10B, US32, US32D.

Deadlock Cylinders:



General Specifications:

Body – Solid brass pin tumbler, 6 chambers for E & D series deadlocks. E series pinned 5. D series pinned 6.

Keyway – "A" keyway standard. Optional Schlage C keyway available.

Finish:

US4, US26D.

Product Line	AM/BM	CL	D	E	GL	МК
Cylinder	MC61-001 ¹ MC61-AM2 ²	100YC	692C ⁵ 692DC ⁶	96C⁵ 96DC ⁶ 100 ⁷ 100DC ⁸	600HD-GL	100C³ 100C-750⁴

Product Line	N	RK	RL	
Cylinder	MC61-004	100C-RK	600HD	

- 1. For mortise functions 12, 17, 22, 23, 24, 27, 32 (i/s), 33, 37
- 2. For mortise functions 11, 13, 19, 20, 21, 31, 32 (o/s), 34, 38, 40, 41, 42, 44 3. Except for trims with a "B" knob
- 4. For trims with a "B" knob
- 5. For single cylinder function
- 6. For double cylinder function
- 7. For E41 function
- 8. For E42 function

