

Electrically Controlled Single-point Locks and Latches

[See General Information for Electrically Controlled Single-point Locks and Latches](#)

COMMAND ACCESS TECHNOLOGY L L C

R19074

22901 LA PALMA AVE
YORBA LINDA, CA 92887-6701 USA

Cylindrical type, with 1/2 in. (13 mm) latch bolts, Model(s) CL03, CL05, CL77 or CL78, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 10 ft (3048 mm) high.

Cylindrical type, with 1/2 in. (13 mm) latch bolts, Model(s) CL12, CL70, CL80, CL93, CL94, CL96, CLN12, CLN70, CLN80, CLN94 or CLN 96, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 10 ft (3048 mm) high.

Cylindrical type, with 1/2 in. (13 mm) latch bolts, Model(s) CL370 or CL371, may be used on doors rated up to 3 hrs and measuring up to 4 ft wide and 10 ft high.

Cylindrical type, with 1/2 in. (13 mm) latch bolts, Model(s) CL90, CL 91 or CL180, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Cylindrical type, with 1/2 in. (13 mm) latch bolts, Model(s) CLCR05, CLCLF or CLDH86, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Cylindrical type, with 1/2 in. (13 mm) latch bolts, Model(s) CLDOR80, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 10 ft (3048 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) LPM110, LPM180, LPM182, LPM183, LPM184, LPM185, LPM186, LPM187 or LPM188, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) ML, ML87, ML88, ML8747, ML8748, ML8753, ML8770, ML8780 or ML8782, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) ML01, ML03, ML04, ML05, ML48, ML53, ML59, ML70, ML80, ML82, ML337, ML370, ML371, ML372, ML373, ML482, ML8053 or ML8080, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 10 ft (3048 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) ML1 or ML1D, may be used on doors rated up to 1-1/2 hrs and measuring up to 4 ft (1220 mm) wide and 9 ft (2743 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) ML1 or ML1D, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 10 ft (3048 mm) high, may be used on doors rated up to 1-1/2 hrs and measuring up to 4 ft (1220 mm) wide and 9 ft (2743 mm) high

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) ML11, ML11N, ML21, ML21N, ML51, ML51N, ML81, ML81N, ML651N or ML681N, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) ML148, ML153, ML170, ML180, ML182, ML180-M, ML182-M, ML1035, ML1482, ML8748, ML8753, ML8770, ML8780, ML8782 or ML87482, for use with doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) ML35, ML35D, ML35W, ML45D, ML45W or ML453D, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 10 ft (3048 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MLAN10, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 10 ft (3048 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MLB51 or MLB53, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MLD80, may be used on doors rated up to 1-1/2 hrs and measuring up to 4 ft (1220 mm) wide and 9 ft (2743 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MLDK80 or MLDL80, may be used on doors rated up to 3 hrs and measuring up to 4 ft wide and 10 ft high, may be used on doors rated up to 1-1/2 hrs and measuring up to 4 ft wide and 9 ft high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MLH, ML77, ML78, ML90, ML91, ML94 or ML95, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high or doors rated 1-1/2 hr and measuring up to 4 ft (1220 mm) wide and 9 ft (2743 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MLP15, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MLTS86, MLTS87 or MLTS88, may be used on doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Last Updated on 2020-05-06

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."