



# Flexible Piping Fittings and Valves Catalog

C-FLEX-0320

PEX and PE-RT Fittings and Joining Devices for  
Potable Water Applications



## QUALITY PRODUCTS SINCE 1904

A recognized brand leader bringing flow control products and technologies to market, NIBCO has a history of success and innovation in the plumbing industry.

Headquartered in Elkhart, Indiana, we operate multiple manufacturing plants and distribution centers strategically located throughout the United States and globally, and offer more than 36,000 SKUs, including our NIBCO® family brands, Webstone®, Chemtrol® and Sure Seal®.

We have vertically integrated manufacturing, distribution and networked communications to provide a seamless source of information and service, 24/7. We place great emphasis on personal connections with our factory direct sales, live customer service and technical service support. We also offer unique programs to support our customers' success, including our NIBCO Partner program, Vendor Managed Inventory and EDI for wholesalers.

More than 90 percent of NIBCO-branded products are manufactured in the U.S. using high-quality materials and innovative processes and technologies to improve product performance and quality. For every high-quality valve or fitting made at NIBCO, each is made with pride by the hundreds of NIBCO associates who work there.

Today, NIBCO is a fifth-generation, family- and associate-owned business. Since 1904, we've pioneered many products and processes. As the flow control industry continues to become more demanding, we remain focused on what has made us successful: delivering more than a product and making business better for each of our customers.



**VISIT OUR WEBSITE TO LEARN MORE**

*Visit our website for the most current information.*

**Table Of Contents**

Introduction .....4

Material Selection ..... 5 - 7

Fitting Terms and Abbreviations .....7

Metal Insert Fittings ..... 8 - 11

Plastic Insert Fittings ..... 12 - 13

Multiport Tees .....14

Connections (Crimp Rings and Sleeves) .....14

Valves .....15

Tools and Accessories ..... 16 - 17

NIBCO® Warranty .....18



## Applications

NIBCO fittings and joining devices are designed to work in potable water applications with PEX and PE-RT. This includes PEX types a, b, and c.

## Standards and Approvals

PEX insert fittings and copper crimp rings are manufactured to comply with CSA B137.5 and ASTM F807. NIBCO poly fittings are manufactured to comply with ASTM F2159. PEX components are listed for compliance to NSF/ANSI/CAN 14 and NSF/ANSI/CAN 61 by NSF International for use in potable water systems. PEX fittings intended for use in potable water are also evaluated for compliance with the lead free requirements, as per test method NSF/ANSI/CAN 372.



## Operating Limits

Water: 160 PSI @ 73° F (1.10 MPa @ 23° C)  
100 PSI @ 180° F (0.69 MPa @ 82° C)  
80 PSI @ 200° F (0.55 MPa @ 93° C)\*

## Epoxy

NIBCO does not recommend exposing any of our plastic piping components, o-rings, or elastomer seals to epoxy coatings of any kind.

# Material Selection

## Plastic Piping Standards

Many commercial, industrial, and governmental standards or specifications are available to assist the design engineer in specifying plastic piping systems. Standards most frequently specified in plastic piping systems are American Society for Testing and Materials (ASTM) Standards. Below is a list and description of those standards most typically applied to industrial plastic piping.

## Polyethylene (PE & PE-RT)

Polyethylene is the most common olefin material and is used in transporting water. Because olefins cannot be joined with cements, barbed insert fittings are used for mechanical assembly. PE is light weight, low cost, has excellent chemical resistance, low coefficient of friction, and is non-toxic.

## Cross-Linked Polyethylene (PEX)

PEX is the common name for cross-linked polyethylene. PEX tubing is predominantly used in water distribution systems, hydronic radiant heating systems, and natural gas systems.

Almost all PEX is made from high density polyethylene (HDPE). PEX contains cross-linked bonds that are introduced into the polymer structure, changing the thermoplastic into a thermoset. Cross-linking is accomplished during or after the extrusion of the tubing. The required degree of cross-linking, according to ASTM F876, is between 65 to 89 percent.

The cross-linking process improves high-temperature properties, toughness, chemical resistance and abrasion resistance.

Cross-linking may be done by the peroxide (Engel) method, silane (moisture cure) method, or electron beam method.

## Modified Polyphenylsulfone (PPSU)

Polyphenylsulfone is a thermoplastic that is tough, rigid, high-strength, and retains its properties between -148° F and 302° F (-100° C and 150° C). PPSU has very high dimensional stability; the size change when exposed to boiling water or 302° F (150° C) air generally falls below 0.1 percent. Polyphenylsulfone is resistant to acids and bases. PPSU is resistant to oxidizing agents; therefore, can be cleaned by bleaches. However, PPSU is not resistant to low-polar organic solvents (e.g., ketones and chlorinated hydrocarbons) and aromatic hydrocarbons. In addition, PPSU is often chosen for difficult applications including high water temperatures, chlorides, or when water quality may increase the risk of dezincification, a type of corrosion that can adversely affect metal fittings.

## Brass

Brass is the term used for copper alloys where zinc is the principle alloying element along with copper. Brass has a yellow color, somewhat similar to gold. Brass plumbing components may be machined from extruded shapes, forged, or cast. This alloy is mainly used for decorative fixtures, plumbing components, and electrical applications. Today, almost 90% of all brass alloys are recycled.

## Copper (Cu)

Copper (Cu) is a natural element that has historically been the dominant material used in plumbing, heating, cooling, and other piping applications. Copper is a ductile metal with excellent thermal conductivity and is corrosion resistant. The materials used in copper piping products comply with the requirements of specifications established by the American Society for Testing and Materials (ASTM). The alloy customarily used for copper tube and copper fittings is designated as C12200 (Copper No. 122). This alloy contains a minimum of 99.9% pure copper and is deoxidized by the addition of phosphorus. Other copper alloys may be used.

*Visit our website for the most current information.*

# Material Selection

## Plastic Piping Standards

### NSF/ANSI/CAN 61

Drinking Water System Components - Health Effects. This is the American National Standard for health effects of drinking water system components. This standard establishes the health effects requirements for the chemical contaminants and impurities that are indirectly imparted to drinking water from products, components and materials used in drinking water systems. This Standard is maintained by a Joint Committee with equal representation from regulators (such as; EPA, Health Canada, and state drinking water officials), users (such as; water purveyors, utilities, and engineers) and manufacturers. Approval by the American National Standards Institute ensures the standard is developed and maintained using an open consensus process and has representation by all stakeholders.

### NSF/ANSI 14

Plastics Piping System Components and Related Materials. NSF/ANSI Standard 14 establishes minimum physical, performance, health effects, quality assurance, marking, and record keeping requirements for plastic piping components and related materials such as: Thermoplastic Materials, Thermoset Materials, Non-plastic Components, Piping and Tubing, Fittings and Valves, Appurtenances, Joining Materials, and Gaskets, Ingredients of Materials and Special Engineered Products and Materials. Standard 14 outlines production facility inspection, quality control, short-term performance testing, long-term performance evaluation, and chemical extraction testing of the products to ensure continued compliance. The NSF Mark for these certified products include such things as the manufacturer name or trademark; the certification agency/ laboratory name or trademark; the reference performance standard (such as ASTM F876 and F877); product end use (pw or rfh), material type designation such as PEX or PEX/AL/PEX; product size, date of production and manufacturer identification code for tubing. For products with size constraints that do not accommodate complete marking, the manufacturer must include all such details on the product packaging.

### ASTM Standard F876

Standard Specification for Cross-linked Polyethylene (PEX) Tubing. This Standard contains dimensional requirements for tubing in addition to burst, sustained pressure, and other relevant performance tests at different water temperatures.

### ASTM Standard F877

Standard Specification for Cross-linked Polyethylene (PEX) Plastic Hot- and Cold-Water Distribution Systems. This Standard contains performance requirements for PEX tubing and fittings systems. Also, this Standard contains test methods and methods of marking for components used in PEX hot- and cold-water distribution systems intended for 100 psi (0.69 MPa) water service up to and including 180°F (82°C).

### ASTM Standard F1807

Standard Specification for Metal Insert Fittings Utilizing a Copper Crimp Ring for SDR9 Cross-linked Polyethylene (PEX) Tubing. This Standard contains material and dimensional requirements for the insert fittings and crimp rings used with PEX tubing. The performance requirements for these products are defined within ASTM F877.

### ASTM Standard F2159

Specification for Plastic Insert Fittings Utilizing a Copper Crimp Ring for SDR9 Cross-linked Polyethylene (PEX) Tubing. This Standard covers Polyphenylsulfone insert fittings and copper crimp rings for use with cross-linked polyethylene (PEX) tubing. The performance requirements for these products are defined within ASTM F877.

### ASTM Standard F2623

Standard Specification for Polyethylene Raised Temperature (PE-RT) Tubing. The tubing produced under this specification is for use in general fluid transport, including hydronics and irrigations systems.

Visit our website for the most current information.

# Material Selection

## Plastic Piping Standards

### CSA B137.5

Crosslinked polyethylene (PEX) tubing systems for pressure applications.

### CSA B137.18

Polyethylene of raised temperature resistance (PE-RT) tubing systems for pressure applications.

### ASTM Standard F2769

Standard Specification for Polyethylene Raised Temperature (PE-RT) Tubing. This Standard contains dimensional requirements for tubing in addition to burst, sustained pressure, and other relevant performance tests at different water temperatures.

### NSF-pw

Identification mark for products that meet all applicable performance standards for pressure-rated potable water applications as required by NSF/ANSI Standard 14 and that comply with NSF/ANSI/CAN 61 for health effects.

### NSF-rfh

Identification mark for products that meet all applicable performance standards for a pressure-rated in-floor heating application as required by NSF/ANSI Standard 14. No health effects evaluation is required.

### NSF-61

Identification mark for products that meet the applicable requirements of NSF/ANSI/CAN 61.

### California Proposition 65

In November 1986, California voters approved a ballot initiative to address concerns about exposures to toxic chemicals. That initiative became The Safe Drinking Water and Toxic Enforcement Act of 1986, better known by its original name, Proposition 65. This Proposition requires the Governor of California to publish a list of chemicals that are known to the State of California to cause cancer, birth defects or other reproductive harm. Over 750 chemicals and materials, including many metals and plastics, have been listed as of December 12, 2006. Second, Manufacturers are required to provide a "clear and reasonable" warning before exposing anyone to a listed chemical. This warning can be given by a variety of means, such as by labeling a consumer product, by posting signs at the workplace, or by publishing notices in a newspaper. A Proposition 65 warning means that the Manufacturer issuing the warning believes that one or more listed chemicals is present in its product, even if it is only present in trace quantities.

### Kentucky

Metal insert fittings utilizing a copper crimp ring for cross-linked polyethylene (PEX) tubing must be produced and labeled as ASTM F1807. Methods of joining other than mentioned above shall be prohibited unless documentation is provided, from the systems manufacturer, honoring full warranty of the system installed. Fittings which have a smaller ID (inside diameter) other than what is required for the insert portion of the fitting shall not be permitted. A system consisting of material from multiple manufacturers (i.e. fittings, tubing and crimp rings) shall be prohibited unless documentation from manufacturers is produced providing full warranty. Connections for PEX systems other than those in section 1 of this regulation will be prohibited.

# Fitting Terms and Abbreviations

FIP = Female Iron Pipe  
MIP = Male Iron Pipe  
NPSM = Straight Pipe Thread  
CTS = Copper Tube Size

SVL = Swivel  
PB = Polybutylene  
MSWT = Male Sweat  
FSWT = Female Sweat

Visit our website for the most current information.

# METAL INSERT FITTINGS FOR PEX AND PE-RT LEAD-FREE\* PERFORMANCE BRONZE®

## COUPLINGS

NP01-LF  
NP01R-LF



### COUPLINGS

Figure No.	Material No.	Size	Weight	Bag Qty	Master Ctn Qty
NP01-LF	PX80500X	3/8"	0.018	25	2,000
NP01R-LF	PX80510A	1/2" x 3/8"	0.024	50	1,000
NP01-LF	PX80521A	1/2"	0.032	50	1,000
NP01R-LF	PX80540A	3/4 x 1/2"	0.056	25	500
NP01-LF	PX80550A	3/4"	0.058	25	500
NP01R-LF	PX80560A	1 x 3/4"	0.093	15	120
NP01-LF	PX80570A	1"	0.106	15	120
NP01R-LF	PX80590A	1 1/4 x 3/4"	0.095	10	80
NP01R-LF	PX80600X	1 1/4 x 1"	0.126	10	80
NP01-LF	PX80580E	1 1/4"	0.126	25	150

## ELBOWS

NP07-LF  
NP07R-LF



### ELBOWS

Figure No.	Material No.	Size	Weight	Bag Qty	Master Ctn Qty
NP07-LF	PX80631A	1/2"	0.0440	50	750
NP07R-LF	PX80640A	3/4 x 1/2" x 1/2"	0.1280	25	300
NP07-LF	PX80650A	3/4"	0.0820	25	300
NP07-LF	PX80660A	1"	0.1800	15	150
NP07-LF	PX80670E	1 1/4"	0.2730	10	100

## TEES

NP11-LF  
NP11R-LF



### Tees

Figure No.	Material No.	Size	Weight	Bag Qty	Master Ctn Qty
NP11-LF	PX80711A	1/2"	0.065	50	500
NP11R-LF	PX80720E	1/2 x 1/2" x 3/4"	0.150	25	250
NP11R-LF	PX80730A	3/4 x 1/2" x 1/2"	0.128	25	250
NP11R-LF	PX80740A	3/4 x 1/2" x 3/4"	0.102	25	250
NP11R-LF	PX80750A	3/4 x 3/4" x 1/2"	0.092	25	250
NP11-LF	PX80760A	3/4"	0.125	25	250
NP11R-LF	PX80800A	1 x 1 x 1/2"	0.130	15	120
NP11R-LF	PX80810A	1 x 1" x 3/4"	0.211	15	120
NP11-LF	PX80820X	1"	0.198	10	120
NP11-LF	PX80860X	1 1/4"	0.355	10	60
NP11R-LF	PX80880X	1 1/4" x 1" x 1"	0.289	10	60
NP11R-LF	PX80870E	1 1/4" x 1 1/4" x 1"	0.275	10	80

\*Weighted average lead content ≤ 0.25%

Visit our website for the most current information.



# METAL INSERT FITTINGS FOR PEX AND PE-RT LEAD-FREE\* PERFORMANCE BRONZE®

## ADAPTERS

### NP22F-LF



#### SWEAT ELBOW ADAPTERS\*\*

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP22F-LF	PX81030E	3/4" x 3/4" Female Sweat Elbow Adapter	0.1080	10	50

### NP23-LF



#### MALE SWEAT ADAPTERS\*\*

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP23-LF	PX81070X	1/2" x 1/2" Male Sweat Adapter	0.032	50	500
NP23-LF	PX81090A	3/4" x 3/4" Male Sweat Adapter	0.064	25	250
NP23-LF	PX81100A	1" x 1" Male Sweat Adapter	0.116	15	120

### NP23F-LF



#### FEMALE SWEAT ADAPTERS\*\*

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP23F-LF	PX81121A	1/2" x 1/2" Female Sweat Adapter	0.032	25	500
NP23F-LF	PX01676X	1/2" x 3/4" Female Sweat Adapter	0.084	50	500
NP23F-LF	PX81130A	3/4" x 3/4" Female Sweat Adapter	0.062	25	250
NP23F-LF	PX81140X	1" x 1" Female Sweat Adapter	0.145	15	120

### NP25B-LF



#### MIP ADAPTERS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP25B-LF	PX81180X	3/8" x 1/2" MIP Brass Adapter	0.080	25	500
NP25B-LF	PX81190X	1/2" x 1/2" MIP Brass Adapter	0.081	50	500
NP25B-LF	PX81200X	1/2" x 3/4" MIP Brass Adapter	0.130	25	250
NP25B-LF	PX81210A	3/4" x 1/2" MIP Brass Adapter	0.087	25	250
NP25B-LF	PX81220X	3/4" x 3/4" MIP Brass Adapter	0.151	10	300
NP25B-LF	PX81250E	3/4" x 1" MIP Brass Adapter	0.209	25	200
NP25B-LF	PX81240A	1" x 3/4" MIP Brass Adapter	0.137	15	120
NP25B-LF	PX81260A	1" x 1" MIP Brass Adapter	0.242	15	120

\*Weighted average lead content ≤ 0.25%

\*\* For solder only, do not Press

Visit our website for the most current information.

# METAL INSERT FITTINGS FOR PEX AND PE-RT LEAD-FREE\* PERFORMANCE BRONZE®

## ADAPTERS

### NP25BE-LF



### MIP ELBOWS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP25BE-LF	PX81500X	1/2" x 1/2" MIP Elbow	0.1840	50	250
NP25BE-LF	PX81502A	3/4" x 1/2" MIP Elbow	0.1900	25	250

### NP26BS-LF



### SWIVEL ADAPTERS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP26BS-LF	PX81340A	1/2" x 3/4" NPSM Swivel Adapter - Brass Nut	0.170	25	50
NP26BS-LF	PX81360A	3/4" x 3/4" NPSM Swivel Adapter - Brass Nut	0.150	25	250

### NP26PS-LF NP44-LF



### FAUCET AND SWIVEL ADAPTERS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP26PS-LF	PX81330A	3/8" x Faucet Swivel Adapter - Plastic Nut	0.044	25	50
NP26PS-LF	PX02345A	1/2" x Faucet Swivel Adapter - Plastic Nut	0.048	50	500
NP44-LF	PX81380A	1/2" x Closet Swivel Adapter - Plastic Nut	0.062	10	50

### NP27P-LF



### FAUCET ELBOWS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP27P-LF	PX02245A	1/2 x 1/2" NPSM Faucet Elbow (Plastic Nut)	0.091	50	250

NOTE: Faucet and Swivel Adapters are to be hand tightened ONLY.

### NP26BE-LF



### FEMALE ELBOW NON-SWIVEL ADAPTERS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP26BE-LF	PX81317X	1/2 x 3/4 FIP Elbow Non-Swivel Adapter	0.1610	25	200

\*Weighted average lead content ≤ 0.25%

Visit our website for the most current information.

# METAL INSERT FITTINGS FOR PEX AND PE-RT LEAD-FREE\* PERFORMANCE BRONZE®

## ADAPTERS

### NP26B-LF



### FIP NON-SWIVEL ADAPTERS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP26B-LF	PX81271A	1/2" x 1/2" FIP Non-Swivel Adapter	0.1200	25	100
NP26B-LF	PX81280X	1/2" x 3/4" FIP Non-Swivel Adapter	0.1320	25	250
NP26B-LF	PX81285X	3/4" x 1/2" FIP Non-Swivel Adapter	0.1320	25	250
NP26B-LF	PX81300X	3/4" x 3/4" FIP Non-Swivel Adapter	0.1450	25	250
NP28B-LF	PX81305X	3/4" x 1" FIP Non-Swivel Adapter	0.1500	15	120
NP26B-LF	PX81310A	1" x 1" FIP Non-Swivel Adapter	0.2280	15	120
NP26B-LF	PX81313E	1 1/4" x 1" FIP Non-Swivel Adapter	0.2290	10	60

## MISCELLANEOUS FITTINGS

### NP18-LF



### PLUGS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP18-LF	PX81450A	1/2"	0.023	50	1,500
NP18-LF	PX81460A	3/4"	0.046	25	1,000
NP18-LF	PX81480E	1"	0.066	15	120
NP18-LF	PX81470E	1 1/4"	0.071	15	120

### NP28-LF



### FIP DROP EAR ELBOWS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP28-LF	PX81400A	1/2" x 1/2" FIP Drop Ear Elbow	0.1780	25	200
NP28-LF	PX81420E	3/4" x 3/4" FIP Drop Ear Elbow	0.2870	25	100

### NP29R-LF



### POLYBUTYLENE TRANSITION FITTINGS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP29R-LF	PX02283A	1/2" x 1/2" PB Transition Fitting w/Rings	0.0500	25	250
NP29R-LF	PX02293A	3/4" x 3/4" PB Transition Fitting w/ Rings	0.1000	25	100

*Kit includes fitting, PEX/PE-RT crimp ring, PB crimp ring*

\*Weighted average lead content ≤ 0.25%

Visit our website for the most current information.

# PLASTIC INSERT FITTINGS

POTABLE WATER - NOT FOR RADIANT HEAT USE

## NPD01 NPD01R



### POLY COUPLINGS

Figure No.	Material No.	Size	Weight	Bag Qty	Master Ctn Qty
NPD01	PX00508C	3/8"	0.0070	50	2,500
NPD01R	PX00518C	1/2" x 3/8"	0.0070	50	2,000
NPD01	PX00528C	1/2"	0.0070	50	2,000
NPD01R	PX00538G	3/4" x 1/2"	0.0100	50	1,200
NPD01	PX00548G	3/4"	0.0100	50	500
NPD01R	PX00558C	3/4" x 1"	0.0200	25	500
NPD01	PX00578C	1"	0.0200	25	500

## NPD07 NPD07R



### POLY ELBOWS

Figure No.	Material No.	Size	Weight	Bag Qty	Master Ctn Qty
NPD07	PX00588C	1/2"	0.0100	50	500
NPD07R	PX00598C	3/4" x 1/2"	0.0200	25	250
NPD07	PX00608C	3/4"	0.0210	25	600
NPD07R	PX00612C	1" x 3/4"	0.0370	25	250
NPD07	PX00618C	1"	0.0500	25	250

## NPD11 NPD11R



### POLY TEES

Figure No.	Material No.	Size	Weight	Bag Qty	Master Ctn Qty
NPD11	PX00628C	3/8"	0.0160	25	1,200
NPD11	PX00638C	1/2"	0.0100	50	500
NPD11R	PX00648C	1/2" x 1/2" x 3/4"	0.0200	25	500
NPD11R	PX00658C	3/4" x 1/2" x 1/2"	0.0180	25	300
NPD11R	PX00668G	3/4" x 1/2" x 3/4"	0.0200	25	400
NPD11R	PX00678C	3/4" x 3/4" x 1/2"	0.0240	25	400
NPD11	PX00688C	3/4"	0.0300	25	300
NPD11R	PX00698C	3/4" x 3/4" x 1"	0.0500	25	300
NPD11R	PX00708C	1" x 3/4" x 3/4"	0.0500	25	250
NPD11R	PX00718C	1" x 3/4" x 1"	0.0500	25	200
NPD11R	PX00728G	1" x 1" x 1/2"	0.0400	25	250
NPD11R	PX00738C	1" x 1" x 3/4"	0.0500	25	250
NPD11	PX00748C	1"	0.0600	25	150

## PLUGS

### NP18P



### POLY PLUGS

Figure No.	Material No.	Size	Weight	Bag Qty	Master Ctn Qty
NP18P	PX01975C	3/8"	0.0060	20	3,000
NP18P	PX01980C	1/2"	0.0050	100	1,000
NP18P	PX01990C	3/4"	0.0130	100	1,000
NP18P	PX01995C	1"	0.1690	25	250

**Note:** If poly fittings come in contact with glues, chemicals, sealers, or solvents; they should be discarded.

Visit our website for the most current information.



# PLASTIC INSERT FITTINGS

POTABLE WATER - NOT FOR RADIANT HEAT USE

## NPD22



### MALE POLY ADAPTERS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NPD22	PX01758C	1/2" x 1/2" MIP Poly Adapter	0.0200	50	500
NPD22	PX01768G	3/4" x 3/4" MIP Poly Adapter	0.0200	25	400
NPD22	PX01778C	1/2" x 3/4" MIP Poly Adapter	0.0180	25	700
NPD22	PX01788C	3/4" x 1/2" MIP Poly Adapter	0.0180	25	600
NPD22	PX01798C	1" MIP Poly Adapter	0.0200	25	300

## NPD25BE



### MALE ELBOW POLY ADAPTERS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NPD25BE	PX01948C	1/2" X 3/8" MIP Poly Adapter Elbow	0.0180	25	900
NPD25BE	PX01958C	1/2" X 1/2" MIP Poly Adapter Elbow	0.0180	50	800
NPD25BE	PX01968C	3/4" x 1/2" MIP Poly Adapter Elbow	0.0180	25	500
NPD25BE	PX01978C	3/4" MIP Poly Adapter Elbow	0.0180	25	400
NPD25BE	PX01988C	1" X 3/4" MIP Poly Adapter Elbow	0.0180	25	500

## NPD26 NPD26E



### FEMALE POLY SWIVEL ADAPTERS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NPD26	PX01898C	3/4" x 3/4" NPSM Poly Swivel	0.0400	50	500
NPD26	PX02148C	3/8" x 1/2" NPSM Poly Swivel (Faucet)	0.0300	50	600
NPD26	PX01888C	1/2" x 1/2" NPSM Poly Swivel (Faucet)	0.0260	25	500
NPD26C	PX02358C	1/2" x 7/8" NPSM Poly Swivel (Closet/Ballcock)	0.0300	25	400
NPD26E	PX02248C	1/2" x 1/2" NPSM Poly Swivel Elbow (Faucet)	0.0300	10	500
NPD26E	PX02348C	3/4" x 3/4" NPSM Poly Swivel Elbow	0.0300	25	400

**Note:** If poly fittings come in contact with glues, chemicals, sealers, or solvents; they should be discarded.

Visit our website for the most current information.

# MULTIPORT TEES

POTABLE WATER - NOT FOR RADIANT HEAT USE

## NPDCMT



## MULTIPORT TEES - CLOSED

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NPDCMT102	PX30500	MULTIPORT TEE 3/4" 2-PORT CLOSED	0.036	10	100
NPDCMT103	PX30501	MULTIPORT TEE 3/4" 3-PORT CLOSED	0.054	10	100
NPDCMT104	PX30502	MULTIPORT TEE 3/4" 4-PORT CLOSED	0.072	10	100
NPDCMT106	PX30503	MULTIPORT TEE 1" 6-PORT CLOSED	0.143	10	100

## NPDOMT



## MULTIPORT TEES - OPEN

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NPDOMT102	PX30504	MULTIPORT TEE 3/4" 2-PORT OPEN	0.039	10	100
NPDOMT103	PX30505	MULTIPORT TEE 3/4" 3-PORT OPEN	0.058	10	100
NPDOMT104	PX30506	MULTIPORT TEE 3/4" 4-PORT OPEN	0.076	10	100
NPDOMT106	PX30507	MULTIPORT TEE 3/4" 6-PORT OPEN	0.112	10	100

# CONNECTIONS (CRIMP and SLEEVE)

## NP19



## COPPER CRIMP RINGS

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP19	PX80905	3/8" Copper Crimp Ring (black)	0.0110	25	250
NP19	PX80915	1/2" Copper Crimp Ring (black)	0.0130	100	1,000
NP19	PX80925	3/4" Copper Crimp Ring (black)	0.0170	50	500
NP19	PX80935	1" Copper Crimp Ring (black)	0.0220	50	250
NP19	PX80945	1-1/4" Copper Crimp Ring (black)	0.2530	25	250

## NP19CS



## COPPER CRIMP SLEEVES

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP19CS	PX80911	1/2" Copper Crimp Sleeve	0.019	50	600
NP19CS	PX80921	3/4" Copper Crimp Sleeve	0.028	50	500
NP19CS	PX80931	1" Copper Crimp Sleeve	0.031	50	250

## NP50



## STAINLESS STEEL SLEEVES

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP50	PX02110	1/2" SS Sleeve	0.0070	50	5,000
NP50	PX02120	3/4" SS Sleeve	0.0100	50	2,500
NP50	PX02130	1" SS Sleeve	0.0100	50	2,500

Visit our website for the most current information.

# VALVES

## PXCP400-LF, NPR50A-LF



## LEAD-FREE\* BALL VALVES

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
PXCP400-LF	PX01526X	1/2" Brass Ball Valve w/ LH	0.2500	18	18
PXCP400-LF	PX01546X	3/4" Brass Ball Valve w /LH	0.4100	12	12
PXCP400-LF	PX01566X	1" Brass Ball Valve w/ LH	0.5700	6	6
NPR50A-LF	PX10297X	1/2" Mini Brass Ball Valve	0.1500	10	100

## STRAIGHT STOP VALVES



Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP7160-LF	ND615L8	1/2" x 1/4" OD (Icemaker) Straight Stop	0.1530		5
7160-LF	ND618L6	Straight Supply Stop 1/2" x 3/8"OD	0.1520		10
7160PEX-LF	ND618L7	Straight Supply Stop 1/2" x 1/2"	0.1340		10
7160M-LF	ND618L5	1/2" x 1/2" Male Straight Supply Stop	0.1590		10

## ANGLE STOP VALVES



Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
7165-LF	ND615L9	1/2" x 1/4"OD (Icemaker) Angle Supply Stop	0.1650		5
7165-LF	ND619L6	Angle Supply Stop 1/2" x 3/8" OD	0.1640		10
7165PEX-LF	ND619L7	1/2" x Angle Stop	0.1480	5	200

## OTHER VALVES



Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP7170	PX01521E	1/2" x Hose Thread Valve	0.1500	10	150

Visit our website for the most current information.

## CRIMP & SLEEVE TOOLS



### CRIMP TOOLS - COMPACT (11") - N9

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP32S	PX02530	1/2" Compact Crimp Tool (No Gauge)	2.00	1	10
NP32C	PX02540	3/4" Compact Crimp Tool w/ Gauge	2.00	1	10

### CRIMP TOOLS - STANDARD (13") - N9

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP32CH	PX02532	1/2" Standard Crimp Tool w/ Gauge	3.00	1	10
NP32CH	PX02531	3/4" Standard Crimp Tool w/ Gauge	3.00	1	10
NP32CH	PX02533	1" Standard Crimp Tool w/ Gauge	3.25	1	10

### CRIMP TOOLS - LONG (15") - N9

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP32LH	PX02545	1-1/4" Long Handle Crimp Tool w/ Gauge (19")	6.00	1	10



### STAINLESS STEEL SLEEVE TOOLS - N9

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP52	PX01364C	1/2" SS Sleeve Tool (12")	3.00	1	16
NP52C	PX01365	1/2" Compact SS Sleeve Tool	2.00	1	10
NP52	PX01366C	3/4" SS Sleeve Tool (12")	4.00	1	16
NP52	PX01368	1" SS Sleeve Tool (12")	4.50	1	12

## TOOLS & ACCESSORIES

### NP34



### OTHER TOOLS & ACCESSORIES

Figure No.	Material No.	Description	Weight	Bag Qty	Master Ctn Qty
NP34	PX01384	3/8" - 1" Go/No Go Gauge	0.15	10	300

Visit our website for the most current information.



# MINI PRESSING TOOL JAWS AND ACCESSORIES

## MINI PRESS TOOL JAWS & ACCESSORIES

Figure No.	Material No.	Description	Weight	Box Qty
PCX-1M	R00215PCX	1/2" Crimp Jaw for PC-20M and PC-10M (Includes Gauge)	2.94	1
PCX-6M	R00240PCX	5/8" Crimp Jaw for PC-20M and PC-10M (Includes Gauge)	2.97	1
PCX-2M	R00220PCX	3/4" Crimp Jaw for PC-20M and PC-10M (Includes Gauge)	2.90	1
PCX-3M	R00230PCX	1" Crimp Jaw for PC-20M and PC-10M (Includes Gauge)	2.92	1
PCX-7M	R00250PCX	1-1/4" Crimp Jaw for PC-20M and PC-10M (Includes Gauge)	3.11	1
PC-4ML	R00245PC	18V, 1.3Ah Lithium-ion Battery for PC-20M	0.80	1
PC-7L	R00175PC	18V, 3.0Ah Lithium-ion Battery for PC-20M	1.30	1
PC-8L	R00187PC	110V Battery Charger for PC-4ML and PC-7L	2.20	1
PC-9L	R00195PC	AC Adapter for PC-20M	1.70	1
NP34	PX01388	Go/No Go Crimp Gauge (1/2", 3/4", 1")	0.85	1
NP34	PX01389	Go/No Go Crimp Gauge (5/8", 1-1/4")	0.85	1

**Note:** Please order R00213PC from our Press price sheet to obtain a tool, case, batteries and charger that is compatible with PEX jaws.



**PCX-1M**  
**PCX-2M**  
**PCX-3M**  
**PCX-6M**  
**PCX-7M**



**PC-7L**  
18V, 3.0 Ah  
Lithium-ion Battery



**PC-8L**  
110V Battery Charger



**PC-4M**  
9.6V, 1.3 Ah NiMH Battery



**PC-4ML**  
18V, 1.3 Ah  
Lithium-ion Battery



**PC-9L**  
AC Adapter



**PC-5M**  
120V Battery Charger

Visit our website for the most current information.

# NIBCO® Flexible Piping Systems Limited Warranty



## NIBCO INC. LIMITED WARRANTY Applicable to NIBCO Flexible Piping Systems

NIBCO INC. warrants each NIBCO flexible pipe fitting, manifold, transition fitting and valve under normal conditions, use and service in potable water and radiant heat systems (together the "NIBCO Products") to be free from defects in materials and workmanship under normal use, service, and maintenance in accordance with the product specifications (including, but not limited to installation recommendations) for a period of ten (10) years from the date of purchase. NIBCO warrants NIBCO associated flexible piping hardware and tools for a period of 90 days from the date of purchase when installed by a licensed professional contractor.

NIBCO will repair or replace – at its option and at no charge – NIBCO Products that have been determined by NIBCO, or an authorized representative or agent thereof, to have failed solely because of a defect in materials or workmanship under normal use, service, and maintenance during the warranty period. Replacements shall be shipped free of charge to the owner.

This limited warranty applies to all NIBCO Products installed, tested, applied, and used in accordance with NIBCO's approved and published recommendations and instructions.

This warranty does not cover any failure or damage for or caused by:

1. any product, parts, or systems which are not manufactured or sold by NIBCO;
2. any NIBCO Product which is used for purposes other than a purpose authorized by NIBCO;
3. any NIBCO Product not installed, tested, applied, used, or maintained in accordance with NIBCO's recommended installation guidelines and instructions;
4. any NIBCO Product not installed or used in accordance with applicable codes;
5. any damage caused by, contributed in whole or in part by, or resulting from, any of the following:
  - a. abuse, misuse, mishandling, alteration, tampering, neglect, or accidental damage such as, without limitation, vandalism;
  - b. natural disasters, such as, without limitation, flooding, windstorm, and lightning;
  - c. attachments or modifications not authorized by NIBCO;
  - d. external, physical or chemical qualities, or an unsuitable or hostile environment;
  - e. any defects other than those in material or workmanship; or
  - f. any other cause beyond the control of NIBCO.

NIBCO DISCLAIMS ANY AND ALL LIABILITY FOR ANY OTHER DIRECT OR INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY KIND, INCLUDING BUT NOT LIMITED TO, ECONOMIC LOSS, LOSS OF BUSINESS, LOST PROFITS, PUNITIVE DAMAGES, MOLD INTRUSION, WATER DAMAGE, ETC.

Some states do not allow the exclusion or limitation of damages, so the above limitation or exclusion may not apply to you.

THIS WARRANTY IS THE ONLY WARRANTY FOR THE NIBCO PRODUCTS PROVIDED BY NIBCO, AND IS AND SHALL BE IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, AN IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND FOR ALL OTHER OBLIGATIONS OR LIABILITIES ON THE PART OF A MANUFACTURER. NO EMPLOYEE OF NIBCO, OR ANY OTHER DISTRIBUTOR, AGENT, OR OTHER PERSON OR BUSINESS, IS AUTHORIZED TO MAKE ANY OTHER WARRANTY ON BEHALF OF NIBCO.

Some states do not allow limitations on implied warranties, so the above limitation may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state and country to country.

In the event any defect occurs which is believed to be covered by this warranty, NIBCO Technical Services must immediately be contacted by calling 888.446.4226 or emailing CS-TechnicalServices@nibco.com. NIBCO Technical Services after being contacted will make further arrangements for the product's return to NIBCO. at the customer's expense for review and evaluation.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.



Visit our website for the most current information.



## Global Locations

### MANUFACTURING PLANTS

#### **Metal Fittings & Valves**

Blytheville, Arkansas

McAllen, Texas

Nacogdoches, Texas

Stuarts Draft, Virginia

Worcester, Massachusetts

#### **Plastic Pipe, Valves, & Fittings**

Goshen, Indiana

Greensboro, Georgia

#### **International**

Lodz, Poland

Reynosa, Mexico

### INTERNATIONAL OFFICES

#### **World Headquarters**

Elkhart, Indiana

#### **European Office**

Lodz, Poland

[VISIT OUR WEBSITE TO LEARN MORE](#)





# NIBCO®

NIBCO INC.  
WORLD HEADQUARTERS

1516 MIDDLEBURY STREET  
ELKHART, IN 46516-4740 USA  
WEB: [www.nibco.com](http://www.nibco.com)

DOMESTIC CUSTOMER SERVICE  
PHONE: 800.234.0227  
FAX: 800.234.0557

TECHNICAL SERVICE  
PHONE: 888.446.4226  
FAX: 888.336.4226

INTERNATIONAL OFFICE  
PHONE: +1/574.295.3327  
FAX: +1/574.295.3455