

SIMPLER AT EVERY STEP

# Why Choose Enkore



## **Wireless Convenience**

Locks and readers connect simply and securely to the network via Wi-Fi.



## **Centralized Tools**

Grant and audit access remotely. Run and manage everything from a single PC.



### **Dedicated Support Team**

Rely on our team of experts for setup, training, and ongoing support.



# **Deadbolt**

Programmable deadbolt lock for resident or tenant entry.

FINISH US15-619 Satin Nickel

DOOR THICKNESS 1-3/8" to 1-3/4"







exterior



# Interconnected

Programmable interconnected lock for resident or tenant entry.

FINISH US15-619 Satin Nickel

DOOR THICKNESS 1-3/8" to 1-3/4"



Suitable for offices and indoor or outdoor access. Set and audit access times.

FINISH US15-619 Satin Nickel

DOOR THICKNESS 1-3/8" to 1-3/4"





interior

exterior



WALL READERS

# **AMENITY ACCESS**

Ideal for common area access such as club houses, pool gates, fitness rooms, and other shared facilities. Enkore wall readers connect to the local network via Wi-Fi. Weather-resistant design for indoor or outdoor use. Available in Satin Nickel.



#### Secure

High-security authentication with 128-bit AES encryption.

#### **Weather Resistant**

All Enkore hardware is certified weather resistant for exterior use.

#### **Flexible Control**

Programmable time control. Grant or limit access by user, location, or time.

## **Tamper Proof**

Get real-time alerts when the lock is tampered with. Audit access times, locations, and credentials.

# System Features

- Retain a log of all lock events, each with its own date and time stamp
- Restrict or grant access to certain locks and users by time and day
- Auditory and software alerts when key cover is being tampered with
- Programm all locks via Wi-Fi using Enkore's robust management software
- Receive live alerts via e-mail for specified events
- Allow unrestricted access with Passage Mode
- Temporarily restrict all access with Privacy Mode
- · Visual and auditory low battery alerts

Specs	LOCKS	WALL READER
Certifications:	ANSI/BHMA Grade 2, ANSI 117.1 for ADA, IP55 Weatherproof, FCC	IP55 Weatherproof
UL Rating:	UL 10C (Deadbolt & Interconnected 90 mins; Leverset 20 mins)	
Latch:	Adjustable UL latch with 1-1/8" square corner faceplate	
Strike Plates:	1-1/8" × 2-3/4" square corner deadbolt strike, or lever T-strike	
Cylinder:	6-pin SC keyway standard, other options available	
Technologies:	Wi-Fi 802.11 b/g/n (2.4 GHz) WPA2, ISO/IEC 14443A, MIFARE DESFire EV1/EV2	
Frequency:	13.56 MHz MIFARE DESFire	
Encryption:	AES 128-bit Commercial-Grade Encryption	
Read Range:	1/2"	
Wi-Fi Range:	Up to 300 feet line of sight	
Power Supply:	4 AA Batteries	12/24 VDC 150 mA
Output Rating:		2A @ 28 VDC max
Op. Temp:	Interior: 15°F - 122°F, Exterior: -30°F - 150°F	
Event Log:	3,000 Entries	
Users:	6,000+ Keyfobs	
Warranties:	Lifetime Mechanical Warranty   1-Year Electronics Warranty   5-Year Finish Warranty	

# **Comparable Systems**

Schlage Control with Engage Cloud System, Kaba Saffire LX Series, Latch R & M Series

