

MCK Series

Mortise Cylinder Stations



MCK-1



MCK-4

Slimline or single gang mortise cylinder key switch stations. Choose between momentary action switch that remains active as long as it's depressed, or alternate action switch that alternates between open (disconnected) and closed (connected) each time it's pressed. Available with LED options.

Features

Standard Features

- Stainless steel wall plate accepts standard 1-1/8" mortise cylinder
- Tamper-proof and slotted-head screws included
- Mortise Cylinders not included, available separately (CY-1, CY-1A)

Options

- Momentary or alternate switch, see model chart
- SPDT or DPDT, see model chart
- No LED, green LED, green and red LEDs, see model chart
- Pneumatic timer: 2 to 45 seconds, see model chart
- Add **WP** for weather resistant cover and surface mount box. Available for single gang models only.

Specifications

Electrical

- Contacts rated 4A at 28 VDC
- LEDs operate on 12 or 24 VDC/VAC
- 6" red and black leads
- Switch depth behind plate: 1-1/4"
- Switches terminated in colored leads

Operating Temperature

- +15 to +120F [-9 to +49C]

Switch Type	1.75" Wide	1.75" Wide Green LED	1.75" Wide Green LED Red LED	Single Gang	Single Gang Green LED	Single Gang Green LED Red LED
SPDT Momentary Action	MCK-1	MCK-2	MCK-3	MCK-4*	MCK-5*	MCK-6*
SPDT Alternate Action	MCK-1-2	MCK-2-2	MCK-3-2	MCK-4-2*	MCK-5-2*	MCK-6-2*
DPDT Momentary Action	MCK-1-3	MCK-2-3	MCK-3-3	MCK-4-3*	MCK-5-3*	MCK-6-3*
DPDT Alternate Action	MCK-1-4	MCK-2-4	MCK-3-4	MCK-4-4*	MCK-5-4*	MCK-6-4*
Pneumatic Timer (2 to 45 seconds)	N/A	N/A	N/A	MCK-4-5*	MCK-5-5*	MCK-6-5*

*Weather resistant cover and surface mount back box available for single gang option only. Add "-WP" to model number for the weather resistant option.