



WALL SAFES

WALL SAFES

AMSEC **WALL SAFES** are designed to provide hidden protection for documents and miscellaneous valuables. Each wall safe is also designed for easy installation between 16" o/c wall studs. Pre-drilled anchor holes and a built-in flange eliminates unnecessary replastering.



WEST2114 FEATURES:

- Heavy duty steel body, 3/16" solid steel door and flange.
- Extra spacious interior, while still offering the convenience of fitting between studs.

WEST2114

- New State-of-the-art DL5000 electronic lock with a large 3 3/4" touch screen LCD input display allows smooth and easy operation.
- Mode altering display changes from orange in standby mode to bright blue in the open position.
- Accepts (2) user codes and can show open door records for the past 14 entries.
- LCD touch screen display shows low-battery indicator, time, date and keypad.
- Emergency key-lock override system with two (2) keys, power override battery box, built-in spy-proof function and motion detector alert.
- Dual live bolts ensure protection against pry attacks.
- Two removable shelves.
- Cream colored, durable powder coated finish.
- Packaged for UPS shipment.



WS1014

WS1014

FEATURES:

- U.L. listed Group II key changeable lock, with relock and 1 million possible combinations.
- Electronic lock optional.
- Flat dial allows flush mounted installation.
- 3/16" thick solid steel door with dead bar.



WS1214E5

HEAVY-DUTY WS1214E5

FEATURES:

- Same features as Super Brute Floor safes. Please see page 4.
- Two removable shelves. Extra deep interior.
- AMSEC's ESL5 electronic lock with illuminated keypad.



WFS149E5LP

When fire is a concern, there is no better wall safe than the WFS149 or WFS149E5LP.

WFS149

FEATURES:

- UL Listed one hour fire rating, ensuring the inside temperature never exceeded 350° F (paper chars at 450° F).
- Extra deep interior, with one (1) convenient drawer shelf.
- Combo lock with key operated side-locking mechanism incorporating one chromed locking bolt.
- Each safe is equipped with side locking boltwork mechanism incorporating 1/2" steel deadbolts.
- Impressive 1/2" thick door with attractive two-tone Sage finish.

WFS149E5LP with ESL5LP Electronic Lock:

- Illuminated Keypad
- Factory Reset Combination for resolving lost combinations without requiring expensive service calls.
- Beep and flash from every keystroke gives maximum feedback to the user.
- Lock can be programmed to silence the beep in stealth mode.
- 15-Minute Penalty Lockout after four incorrect entries protects against manipulation attempts.
- One 9-volt battery can be easily replaced in the keypad housing.

| Model | Inside Dimension H x W x D | Outside Dimension H x W x D | Clear Door H x W | Cu. In. | Wt. |
|--------------|-------------------------------|--------------------------------|---------------------|---------|-----|
| WS1014 | 10 x 13-3/4 x 3 1/2 | 12-1/4 x 15-3/4 x 4 | 9-5/8 x 12-3/4 | 481 | 20 |
| WFS149* | 14 x 8 1/2 x 10-5/8 | 19-1/8 x 13 1/2 x 15-3/4 | 14 x 8 1/2 | 1258 | 106 |
| WFS149E5LP * | 14 x 8 1/2 x 10-5/8 | 19-1/8 x 13 1/2 x 15-3/4 | 14 x 8 1/2 | 1258 | 106 |
| WS1214E5 | 12 x 13 1/2 x 5 1/2 | 12-5/8 x 14-1/8 x 10 | 10-3/4 x 11-1/8 | 891 | 86 |
| WEST2114 | 21-1/8 x 13-3/4 x 2-7/8 | 22-1/4 x 15 x 4 | 19-1/4 x 10-1/4 | 733 | 31 |

* 350° F, UL Listed, 1-Hr fire rated wall safe.