CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

PRODUCT CATALOG
2026 EDITION



CALIBRE DOOR CLOSERS, INC.

1481 North Main Street • Orange, California 92867
714-633-5100 • 800-560-0012
www.calibredoorclosers.com

Welcome to

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Calibre® is proud to introduce our company and the products we stand behind.

From the beginning, our mission has remained clear: to provide our customers with quality products that deliver dependable performance, reliable availability, and lasting value. While the industry has evolved, our commitment to doing business the right way has remained unchanged.

At Calibre, we believe strong companies are built on strong values. Those values guide our decisions, shape our culture, and define how we serve our customers every day. They influence the people we hire, the standards we uphold, and the long-term relationships we work to build. We understand that lasting partnerships are earned through consistency, integrity, and trust, and we take that responsibility seriously.

The name Calibre reflects exactly who we are. It represents distinction, quality, strength, and reliability. More than a name, it is a promise to stand behind our products, support our customers, and deliver solutions you can depend on today and into the future. When you choose Calibre, you are choosing a supplier committed to partnership, accountability, and long-term success.

We appreciate your interest in Calibre Door Closers and look forward to the opportunity to work with you.

Calibre Door Closers, Inc., 1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 - Toll Free: 800/560-0012 - FAX: 714/633-5102
Visit Calibre at www.calibredoorclosers.com

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Terms & Conditions

TERMS:	Standard C.O.D. With credit approval, Net 30 days from date of invoice.
PAYMENT POLICY:	Accounts with unpaid invoices exceeding 30 days may be placed on credit hold until past due amount is paid. If account balances exceed unpaid invoices over 60 days, open account status may be rescinded and C.O.D. terms will apply for subsequent invoices.
MINIMUM CHARGE:	A $25.00 NET charge applies.
RETURNED CHECKS:	A $30.00 bank NSF charge will be added for checks returned. Payment terms will be “Cash in Advance” thereafter.
PRICING:	All prices are subject to pricing prevailing at the date the order is received, and are subject to change and correction without notice. State and local taxes, if any, are to be the responsibility of the customer.
SHIPMENTS:	F.O.B. Our warehouse, and title passes to the purchaser while en route.
FREIGHT:	Freight will be prepaid on 300 pounds or more by the carrier of our choice within the continental United States. This excludes accessorial charges, i.e., residential delivery, oversize fee, lift gate charge, etc.
RETURNED GOODS:	A Returned Goods Authorization (RGA) must be issued before returning any material. Material thus returned shall be freight prepaid and subject to inspection with charges made for reconditioning as needed. A 25% re-stocking fee will be assessed on all non-defective returns.
ORDERS:	Accepted contingent upon strikes, fires, pandemics, delays of carriers, or other causes beyond the control of the Company.
CLAIMS:	All claims must be reported to the Company within ten (10) days of receipt of the merchandise. Please notify us promptly of any shipment or invoice discrepancy.

LIMITED WARRANTY

Effective May 1, 2006

Calibre® products purchased after May 1, 2006 are warranted by Calibre® Door Closers, Inc. to the original purchaser from the date of purchase in accordance with the following warranty schedule:

OVERHEAD CONCEALED DOOR CLOSERS .....5 Years
SURFACE APPLIED DOOR CLOSERS .....5 Years
DOOR HARDWARE PRODUCTS .....2 Years

Calibre® Products are warranted against defects in workmanship and/or material only. They will be replaced with brand-new products at no charge with return postage or freight prepaid by Calibre® Door Closers, Inc. No claims for damage incurred or work done thereon will be allowed, or for liability for incidental or consequential damages arising from defective parts, nor do we assume any responsibility for failure, breakage or cost which results from abuse, abnormal use, misuse, improper installation, negligence or accident.

This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Overhead Concealed Door Closers	Page 4 - 13
Surface Mounted Door Closers	Page 14 - 27
Storefront Door Hardware	Page 28 - 44
Panic Exit Devices	Page 45 - 50

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Standard Overhead Concealed Closers
Hydraulic Door Closers

CA1100 OHC Series



FEATURES

- Underwriters' Laboratories Inc. Listed for units without hold open feature. UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- **Center Hung Door Application :** Double or Single Acting (applied door stop renders unit Single Acting). Adjustable 'S' type side loading or 'A' type, 'K' type, and 'PT' type end loading arms are available for center pivoted door applications.
- **Offset Hung Door Application :** Single Acting Offset 'JO' and 'VO' type top arms are available for butt hung or offset pivoted applications.

DOOR CLOSER FUNCTIONS

- Built-in positive Back Stop and Hold-Open positions are available:

YKK-API H6200 Series (Unit Body Only)

Model Number	Function
1100-B-1130 **YKK-H6209**	105° Back Stop with Hold-Open
1100-B-1131 **YKK-H6210**	105° Back Stop -no Hold-Open
1100-B-1132 **YKK-H6211**	90° Back Stop with Hold-Open
1100-B-1133 **YKK H6212**	90° Back Stop -no Hold-Open

- Standard Fixed spring tensions available: **Medium**

  For optional ADA, Light, and Heavy spring tensions see CA2200 Series and CA6900 Series door closers.
- **Dual Speed Control Valves :** Closing and Latching speeds controlled by separate regulating valves, fully adjustable after installation.
- Adjustable CA3010-DP dual purpose radial ball-bearing bottom pivot set is provided for floor or threshold mounted (Side or End Loading) center pivoted installation. CA3010-G and CA3010-GE bottom pivot sets are optional, and must be ordered separately.
- Universal application. Non-handed for left or right door application.
- Installs in an aluminum storefront header or transom as small as 1-3/4" x 4"
- Positive cam centering for alignment and to hold door closed against normal wind or draft conditions.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.


Center Hung Doors : Complete units for aluminum doors and frames are furnished with top arm assembly ('S' side loading, 'A', 'K', or 'PT' end loading), adjustable dual purpose CA3010-DP bottom pivot set for floor or threshold mounting (side or end loading), and CA3010-FS anchor set with all fasteners.

'S' type side loading top arm, CA3010-DP adjustable dual purpose pivot set, and the CA3010-FS anchor set will be furnished unless otherwise specified by the customer.

'A' type, 'K' type or 'PT' type end loading, and 'JO' or 'VO' type offset arms are optional, but must be specified.

Offset Hung Doors : Complete units for offset pivoted or butt hung aluminum doors and frames are furnished with a 'JO' or 'VO' type offset arm and CA3010-FS anchor set with all fasteners. (Offset pivots or butt hinges not included. Note: Top Door Stop / Arm Cover by others).

CLOSER OVERVIEW (CA1100 SERIES)



COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

OHC CLOSER DOOR SIZE CHART AND SCHEDULE OF MODELS & TYPES

DOOR SIZE	SPRING TENSION	TYPE FUNCTION	"S" "A" "K" OR "PT" ARM	"JO" OR "VO" OFFSET ARM
From 31" to 41" X 96"	MEDIUM SPRINGS	105° Back Stop with Hold-Open	1130	1130 x JO or VO
		105° Back Stop -no Hold-Open	1131	1131 x JO or VO
		90° Back Stop with Hold-Open	1132	1132 x JO or VO
		90° Back Stop -no Hold-Open	1133	1133 x JO or VO

NOTE:
Doors of sizes over the schedule, or excessive weight, or doors subject to severe wind or draft conditions, or abusive usage, may require the next stronger spring tension model closer.

SPECIFY:
Door Closer Model Number and type of Top Arm, Anchor Set, and / or Bottom Pivot Set.

SPECIFY FINISH:
For CA3010-JO or the CA3020-VO Offset Arms:
AL - Aluminum
DU - Storefront Bronze

WARRANTY:
Refer to inside of the Catalog Front cover page.

CA1100 SERIES PARTS and ACCESSORIES

Description	Part Number
Unit Body Only (Specify: Spring Tension, Type & Function)	CA1100-B
"S" Type Side Loading Top Arm Assembly (1/2" Depth Top Rail)	CA3010-S
"A" Type End Loading Top Arm Assembly (1" Depth Top Rail)	CA3010-A
"K" Type End Loading Top Arm Assembly (5/8" Depth Top Rail)	CA3010-K
"PT" Type End Loading Top Arm Assembly (7/8" Depth Top Rail)	CA3010-PT
"JO" Type Offset Top Arm Assembly (Mortised Type, Cut down into 9/16" Depth Top Rail)	CA3010-JO
"VO" Type Offset Top Arm Assembly (Surface Type, Requires 7/8" Depth Top Rail)	CA3020-VO
Anchor Set (Standard - for Snap together Header)	CA3010-FS
Anchor Set (Optional - for Full tube Cut Away Header)	CA3010-FK
Corner Anchor Clip ("F" Clip Only)	CA3010-F
Adjustable Dual Purpose Bottom Pivot Set (Standard)	CA3010-DP
Adjustable Floor Mount Bottom Pivot Set (Optional)	CA3010-G
Adjustable Threshold Mount Bottom Pivot Set (Optional)	CA3010-GE

CA1100-B SERIES DOOR CLOSER COMPARISON CHART

Calibre® CA1100 Series	Global TC7000	Doromatic 100 Series	International 200 Series	Rixon 608	CRL 7000 Series	Ryobi 30 Series

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE
1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Overhead Concealed Closers
Hydraulic Door Closers

CA1100-20 OHC Series
Extended Spindle Closers



FEATURES


- For Use with Heavy Tempered All Glass Doors.
- Longer 3/4" (19.0 mm) Spindle for deeper Arm penetration and a more secure installation for added door support.
- Complies with ANSI A156.4-2008, and conforms to UL10C for positive pressure and UBC 7.2 (1997) BS476 for Fire Safety for units without hold-open feature.
- **Center Hung Door Application :**
  Double or Single Acting (applied door stop renders unit Single Acting). Adjustable 'A' type (CA3010-A) End Loading top arm assembly available for 1" depth, full length, top door rail.
- Optional adjustable shortened 'A' type (CA3010-A-MOD) End Loading top arm assembly available for shorter top door rail, and patch fitting applications.

DOOR CLOSER FUNCTIONS

- **Built-in positive Back Stop and Hold-Open positions are available :**
  105° Back Stop with Hold-Open
  105° Back Stop -no Hold-Open
  90° Back Stop with Hold-Open
  90° Back Stop -no Hold-Open
- Handicap (ADA) spring tension and opening force compliance may be better achieved by the use of the Calibre 3300-20 Series Adjustable Spring Tension door closers.
- **Standard Fixed Spring tensions available :**
  - **Medium (RD) Spring Tension**
  - **Heavy Spring Tension**
- **Dual Speed Control Valves :**
  Closing and Latching speeds controlled by separate regulating valves, fully adjustable after installation.
- Adjustable CA3010-DP Heavy Duty dual purpose radial ball-bearing bottom pivot set is provided for floor or for threshold mounted center pivoted installation.
- Universal application. Non-handed for left or right hand door application.
- Unit Body installs in an aluminum storefront header or transom as small as 1-3/4" x 4".
- Positive cam centering for alignment and to hold door closed against normal wind or draft conditions.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.

Center Hung Doors : Units may be purchased as Unit Body Only for retrofit and replacement applications. Complete units for All Glass Door application are furnished with CA3010-FS Standard Anchor Set, the CA3010-DP Bottom Pivot Set, and the CA3010-A End Load top arm assembly. The optional CA3010-A-MOD shortened End Load top arm assembly must be ordered separately.

CLOSER OVERVIEW (CA1100-20 SERIES)



COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

OHC CLOSER DOOR SIZE CHART AND SCHEDULE OF MODELS & TYPES

DOOR SIZE	SPRING TENSION	TYPE FUNCTION	MODEL NUMBER
From	Medium	105° Back Stop with Hold-Open	1130-20
31" to 41"	Medium	105° Back Stop -no Hold-Open	1131-20
X	Medium	90° Back Stop with Hold-Open	1132-20
96"	Medium	90° Back Stop -no Hold-Open	1133-20
From	Heavy	105° Back Stop with Hold-Open	1140-20
42" to 48"	Heavy	105° Back Stop -no Hold-Open	1141-20
X	Heavy	90° Back Stop with Hold-Open	1142-20
96"	Heavy	90° Back Stop -no Hold-Open	1143-20

NOTE:
Doors of sizes over the schedule, or excessive weight, or doors subject to severe wind or draft conditions, or abusive usage, may require the next stronger spring tension model closer.

SPECIFY:
Door Closer Model Number (see above), Unit Body Only, or Complete Closer Package.

WARRANTY:
Refer to inside of the Catalog Front cover page.

CA1100-20 SERIES PARTS and ACCESSORIES

Description		Part Number
Unit Body Only (Specify: Spring Tension, Type & Function)		CA1100-20
“A” Type End Loading Top Arm Assembly (1" Depth Top Rail)		CA3010-A
“A” Short Type End Loading Top Arm Assembly		CA3010-A-MOD
Anchor Set (Standard - for Snap together Header)		CA3010-FS
Anchor Set (Optional - for Full Tube Cut Away Header)		CA3010-FK
Corner Anchor Clip (“F” Clip Only)		CA3010-F
Adjustable Dual Purpose Bottom Pivot Set (Standard)		CA3010-DP

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Standard Overhead Concealed Closers
Hydraulic Door Closers

CA2200 OHC Series



FEATURES

- Underwriters' Laboratories Inc. Listed for units without hold open feature. UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- **Center Hung Door Application :**
  Double or Single Acting (applied door stop renders unit Single Acting). Adjustable 'S' type side loading or 'A' type, 'K' type, and 'PT' type end loading arms are available for center pivoted door applications.
- **Offset Hung Door Application :**
  Single Acting Offset 'JO' and 'VO' type top arms are available for butt hung or offset pivoted applications.

DOOR CLOSER FUNCTIONS

- Built-in positive Back Stop and Hold-Open positions are available:
  105° Back Stop with Hold-Open
  105° Back Stop -no Hold-Open
  90° Back Stop with Hold-Open
  90° Back Stop -no Hold-Open
- Handicap (ADA) spring tensions available for use on center pivoted door applications :

  5.0 lb. Opening Force (Center Hung door)
  8.5 lb. Opening Force (Center Hung door)
- Standard Fixed spring tensions available:
  Light
  Medium
  Heavy
- **Dual Speed Control Valves :**
  Closing and Latching speeds controlled by separate regulating valves, fully adjustable after installation.
- Adjustable CA3010-DP dual purpose radial ball-bearing bottom pivot set is provided for floor or threshold mounted (Side or End Loading) center pivoted installation. CA3010-G and CA3010-GE bottom pivot sets are optional, and must be ordered separately.
- Universal application. Non-handed for left or right door application.
- Installs in an aluminum storefront header or transom as small as 1-3/4" x 4"
- Positive cam centering for alignment and to hold door closed against normal wind or draft conditions.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.

ADA Opening Force Requirements
Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch the door.


Center Hung Doors : Complete units for aluminum doors and frames are furnished with top arm assembly ('S' side loading, 'A', 'K', or 'PT' end loading), adjustable dual purpose CA3010-DP bottom pivot set for floor or threshold mounting (side or end loading), and CA3010-FS anchor set with all fasteners.

'S' type side loading top arm, CA3010-DP adjustable dual purpose pivot set, and the CA3010-FS anchor set will be furnished unless otherwise specified by the customer.

'A' type, 'K' type or 'PT' type end loading, and 'JO' or 'VO' type offset arms are optional, but must be specified.

Offset Hung Doors : Complete units for offset pivoted or butt hung aluminum doors and frames are furnished with a 'JO' or 'VO' type offset arm and CA3010-FS anchor set with all fasteners. (Offset pivots or butt hinges not included. Note: Top Door Stop / Arm Cover by others).

CLOSER OVERVIEW (CA2200 SERIES)



COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

OHC CLOSER DOOR SIZE CHART AND SCHEDULE OF MODELS & TYPES

NOTE:
Doors of sizes over the schedule, or excessive weight, or doors subject to severe wind or draft conditions, or abusive usage, may require the next stronger spring tension model closer.

SPECIFY:
Door Closer Model Number and type of Top Arm, Anchor Set, and / or Bottom Pivot Set.

SPECIFY FINISH:
For CA3010-JO or the CA3020-VO Offset Arms:
AL - Aluminum
DU - Storefront Bronze

WARRANTY:
Refer to inside of the Catalog Front cover page.

DOOR SIZE	SPRING TENSION	TYPE FUNCTION	"S" "A" "K" OR "PT" ARM	"JO" OR "VO" OFFSET ARM
From 36" to 48" X 96"	ADA 5 lb. HANDICAP SPRINGS	105° Back Stop with Hold-Open	2200	N/A
		105° Back Stop -no Hold-Open	2201	N/A
		90° Back Stop with Hold-Open	2202	N/A
		90° Back Stop -no Hold-Open	2203	N/A
From 36" to 48" X 96"	ADA 8-1/2 lb. HANDICAP SPRINGS	105° Back Stop with Hold-Open	2210	N/A
		105° Back Stop -no Hold-Open	2211	N/A
		90° Back Stop with Hold-Open	2212	N/A
		90° Back Stop -no Hold-Open	2213	N/A
Up to 30" X 96"	LIGHT SPRINGS	105° Back Stop with Hold-Open	2220	2220 x JO or VO
		105° Back Stop -no Hold-Open	2221	2221 x JO or VO
		90° Back Stop with Hold-Open	2222	2222 x JO or VO
		90° Back Stop -no Hold-Open	2223	2223 x JO or VO
31" to 41" X 96"	MEDIUM SPRINGS	105° Back Stop with Hold-Open	2230	2230 x JO or VO
		105° Back Stop -no Hold-Open	2231	2231 x JO or VO
		90° Back Stop with Hold-Open	2232	2232 x JO or VO
		90° Back Stop -no Hold-Open	2233	2233 x JO or VO
42" to 48" X 96"	HEAVY SPRINGS	105° Back Stop with Hold-Open	2240	2240 x JO or VO
		105° Back Stop -no Hold-Open	2241	2241 x JO or VO
		90° Back Stop with Hold-Open	2242	2242 x JO or VO
		90° Back Stop -no Hold-Open	2243	2243 x JO or VO

CA2200 SERIES PARTS and ACCESSORIES

Description		Part Number
Unit Body Only (Specify: Spring Tension, Type & Function)		CA2200-B
"S" Type Side Loading Top Arm Assembly (1/2" Depth Top Rail)		CA3010-S
"A" Type End Loading Top Arm Assembly (1" Depth Top Rail)		CA3010-A
"K" Type End Loading Top Arm Assembly (5/8" Depth Top Rail)		CA3010-K
"PT" Type End Loading Top Arm Assembly (7/8" Depth Top Rail)		CA3010-PT
"JO" Type Offset Top Arm Assembly (Mortised Type, Cut down into 9/16" Depth Top Rail)		CA3010-JO
"VO" Type Offset Top Arm Assembly (Surface Type, Requires 7/8" Depth Top Rail)		CA3020-VO
Anchor Set (Standard - for Snap together Header)		CA3010-FS
Anchor Set (Optional - for Full tube Cut Away Header)		CA3010-FK
Corner Anchor Clip ("F" Clip Only)		CA3010-F
Adjustable Dual Purpose Bottom Pivot Set (Standard)		CA3010-DP
Adjustable Floor Mount Bottom Pivot Set (Optional)		CA3010-G
Adjustable Threshold Mount Bottom Pivot Set (Optional)		CA3010-GE

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Adjustable Spring Tension (ADA)
Overhead Concealed Closers
Hydraulic Door Closers

CA3300 OHC Series



FEATURES

- Handicap (ADA) multi-sized closers with adjustable spring power for a range of sizes after installation.
- Underwriters' Laboratories Inc. Listed for units without hold open feature. UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- **Center Hung Door Application :**
  Double or Single Acting (applied door stop renders unit Single Acting). Adjustable 'S' type side loading or 'A' type, 'K' type, and 'PT' type end loading arms are available for center pivoted door applications.
- **Offset Hung Door Application:**
  Single Acting Offset 'JO' and 'VO' type top arms are available for butt hung or offset pivoted applications. Note : Offset arm application geometry increases the effective spring tension in some instances thereby possibly exceeding the 5 lb. Opening Force requirements.

DOOR CLOSER FUNCTIONS

- **Built-in positive Back Stop and Hold-Open positions are available :**

Models CA3310, CA3311, CA3312, CA3313

105° Back Stop with Hold-Open
105° Back Stop -no Hold-Open
90° Back Stop with Hold-Open
90° Back Stop -no Hold-Open

- **Dual Speed Control Valves :**
  Closing and Latching speeds controlled by separate regulating valves, fully adjustable after installation.
- Adjustable CA3010-DP dual purpose radial ball-bearing bottom pivot set is provided for floor or threshold mounted (Side or End Loading) center pivoted installation. CA3010-G and CA3010-GE bottom pivot sets are optional, and must be ordered separately.
- Universal application. Non-handed for left or right door application.
- Installs in an aluminum storefront header or transom as small as 1-3/4" x 4"
- Positive cam centering for alignment and to hold door closed against normal wind or draft conditions.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.
- The 3300-20 Series is the standard 3300 Series OHC door closer assembled with an Extended Spindle Shaft (1/4" longer than standard).

Center Hung Doors : Complete units for aluminum doors and frames are furnished with top arm assembly ('S' side loading, 'A', 'K', or 'PT' end loading), adjustable dual purpose CA3010-DP bottom pivot set for floor or threshold mounting (side or end loading), and CA3010-FS anchor set with all fasteners.

'S' type side loading top arm, CA3010-DP adjustable dual purpose pivot set, and the CA3010-FS anchor set will be furnished unless otherwise specified by the customer.


'A' type, 'K' type or 'PT' type end loading, and 'JO' or 'VO' type offset arms are optional, but must be specified.

ADA Opening Force Requirements

Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch the door.

Offset Hung Doors : Complete units for offset pivoted or butt hung aluminum doors and frames are furnished with a 'JO' or 'VO' type offset arm and CA3010-FS anchor set with all fasteners. (Offset pivots or butt hinges not included. Note: Top Door Stop / Arm Cover by others).

CLOSER OVERVIEW (CA3300 SERIES)



COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

OHC CLOSER DOOR SIZE CHART AND SCHEDULE OF MODELS & TYPES

DOOR SIZE	SPRING TENSION	TYPE FUNCTION	"S" "A" "K" OR "PT" ARM	"JO" OR "VO" OFFSET ARM
From 36" to 48" X 96"	ADA 5 lb. HANDICAP SPRINGS	105° Back Stop with Hold-Open	3310	N/A
		105° Back Stop -no Hold-Open	3311	N/A
		90° Back Stop with Hold-Open	3312	N/A
		90° Back Stop -no Hold-Open	3313	N/A



NOTE:
Doors of sizes over the schedule, of excessive weight, or doors subject to severe wind or draft conditions, or abusive usage, refer to the CA2200 Series OHC door closers.

SPECIFY:
Door Closer Model Number and type of Top Arm, Anchor Set, and / or Bottom Pivot Set.

SPECIFY FINISH:
For CA3010-JO or the CA3020-VO Offset Arms:
AL - Aluminum
DU- Storefront Bronze

WARRANTY:
Refer to inside of the Catalog Front cover page.

CA3300 SERIES PARTS and ACCESSORIES

Description		Part Number
Unit Body Only (Specify: Spring Tension, Type & Function)		CA3300-B
Unit Body Only (Specify: Spring Tension, Type & Function) - Extended Spindle		CA3300-20-B
"S" Type Side Loading Top Arm Assembly (1/2" Depth Top Rail)		CA3010-S
"A" Type End Loading Top Arm Assembly (1" Depth Top Rail)		CA3010-A
"A" Type End Loading Top Arm Assembly (Shortened)		CA3010-A-MOD
"K" Type End Loading Top Arm Assembly (5/8" Depth Top Rail)		CA3010-K
"PT" Type End Loading Top Arm Assembly (7/8" Depth Top Rail)		CA3010-PT
"JO" Type Offset Top Arm Assembly (Mortised Type, Cut down into 9/16" Depth Top Rail)		CA3010-JO
"VO" Type Offset Top Arm Assembly (Surface Type, Requires 7/8" Depth Top Rail)		CA3020-VO
Anchor Set (Standard - for Snap together Header)		CA3010-FS
Anchor Set (Optional - for Full tube Cut Away Header)		CA3010-FK
Corner Anchor Clip ("F" Clip Only)		CA3010-F
Adjustable Dual Purpose Bottom Pivot Set (Standard)		CA3010-DP
Adjustable Floor Mount Bottom Pivot Set (Optional)		CA3010-G
Adjustable Threshold Mount Bottom Pivot Set (Optional)		CA3010-GE

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Overhead Concealed Closers
Hydraulic Door Closers

CA6900 OHC Series



FEATURES

- Independently tested and certified to Meet ANSI A156.4, Grade 1, exceeding the required 2,000,000 independent lab test cycles.
- **Center Hung Door Application :**
  Double or Single Acting (applied door stop renders unit Single Acting). Adjustable 'S' type side loading or 'A' type, 'K' type, and 'PT' type end loading arms are available for center pivoted door applications.
- **Offset Hung Door Application :**
  Single Acting Offset 'JO' and 'VO' type top arms are available for butt hung or offset pivoted applications.

DOOR CLOSER FUNCTIONS

- **Built-in positive Back Stop and Hold-Open positions are available :**
  105° Back Stop with Hold-Open
  105° Back Stop -no Hold-Open
  90° Back Stop with Hold-Open
- **Handicap (ADA) spring tensions available for use on center pivoted door applications :**

8-1/2 lb. Opening Force (Exterior Door)

ADA Opening Force Requirements

Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch the door.

- **Standard Fixed spring tensions available :**
  Light
  Medium
  Heavy
- **Dual Speed Control Valves :**
  Closing and Latching speeds controlled by separate regulating valves, fully adjustable after installation.
- Adjustable CA3010-DP dual purpose radial ball-bearing bottom pivot set is provided for floor or threshold mounted (Side or End Loading) center pivoted installation. CA3010-G and CA3010-GE bottom pivot sets are optional, and must be ordered separately.
- Universal application. Non-handed for left or right door application.
- Installs in an aluminum storefront header or transom as small as 1-3/4" x 4".
- Positive cam centering for alignment and to hold door closed against normal wind or draft conditions.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.


Center Hung Doors : Complete units for aluminum doors and frames are furnished with top arm assembly ('S' side loading, 'A', 'K', or 'PT' end loading), adjustable dual purpose CA3010-DP bottom pivot set for floor or threshold mounting (side or end loading), and CA3010-FS anchor set with all fasteners.

'S' type side loading top arm, CA3010-DP adjustable dual purpose pivot set, and the CA3010-FS anchor set will be furnished unless otherwise specified by the customer.

'A' type, 'K' type or 'PT' type end loading, and 'JO' or 'VO' type offset arms are optional, but must be specified.

Offset Hung Doors : Complete units for offset pivoted or butt hung aluminum doors and frames are furnished with a 'JO' or 'VO' type offset arm and CA3010-FS anchor set with all fasteners. (Offset pivots or butt hinges not included. Note: Top Door Stop / Arm Cover by others).

CLOSER OVERVIEW (CA6900 SERIES)



COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

OHC CLOSER DOOR SIZE CHART AND SCHEDULE OF MODELS & TYPES

DOOR SIZE	SPRING TENSION	TYPE FUNCTION	"S" "A" "K" OR "PT" ARM	"JO" OR "VO" OFFSET ARM
From 36" to 48" X 96"	ADA 8-1/2 lb. HANDICAP SPRINGS	105° Back Stop with Hold-Open 105° Back Stop -no Hold-Open 90° Back Stop with Hold-Open	6910 (050-923) 6911 (050-921) 6912 (050-922)	N/A N/A N/A
Up to 30" X 96"	LIGHT SPRINGS	105° Back Stop with Hold-Open 105° Back Stop -no Hold-Open 90° Back Stop with Hold-Open	6920 (050-926) 6921 (050-924) 6922 (050-925)	6920 x JO or VO 6921 x JO or VO 6922 x JO or VO
31" to 41" X 96"	MEDIUM SPRINGS	105° Back Stop with Hold-Open 105° Back Stop -no Hold-Open 90° Back Stop with Hold-Open	6930 (050-929) 6931 (050-927) 6932 (050-928)	6930 x JO or VO 6931 x JO or VO 6932 x JO or VO
42" to 48" X 96"	HEAVY SPRINGS	105° Back Stop with Hold-Open 105° Back Stop -no Hold-Open 90° Back Stop with Hold-Open	6940 (050-932) 6941 (050-930) 6942 (050-931)	6940 x JO or VO 6941 x JO or VO 6942 x JO or VO

NOTE:
Doors of sizes over the schedule, or excessive weight, or doors subject to severe wind or draft conditions, or abusive usage, may require the next stronger spring tension model closer.

SPECIFY:
Door Closer Model Number and type of Top Arm, Anchor Set, and / or Bottom Pivot Set.

SPECIFY FINISH:
For CA3010-JO or the CA3020-VO Offset Arms:
AL - Aluminum
DU - Storefront Bronze

WARRANTY:
Refer to inside of the Catalog Front cover page.

CA6900 SERIES PARTS and ACCESSORIES


Description		Part Number
Unit Body Only (Specify: Spring Tension, Type & Function)		CA6900-B
"S" Type Side Loading Top Arm Assembly (1/2" Depth Top Rail)		CA3010-S
"A" Type End Loading Top Arm Assembly (1" Depth Top Rail)		CA3010-A
"K" Type End Loading Top Arm Assembly (5/8" Depth Top Rail)		CA3010-K
"PT" Type End Loading Top Arm Assembly (7/8" Depth Top Rail)		CA3010-PT
"JO" Type Offset Top Arm Assembly (Mortised Type, Cut down into 9/16" Depth Top Rail)		CA3010-JO
"VO" Type Offset Top Arm Assembly (Surface Type, Requires 7/8" Depth Top Rail)		CA3020-VO
Anchor Set (Standard - for Snap together Header)		CA3010-FS
Anchor Set (Optional - for Full tube Cut - Away Header)		CA3010-FK
Corner Anchor Clip ("F" Clip Only)		CA3010-F
Adjustable Dual Purpose Bottom Pivot Set (Standard)		CA3010-DP
Adjustable Floor Mount Bottom Pivot Set (Optional)		CA3010-G
Adjustable Threshold Mount Bottom Pivot Set (Optional)		CA3010-GE

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Adjustable Spring Tension (ADA) Hydraulic Door Closers



CA1400 Series

FEATURES

- Complies with ANSI A156.4-2008 Grade 1 for Modern Types with Cover C02011, C02021, and C02041, and conforms with the Federal Accessibility Standards (ADA) and ANSI A117.1 (4, 13, 11).
- UL Listed for UL10C for positive pressure and UBC 7.2 (1997) BS476 and Fire Safety, and for use on “A” label fire doors.
- ADA (Handicapped) multi-sized closer with adjustable spring power for a range of sizes from 5 lbs. Opening Force to spring Size 5.
- Universally non-handed and Tri-Packed for Standard, Top Jamb, and Parallel Arm installations (Parallel Arm Bracket included).
- Retrofits existing LCN 1460/1461 Series and similar type door closer installations.
- **Dual Speed Control Valves :** Closing and Latching speeds controlled by separate Regulating valves, fully adjustable after installation.
- Specially formulated stable high viscosity door check fluid for climatic operation in extremes of heat and cold, high flash point, and provides for constant unit lubrication.
- Series 1400 includes a high impact PVC Dress Cover, wood, machine, and self tapping installation screws.
- TAA Compliant and Meets Buy America Act criteria and requirements.
- Attractive Baked Enamel finishes :

  AL - Aluminum
  DU - Storefront Bronze


DOOR CLOSER FUNCTIONS

CA1401...5 lb. Opening Force to Size 5.
Adjustable Spring power with fully adjustable Back-Check controlled by a separate regulating valve.

ADA Opening Force Requirements
Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch the door.


CLOSER OVERVIEW (Model CA1401)

A. Length of Closer w/ Cover	12-1/4"
B. Horizontal Mounting Holes	7-1/2”
C. Vertical Mounting Holes	1"
D. Overall Height	4-1/2"
E. Top of Door to Bottom of Closer	2-9/16"
F. Height of Closer	2"
G. Projection from Door	2-3/8"




COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

TYPICAL SURFACE MOUNTED DOOR CLOSER INSTALLATIONS (shown with Regular Forearms)




Standard Installation

Door closer mounted on the Door, on the PULL side. For installations on top Door Rails of less than 2-3/4", Drop Plate Part DP-1400-18 is required. Plate requires a 2" minimum height door rail.



Top Jamb Installation

Door closer mounted on the Header, on the PUSH side. For installations on top Door Headers of less than 1-3/4", Drop Plate Part DP-1400-18 may be required



Parallel Arm Installation

Door closer mounted on the Door, on the PUSH side. For installations on top Door Rails of less than 4-1/2", (as measured down from the door stop), Drop Plate Part DP-1400-18PA is required. Drop plate requires 2" minimum height door rail.

NOTE:
Doors of unusual height or weight, or doors subject to severe wind or draft conditions, or abusive usage, or stack pressure may require additional turns of the hex spring adjustment nut than is indicated on the installation instructions.

SPECIFY:
Closer Model or Part Number.

SPECIFY FINISH:
AL - Aluminum
DU - Storefront Bronze

SPECIFY HANDING:
Handing is not required for the CA1400 Series door closers or for the assemblies.

WARRANTY:
Please refer to the inside of the Catalog front cover page.

CA1400 SERIES PARTS and ACCESSORIES

Description		Part Number
PVC Slim Line Dress Cover		CA-DC-1400
Complete Regular Arm Assembly		CA-RA-1400
Parallel Arm Bracket		CA-PA-1400

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A. TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE



Adjustable Spring Tension (ADA) Hydraulic Door Closers

CA4000 Series

FEATURES

- Complies with ANSI A156.4 Grade 1.
- Barrier Free Operation to comply with Federal Accessibility Standards (ADA) and ANSI A117.1 (4,13,11).
- Underwriters' Laboratories Inc. Listed. Listed for UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- ADA (Handicap) multi-sized closer with adjustable spring tension for a range of sizes adjustable after installation from 5 lbs. of Opening Force to spring Size 6.

DOOR CLOSER FUNCTIONS

CA4001...5 lb. Opening Force to Size 6.
Adjustable spring power with fully adjustable Back-Check controlled by a separate regulating valve, adjustable after installation.

ADA Opening Force Requirements

Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch the door.


- **Dual Speed Control Valves** :
  Closing and Latching speeds controlled by separate regulating valves, adjustable after installation.
- Universal application. Non-handed for Standard, Top Jamb, or Parallel Arm installation (Parallel Arm Bracket included).
- Rack and pinion control mechanism contained in a high strength cast iron body for superior strength and durability.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.
- Furnished with regular arm. Hold-open arm (type 4300 & 4310 optional). Hold-open arms are adjustable from 100° to 180°of door opening.
- Series CA4000 includes high impact PVC Dress Cover, Sex nut and bolt set, blade stop spacer, and wood, machine, and self tapping installation screws.
- Attractive Baked Enamel finishes :
  AL - Aluminum
  DU - Storefront Bronze

CA4000 SERIES DOOR CLOSER COMPARISON CHART

Calibre® CA4000 Series	LCN 4040 / 4041	International 4400 / 4400CI	Cal Royal CR4041	Global TC4041	CRL PR90


CLOSER OVERVIEW (Model CA4001)

A. Length of Closer w/ Cover	12-1/4"
B. Horizontal Mounting Holes	Shown
C. Vertical Mounting Holes	2-1/4"
D. Overall Height	4-7/8"
E. Top of Door to Bottom of Closer	3-11/16"
F. Height of Closer	3-1/2"
G. Projection from Door	2-1/4"




COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

TYPICAL SURFACE MOUNTED DOOR CLOSER INSTALLATIONS (shown with Regular Forearms)




Standard Installation

Door closer mounted on the Door, on the PULL side. For installations on top Door Rails of less than 3-3/4", Drop Plate Part CA4018 is required. Plate requires a 2" minimum height door rail.



Top Jamb Installation

Door closer mounted on the Header, on the PUSH side. For installations on top Door Headers of less than 3-1/2", Drop Plate Part CA4018J is required. With the ceiling flush to top of header use Part CA4018G. Either Drop plate requires 1-3/4" minimum height header.



Parallel Arm Installation

Door closer mounted on the Door, on the PUSH side. For installations on top Door Rails of less than 5-1/2", (as measured down from the door stop), Drop Plate Part CA4018PA is required. Drop plate requires 2" minimum height door rail.

NOTE:
Doors of unusual height or weight, or doors subject to severe wind or draft conditions, or abusive usage, may require additional turns of the hex spring adjustment nut than is indicated on the installation instructions.

SPECIFY:
Closer Model or Part Number.

SPECIFY FINISH:
AL - Aluminum
DU - Storefront Bronze

SPECIFY HANDING:
Handing is not required for the CA4000 arm assemblies.

WARRANTY:
Please refer to the inside of the Catalog front cover page.

CA4000 SERIES PARTS and ACCESSORIES

Description		Part Number
PVC Dress Cover		CA-DC4000
Complete Standard Arm Assembly		CA2000
Hold-Open Arm Assembly - Mechanical Turn Type		CA4300
Hold-Open Arm Assembly - Friction Type		CA4310
Flat Drop Plate (For Door Application - see Top of Page)		CA4018
Flat Drop Plate (For Header Application - see Top of Page)		CA4018J
Flat Drop Plate (For Header Application - see Top of Page)		CA4018G
Flat Drop Plate (For Door Application - see Top of Page)		CA4018PA

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE



Adjustable Spring Tension (ADA) Hydraulic Door Closers

CA5500 Series

FEATURES

- Complies with ANSI A156.4 Grade 1.
- Barrier Free Operation to comply with Federal Accessibility Standards (ADA) and ANSI A117.1 (4,13,11).
- Underwriters' Laboratories Inc. Listed. Listed for UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- ADA (Handicap) multi-sized closer with adjustable spring tension for a range of sizes after installation :

DOOR CLOSER FUNCTIONS

CA5501...5 lb. Opening Force to Size 6. Adjustable spring power with fully adjustable Back-Check controlled by a separate regulating valve, adjustable after installation.

CA5502...5 lb. Opening Force to Size 6. Adjustable spring power with Delayed Closing Action controlled by a separate regulating valve, adjustable after installation.

ADA Opening Force Requirements


Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch the door.

- **Dual Speed Control Valves:** Closing and latching speeds controlled by separate regulating valves, adjustable after installation.
- Universal application. Non-handed for Standard, Top Jamb, or Parallel Arm installation.
- Rack and pinion mechanism contained in a high tensile precision die cast aluminum housing.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.
- Furnished with regular arm. Hold-open arms are optional. Hold-open arms are adjustable from 100° to 180° of door opening.
- Series CA5500 includes a high impact PVC Dress Cover, wood, machine, and self tapping installation screws. Parallel Bracket included.
- Optional Slim-Line PVC Dress Cover (Norton 8300 Type) and Pinion Cap are available.
- Attractive Baked Enamel finishes :

  AL - Aluminum
  DU - Storefront Bronze


CLOSER OVERVIEW (Models CA5501, and CA5502)

	With Cover	No Cover
A. Length of Closer	13"	12-11/16"
B. Horizontal Mounting Holes	12"	12"
C. Vertical Mounting Holes	3/4"	3/4"
D. Overall Height	5-1/8"	5-1/16"
E. Top of Door to Bottom of Closer	3-1/2"	3-7/16"
F. Height of Closer	3"	2-7/8"
G. Projection from Door	2-5/16"	2-3/16"




COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026


TYPICAL SURFACE MOUNTED DOOR CLOSER INSTALLATIONS (shown with Regular Forearms)



Standard Installation
Door closer mounted on the Door, on the PULL side.



Top Jamb Installation
Door closer mounted on the Header, on the PUSH side.



Parallel Arm Installation
Door closer mounted on the Door, on the PUSH side.

SPECIFY DOOR CLOSER MODEL WHEN ORDERING

	Back-Check	Delayed Closing	Function
Door Closers Model Number	5501	5502	Regular Forearm Application Parallel Arm Application

NOTE:
Doors of unusual height or weight, or doors subject to severe wind or draft conditions, or abusive usage, may require additional turns of the hex spring adjustment nut than is indicated on the installation instructions.

SPECIFY:
Closer Model or Part Number.

SPECIFY FINISH:
AL - Aluminum
DU - Storefront Bronze

SPECIFY HANDING:
Handing is not required for the CA5500 Series door closers or for the assemblies.

WARRANTY:
Please refer to the inside of the Catalog front cover page.

CA5500 SERIES PARTS and ACCESSORIES

Description	Part Number
Main Arm	CA620
Regular Forearm	CA521
Hold-Open Forearm	CA522
Top Jamb Forearm Extender	CA514
Parallel Bracket for Regular Forearm	CA525
Parallel Bracket for Hold-Open Forearm	CA526
Flat Drop Plate (for Door Application)	CA5507
Top Jamb Plate (for Header Application)	CA-TJB-5508
PVC Dress Cover (Full Norton 8500 Type)	CA-DC-5500
PVC Dress Cover (Slim-Line Norton 8300 Type)	CA-DC-6000
Thru Bolt and Grommet Nut (Set of 4 each)	CA-TGBN-50
Sex Nut and Bolt Set (1/4-20 x 1.75") (Set of 4 each)	CA-SNB-175

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Standard/Adjustable Back-Check Hydraulic Door Closers




CA6500/CA6800 Series

FEATURES

- Certified ANSI A156.4 Grade 1.
- Underwriters' Laboratories Inc. Listed. Listed for UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- Range of Sizes :
  Standard: CA6503, CA6504 and CA6505
  Back-Check: CA6803, CA6804 and CA6805
- **Dual Speed Control Valves** :
  Closing and Latching speeds controlled by separate regulating valves, fully adjustable after installation.
- CA6800 Series has adjustable Back-Check function controlled by a separate regulating valve, adjustable after installation.
- Universal application. Non-handed for Standard, Top Jamb, or Parallel Arm installation.
- Rack and pinion control mechanism contained in a high tensile precision die cast aluminum housing.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.
- Furnished with regular arm. Hold-open arms are optional. Hold-open arms are adjustable from 100° to 180° of door opening.
- CA6500/CA6800 door closers are contained in two body casting sizes. Spring size 3 contained in a Size 3 body casting, and spring sizes 4 and 5 are contained in a Size 4 body casting.
- Includes wood, machine, and self tapping installation screws.
- Attractive Baked Enamel finishes :
  AL - Aluminum
  DU - Storefront Bronze


CLOSER OVERVIEW (SERIES CA6500 and CA6800)

	Size 3	Size 4 & 5
A. Length of Closer	8-7/8"	9-13/16"
B. Horizontal Mounting Holes	8-3/16"	9-1/16"
C. Vertical Mounting Holes	3/4"	3/4"
D. Overall Height	4-21/32"	4-21/32"
E. Top of Door to Bottom of Closer	2-9/32"	2-9/32"
F. Height of Closer	1-25/32"	1-25/32"
G. Projection from Door	2-27/32"	2-27/32"




COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026


TYPICAL SURFACE MOUNTED DOOR CLOSER INSTALLATIONS (shown with Regular Forearms)



Standard Installation
Door closer mounted on the Door, on the PULL side.



Top Jamb Installation
Door closer mounted on the Header, on the PUSH side.



Parallel Arm Installation
Door closer mounted on the Door, on the PUSH side.

SPECIFY DOOR CLOSER MODEL WHEN ORDERING

INTERIOR Door size	EXTERIOR DOOR SIZE Swing Out	Swing In	MODEL NUMBER Standard	Back-Check	Function
42" 36"	36" 32"	32" 28"	#6503 #6503-P	#6803 #6803-P	Regular Forearm Application Parallel Arm Application
48" 42"	42" 36"	36" 32"	#6504 #6504-P	#6804 #6804-P	Regular Forearm Application Parallel Arm Application
54" 48"	48" 42"	42" 36"	#6505 #6505-P	#6805 #6805-P	Regular Forearm Application Parallel Arm Application

NOTE:
Doors of unusual height or weight, or doors subject to severe wind or draft conditions, or abusive usage, may require the next larger model door closer than the schedule.

SPECIFY:
Closer Model or Part Number.

SPECIFY FINISH:
AL - Aluminum
DU - Storefront Bronze

SPECIFY HANDING:
Handing is not required for the CA6500/6800 Series door closers or for the assemblies.

WARRANTY:
Please refer to the inside of Catalog front cover page.

CA6500 and CA6800 SERIES PARTS and ACCESSORIES

Description		Size	2 & 3	4 & 5
Main Arm		Part #	CA620	CA620
Regular Forearm		Part #	CA521	CA521
Hold-Open Forearm		Part #	CA522	CA522
Top Jamb Forearm Extender		Part #	CA514	CA514
Parallel Bracket Regular Arm		Part #	CA525	CA525
Parallel Bracket for Hold-Open Arm		Part #	CA526	CA526
Flat Drop Plate (Door)		Part #	CA537	CA547
Flat Drop Plate (Header)		Part #	CA-TJB-53	CA-TJB-54
Thru Bolt and Grommet Nut (Set of 4 each)		Part #	CA-TGBN-50	CA-TBGN-50
Sex Nut and Bolt Set (1/4-20 x 1.75") (Set of 4 each)		Part #	CA-SNB-175	CA-SNB-175

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Adjustable Spring Tension (ADA) Hydraulic Door Closers



CA8000 Series

FEATURES

- Complies with ANSI A156.4 Grade 1.
- Barrier Free Operation to comply with Federal Accessibility Standards (ADA) and ANSI A117.1 (4,13,11).
- Underwriters' Laboratories Inc. Listed. Listed for UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- ADA Handicap multi-sized closers with adjustable spring tension for a range of sizes after installation :

DOOR CLOSER FUNCTIONS

CA8001...5 lb. Opening Force to Size 4.
Adjustable spring power with fully adjustable Back-Check controlled by a separate regulating valve, adjustable after installation.

ADA Opening Force Requirements
Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch the door.


- **Dual Speed Control Valves :**
  Closing and Latching speeds controlled by separate regulating valves, fully adjustable after installation.
- Universal application. Non-handed for Standard, Top Jamb, or Parallel Arm installation.
- Rack and pinion control mechanism contained in a high tensile precision die cast aluminum housing.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.
- Furnished with regular arm. Hold-open arms are optional. Hold-open arms are adjustable from 100° to 180° of door opening.
- Series CA8000 has an available high impact PVC Dress Cover.
- Includes wood, machine, and self tapping installation screws
- Attractive Baked Enamel finishes :

  AL - Aluminum
  DU - Storefront Bronze

Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch


CLOSER OVERVIEW (CA8000 Series)

A. Length of Closer	9-3/4"
B. Horizontal Mounting Holes	9-1/16"
C. Vertical Mounting Holes	3/4"
D. Overall Height	4-21/32"
E. Top of Door to Bottom of Closer	2-1/16"
F. Height of Closer	1-3/4"
G. Projection from Door	2-29/32"




COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026


TYPICAL SURFACE MOUNTED DOOR CLOSER INSTALLATIONS (shown with Regular Forearms)



Standard Installation
Door closer mounted on the Door, on the PULL side.



Top Jamb Installation
Door closer mounted on the Header, on the PUSH side.



Parallel Arm Installation
Door closer mounted on the Door, on the PUSH side.

SPECIFY DOOR CLOSER MODEL WHEN ORDERING

	Back-Check		Function
Door Closers Model Number	8001 8001-P		Regular Forearm Application Parallel Arm Application

NOTE:
Doors of unusual height or weight, or doors subject to severe wind or draft conditions, or abusive usage, may require additional turns of the hex spring adjustment nut than is indicated on the installation instructions.

SPECIFY:
Closer Model or Part Number.

SPECIFY FINISH:
AL - Aluminum
DU- Storefront Bronze

SPECIFY HANDING:
Handing is not required for the CA8000 Series door closers or for the assemblies.

WARRANTY:
Please refer to the inside of the Catalog front cover page.

CA8000 SERIES PARTS and ACCESSORIES

Description		Part Number
Main Arm		CA620
Regular Forearm		CA521
Hold-Open Forearm		CA522
Top Jamb Forearm Extender		CA514
Parallel Bracket for Regular Forearm		CA525
Parallel Bracket for Hold-Open Forearm		CA526
Flat Drop Plate (for Door Application)		CA547
Top Jamb Plate (for Header Application)		CA-TJB-54
PVC Dress Cover		CA-DC-8000
Thru Bolt and Grommet Nut (Set of 4 each)		CA-TBGN-50
Sex Nut and Bolt Set (1/4-20 x 1.75") (Set of 4 each)		CA-SNB-175

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Standard/Adjustable Back-Check Hydraulic Door Closers



CA8850/CA8880 Series


FEATURES

- Complies with ANSI A156.4 Grade 1.
- Underwriters' Laboratories Inc. Listed. Listed for UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- Range of Sizes :
  Standard: CA8852, CA8853, CA8854 and CA8855
  Back-Check: CA8883, CA8884
- **Dual Speed Control Valves** :
  Closing and Latching speeds controlled by separate regulating valves, fully adjustable after installation.
- CA8800 Series has adjustable Back-Check function controlled by a separate regulating valve, fully adjustable after installation.
- Universal application. Non-handed for Standard, Top Jamb, or Parallel Arm installation.
- The CA8850 and CA8880 Series are "fixed" spring door closers with no spring power adjustment.
- Rack and pinion control mechanism contained in a high tensile precision die cast aluminum housing.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.
- Furnished with regular arm. Hold-open arms optional. Hold-open arms are adjustable from 100° to 180° of door opening.
- CA8850/CA8880 door closers are contained in three body casting sizes. Spring size 2 is contained in a Size 2 body casting, spring size 3 is contained in a Size 3 body casting, and spring sizes 4 and 5 are contained in a Size 4 body casting.
- Includes wood, machine, and self tapping installation screws
- Attractive Baked Enamel finishes:

  AL - Aluminum
  DU - Storefront Bronze


CLOSER OVERVIEW (SERIES CA8850 and CA8880)

	Size 2	Size 3	Size 4&5
A. Length of Closer	8-1/16"	8-7/8"	9-13/16"
B. Horizontal Mounting Holes	7-3/8"	8-3/16"	9-1/16"
C. Vertical Mounting Holes	3/4"	3/4"	3/4"
D. Overall Height	4-3/4"	4-3/4"	4-3/4"
E. Top of Door to Bottom of Closer	2-1/4"	2-1/4"	2-1/4"
F. Height of Closer			
G. Projection from Door	1-3/4"	1-3/4"	1-3/4"
	3"	3"	3"




COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026


TYPICAL SURFACE MOUNTED DOOR CLOSER INSTALLATIONS (shown with Regular Forearms)



Standard Installation
Door closer mounted on the Door, on the PULL side.



Top Jamb Installation
Door closer mounted on the Header, on the PUSH side.



Parallel Arm Installation
Door closer mounted on the Door, on the PUSH side.

SPECIFY DOOR CLOSER MODEL WHEN ORDERING

INTERIOR Door size	EXTERIOR DOOR SIZE Swing Out	Swing In	MODEL NUMBER Standard	Back-Check	Function
36"	32"	28"	#8852	n/a	Regular Forearm Application
32"	28"	24"	#8852-P	n/a	Parallel Arm Application
42"	36"	32"	#8853	#8883	Regular Forearm Application
36"	32"	28"	#8853-P	#8883-P	Parallel Arm Application
48"	42"	36"	#8854	#8884	Regular Forearm Application
42"	36"	32"	#8854-P	#8884-P	Parallel Arm Application
54"	48"	42"	#8855	n/a	Regular Forearm Application
48"	42"	36"	#8855-P	n/a	Parallel Arm Application

NOTE:
Doors of unusual height or weight, or doors subject to severe wind or draft conditions, or abusive usage, may require the next stronger spring tension model closer.

SPECIFY:
Closer Model or Part Number.

SPECIFY FINISH:
AL - Aluminum
DU - Storefront Bronze

SPECIFY HANDING:
Handing is not required for the CA8850/8880 Series door closers or for the assemblies.

WARRANTY:
Please refer to the inside of the Catalog front cover page.

CA8800 SERIES PARTS and ACCESSORIES

Description		Size	2	3	4 & 5
Main Arm		Part #	CA620	CA620	CA620
Regular Forearm		Part #	CA521	CA521	CA521
Hold-Open Forearm		Part #	CA522	CA522	CA522
Top Jamb Forearm Extender		Part #	CA514	CA514	CA514
Parallel Bracket Regular Arm		Part #	CA525	CA525	CA525
Parallel Bracket for Hold-Open Arm		Part #	CA526	CA526	CA526
Flat Drop Plate (Door)		Part #	CA527	CA537	CA547
Flat Drop Plate (Header)		Part #	n / a	CA-TJB-53	CA-TJB-54
Thru Bolt and Grommet Nut (Set of 4 each)		Part #	(All Door Closers P/N CA-TBGN-50)		
Sex Nut and Bolt Set (1/4-20 x 1.75") (set of 4 each)		Part #	(All Door Closers P/N CA-TBGN-50)		

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE
1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Adjustable Spring Tension (ADA) Hydraulic Door Closers



CA9900 Series

FEATURES

- Complies with ANSI A156.4 Grade 1.
- Barrier Free Operation to comply with Federal Accessibility Standards (ADA) and ANSI A117.1 (4,13,11).
- Underwriters' Laboratories Inc. Listed. Listed for UL10C for positive pressure and certified to conform to UBC 7.2 (1997) BS476 for Fire Safety.
- ADA Handicap multi-sized closers with adjustable spring tension for a range of sizes after installation:

DOOR CLOSER FUNCTIONS

CA9901...8 1/2 lb. Opening Force to Size 6. Adjustable spring power with fully adjustable Back-Check controlled by a separate regulating valve, adjustable after installation.

CA9903...5 lb. Opening Force to Size 4. Adjustable spring power with both adjustable Back-Check and adjustable Delayed Closing Action controlled by separate, regulating valves, adjustable after installation.

ADA Opening Force Requirements


Caution: Any manual door closer, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch the door.

- **Dual Speed Control Valves :** Closing and Latching speeds controlled by separate regulating valves, adjustable after installation.
- Universal application. Non-handed for Standard, Top Jamb, or Parallel Arm installation.
- Rack and pinion control mechanism contained in a high tensile precision die cast aluminum housing.
- Stable hydraulic door check fluid for any climatic operation and provides constant lubrication.
- Furnished with regular arm. Hold-open arms optional. Hold-open arms are adjustable from 100° to 180° of door opening.
- Series CA9900 includes a high impact PVC Dress Cover, wood, machine, and self tapping installation screws. Parallel Bracket included.
- Attractive Baked Enamel finishes :

  AL - Aluminum
  DU - Storefront Bronze


CLOSER OVERVIEW (Models CA9901 & CA9903)

A. Length of Closer	12-1/8"
B. Horizontal Mounting Holes	11-3/32"
C. Vertical Mounting Holes	3/4"
D. Overall Height	4-9/16"
E. Top of Door to Bottom of Closer	3-5/16"
F. Height of Closer	2-13/16"
G. Projection from Door	2-9/16"




COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026


TYPICAL SURFACE MOUNTED DOOR CLOSER INSTALLATIONS (shown with Regular Forearms)



Standard Installation
Door closer mounted on the Door, on the PULL side.



Top Jamb Installation
Door closer mounted on the Header, on the PUSH side.



Parallel Arm Installation
Door closer mounted on the Door, on the PUSH side.

SPECIFY DOOR CLOSER MODEL WHEN ORDERING

	Back-Check	Delayed Closing and/or Back-Check	Function
Door Closers Model Number	9901	9903	Regular Forearm Application or Parallel Arm Application

NOTE:
Doors of unusual height or weight, or doors subject to severe wind or draft conditions, or abusive usage, may require additional turns of the hex spring adjustment nut than is indicated on the installation instructions.

SPECIFY:
Closer Model or Part Number.

SPECIFY FINISH:
AL - Aluminum
DU- Storefront Bronze

SPECIFY HANDING:
Handing is not required for the CA9900 Series door closers or for the assemblies.

WARRANTY:
Please refer to the inside of the Catalog front cover page.

CA9900 SERIES PARTS and ACCESSORIES

Description		Part Number
Main Arm		CA620
Regular Forearm		CA521
Hold-Open Forearm		CA522
Top Jamb Forearm Extender		CA514
Parallel Bracket for Regular Forearm		CA525
Parallel Bracket for Hold-Open Forearm		CA526
Flat Drop Plate (for Door Application)		CA9907
Top Jamb Plate (for Header Application)		CA-TJB-9900
PVC Dress Cover		CA-DC-9900
Thru Bolt and Grommet Nut (Set of 4 each)		CA-TBGN-50
Sex Nut and Bolt Set (1/4-20 x 1.75") (Set of 4 each)		CA-SNB-175

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Glass and Aluminum Storefront Door Hardware Product

CA/Hardware Series

INTRODUCTION

The manufacturers of Calibre® hardware have been successfully producing storefront hardware since 1982. The manufacturers are ISO certified and have a proven record for quality and dependability throughout both the United States and Europe.

Calibre® storefront hardware is not unique, or exotic. Our storefront hardware is the “meat and potatoes” that has become the mainstay for the storefront industry. The people of Calibre® offer you 38-years of experience that will provide you the best possible quality and help you to better control your material costs.

Most of these hardware items have been widely used by the glass and aluminum storefront OEM manufacturers and glazing contractors throughout the U.S. for many years. Calibre® brings a new element to you, the customer, by assuring you Quality, Value & Service that you can trust and depend on.

The next time you are placing an order for your storefront hardware (or for your Door Closers), why not consider giving Calibre® an opportunity to prove to you that we can do it not only better, but perhaps even save you some money, and aggravation. Please give us a call.

GENERAL FEATURES

- Precision die cast A380 aluminum alloy is used for aluminum hardware castings.
- Quality, homogenized steel used for all steel stampings, for all locks, and security hardware product.
- All machining is performed with state of the art equipment for precision and uniformity throughout all phases of production.
- All painted surfaces are either baked enamel, or powder coating (depending on the product) for durability and long lasting finishes.
- Quality Control and Assurance is maintained throughout all phases of manufacturing, packaging, and periodically checked prior to shipments leaving our distribution center.
- Attractive Baked Enamel and Powder Coated finishes:

  AL - Aluminum
  BK - Black
  DU - Storefront Bronze

<< MS STOREFRONT LOCKS, FACEPLATES & CYLINDERS >>

LS-1000 - Long Throw Deadlock (Throw 1-3/8")
LS-2000 - Hook Bolt Deadlock (Throw 13/16")
LS-3000 - Short Throw Deadlock (Throw 13/16")

- Cylinder backsets available: 1-1/2", 1-1/8", and 31/32". (LS-3000: 1-1/8" Backset Only).
- Bolts made of 5-ply laminated steel with a hardened roller pin inserted in a case hardened center ply for maximum security.
- Locks use standard 1-5/32" Mortise Key or Thumbturn Cylinders with AR MS-Type cam.



Long Throw



Hook Bolt



Short Throw

COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

DEADLATCH LOCKS

LS-4000 - Deadlatch Lock
LS-5000 - Quick Change

- Cylinder backsets available: 1-1/8", and 31/32".
- Latchbolt has 1/2" throw, and is chrome plated with a Delrin insert for quiet latching.
- Lock is field reversible for opposite hand.
- Locks use standard 1-5/32" Mortise Key or Thumbturn Cylinders with AR MS-Type cam.
- Deadlatch Lock provides key controlled dogging.
- Standard ST-5000 Strike included (US 26D finish).



Specify: Cylinder Backset and Handing (if required)

LOCK FACEPLATES

- Faceplates measure 1" x 6-7/8", are ordered separately, and include faceplate screws.
- For Use With the following Locks:

LS-1000	Long Throw				
LS-2000	Hook Bolt.....				
LS-3000	Short Throw				
LS-4000	Deadlatch Lock				
LS-5000	Quick Change.....				

- Finishes available:
  - AL - Anodized Satin Aluminum
  - BK - Anodized Black
  - DU - Anodized Storefront Bronze



Flat	Radius	Radius Weatherstripped	Left Hand Beveled	Right Hand Beveled
FA-1001	**FA-1002**	**FA-1003**	**FA-1004**	**FA-1005**
FA-2001	**FA-2002**	**FA-2003**	**FA-2004**	**FA-2005**
FA-4001	**FA-4002**	**FA-4003**	**FA-4004**	**FA-4005**

Specify: Part Number and Finish

CYLINDERS

CL-1000 - Mortise Key Cylinder
DM-1000 - Mortise Dummy Cylinder
TH-1000 - Mortise Thumbturn Cylinder
RM-1000 - Rim Cylinder

- Zinc Die Cast cylinders, with core faces, keys, and thumbturn T-Turn US 26D. Cylinder faces (scalps) anodized aluminum.
- Mortise Key Cylinder and Mortise Thumbturn with AR MS-Type cam.
- Mortise Key Cylinder with Schlage “C” Keyway. Specify cylinder pairs as KA-2 or KA (keyed alike in maximum of 50 pairs each).
- Standard 3/16" cylinder trim ring furnished.
- Finishes available:
  - AL - Anodized Satin Aluminum
  - BK - Anodized Black
  - DU - Anodized Storefront Bronze

Mortise Key Cylinder



Mortise Dummy Cylinder



Mortise Thumbturn Cylinder



Rim Cylinder



Specify: Finish and KA-2 or KA (quantity)

CA/Hardware Series

<< SECURITY HARDWARE >>

CYLINDER GUARD SETS

GU-1000 - Cylinder Guard Set (w/ Retaining Clip)
GU-2000 - Cylinder Guard Set (Cylinder Secured Only)

- Security Ring is made from Hardened Steel.
- For use with Standard Face 5 pin Mortise Cylinder that fits into a free-spinning beveled collar.
- GU-1000 furnished with retaining clip and 2 spacers. High security with Security Ring fastened from inside of the door stile. GU-2000 held in place only by the mortise cylinder secured into the lock.
- Finishes (Powder Coated) available:
  AL - Aluminum
  BK - Black
  DU - Storefront Bronze



GU-1000



GU-2000

Specify: Part Number and Finish

HEADER BOLT SETS

BH-8500 - **Header Bolt Set**
For use in doors with the Centerline of the cylinder to the top of the door between 30-1/2" to 50".

BH-8600 - **Header Bolt Set**
For use in doors with the Centerline of the cylinder to the top of the door between 55-5/8" to 77-1/2".

BH-8700 - **Header Bolt Set**
For use in doors with the Centerline of the cylinder to the top of the door between 67" to 89".

BH-8800 - **Special Header Bolt Set** (Use in an Astragal Stile) Standard for 84" Doors with the Cylinder height not less than 33".

- Inactive leaf security when used with the **LS-1000** Long Throw Deadlock in the active leaf.
- BH-8500/8600/8700 have Expanding Bolt with 5/8" upward throw.
- Units come complete with Rod Guide and Header Strike.
- Simple adjustments can be made after installation.



BH-8500/8600/8700



BH-8800

Specify: Part Number


COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

THRESHOLD BOLT KITS

BT-6000 - Standard Threshold Bolt Kit
Standard for doors with cylinder heights between 34" to 37".

BT-5000 - Long Threshold Bolt Kit
Optional for doors with cylinder heights up to 53-1/2". The threaded rod portion can be cut for cylinder heights less than 53-1/2".

- Complete unit for attachment to basic Deadlock to provide maximum two-point lock security (at the lock jamb, and in the threshold).
- Unit provides 11/16" bolt throw when activated by the Deadlock.
- Furnished with a hardened steel hexagon Bottom Rod Bolt.
- Includes Top Rod Arm Adaptor, Bottom Rod Guide and Spring Roll Pin for installation into the Deadlock.



Specify: Part Number

<< DOOR HANDLES >>

LEVER HANDLE SETS

LH-4000 - Straight Lever Handle Set (LH or RH)
LH-4500 - Eurostyle Return End Lever Handle (LH or RH)

- For use with LS-4000 Deadlatch Lock. Includes field reversible Cam Plug.
- Lever portion baked enamel finish to resist scratching and chipping.
- Eurostyle Return End with 1/2" clearance for UBC anti-snag code requirements and Fire Safety.
- Finishes (Escutcheon) available:
  - AL - Painted Satin Aluminum
  - BK - Painted Black
  - DU - Painted Storefront Bronze



LH-4000



LH-4500

Specify: Part Number, Finish and Handling (if required)

PADDLE HANDLE SETS

PA-1000 - Paddle Handle Set (Push to the LEFT)
PA-2000 - Paddle Handle Set (Push to the RIGHT)

- For use with LS-4000 Deadlatch Lock. Includes field reversible Cam Plug.
- Complete unit is field reversible for either PUSH or PULL function, and for opposite handing with both PUSH and PULL Plates included.
- Extruded, anodized Aluminum paddle plate for long lasting wear and use.
- Finishes (Escutcheon Housing) available:
  - AL - Painted Satin Aluminum
  - DU - Painted Storefront Bronze



Specify: Part Number, Finish and Handling (if required)

Glass and Aluminum Storefront Door Hardware Product

CA/Hardware Series

<< STOREFRONT PIVOT SETS >>


OFFSET PIVOT SETS
(3/4" Offset for use with Aluminum Doors and Frames)

PV-1000 - For use on Flush Doors
PV-1500 - For use on 1/8" Recessed Doors
PV-3000 - For use on Flush Doors
PV-3500 - For use on 1/8" Recessed Doors
PV-4000 - For use on Flush Doors

PV-5000 - For use on 1/8" Recessed Doors (YKK Type) (includes Door Reinforcement Plates)
PV-6000 - For use on 7/64" Recessed Doors
PV-7000 - For use on 1/8" Recessed Doors (Kawneer 50-300 Type) (includes Door Reinforcement Plates)


- A380 aluminum alloy precision die cast pivot portions.
- Oilite bronze bushing in top frame pivot portion.
- Case hardened, spring loaded pin in Top Door pivot portion.
- Full race ball bearing in Bottom Door Pivot portion.
- Steel reinforcement plates for door portions provided with PV-5000 and PV-7000.
- Bottom Door pivot portion with 3/16" vertical height adjustment in the bearing with PV-5000 and PV-7000.
- Case hardened pivot stud in Floor/Jamb pivot portiond
- Floor/Jamb portion with 1/8" vertical height adjustment.
- Finishes available:
  AL - Satin Aluminum
  SL - Sanded and Lacquer (PV-4000 Only)
  BK - Black
  DU - Storefront Bronze

Specify: Part Number and Finish




PV-1000
(Flush Door)
J-27 Type

Non-Handed




PV-1500
(1/8" Recess)
J-28 Type

Non-Handed



PV-3001
(LH Flush Door)
J-30 Type

PV-3002
(RH Flush Door)
J-30 Type
(LH Shown)



PV-3501
(LH 1/8" Recess)
J-31 Type


PV-3502
(RH 1/8" Recess)
J-31 Type
(LH Shown)

COPYRIGHT CALIBRE DOOR CLOSERS, INC. 2026

OFFSET PIVOT SETS

(3/4" Offset for use with Aluminum Doors and Frames)

Specify: Part Number and Finish



PV-4001
(LH Flush Door)
J-34 Type

PV-4002
(RH Flush Door)
J-34 Type
(LH Shown)




PV-5001
(LH 1/8" Recess)
YKK Type

PV-5002
(RH 1/8" Recess)
YKK Type
(LH Shown)



PV-6001
(LH 7/64" Recess)
J-40 Type

PV-6002
(RH 7/64" Recess)
J-40 Type
(LH Shown)



PV-7001
(LH 1/8" Recess)
Kawneer Type


PV-7002
(RH 1/8" Recess)
Kawneer Type
(LH Shown)

REPLACEMENT OFFSET PIVOT SET

(3/4" Offset for use with Aluminum Doors and Frames)

PV-6890 - Non-handed Replacement Pivot Set

- Precision die cast for excellent tensile and shear strength.
- Radius in critical corners for additional fatigue strength.
- Full Race Ball Bearing in Bottom Bearing Housing.
- Non-handed for use in 1-3/4" Aluminum Storefront Doors.
- For use in doors weighing not more than 130 pounds.
- Standard Baked Enamel Finishes available:
  AL - Painted Satin Aluminum
  DU - Painted Storefront Bronze




Specify: Finish

KAWNEER OFFSET PIVOT SET

IN-50331 - KAWNEER 050331 INTERMEDIATE PIVOT

- Complies with ANSI A156.4 Grade 1.
- Non-handed, Reversible and adjustable.
- Standard Baked Enamel Finishes available:
  AL - Aluminum
  DU - Storefront Bronze
  BK - Black





IN-50331-BRACKET

Sold Separately

CA/Hardware Series

<< STOREFRONT PIVOT SETS >>

INTERMEDIATE PIVOT SET
(3/4" Offset for use with Aluminum Doors and Frames)

IN-1401S - LEFT Hand (HRSO)
IN-1402S - RIGHT Hand (HLSO)

- A380 Aluminum Alloy precision die cast.
- Combination Slotted Frame Portion (Handed) and Surface Applied Door Portion.
- For either Flush Door or 1/8" Recessed Door application.
- Standard Baked Enamel Finishes available:
  AL - Painted Satin Aluminum
  BK - Painted Black



Specify: Model Number and Finish

INTERMEDIATE PIVOT SETS
(3/4" Offset for use with Aluminum Doors and Frames)

IN-8001 - Mortise Type (LEFT Hand)
IN-8002 - Mortise Type (RIGHT Hand)

IN-9001 - Slotted Type (LEFT Hand)
IN-9002 - Slotted Type (RIGHT Hand)

- Full race ball bearing backed by an oilite bronze bushing in the Door Portion.
- Case hardened steel pin in Jamb Portion, fully retractable for ease of installation and easy vertical adjustment.
- IN-8000 - Precision A380 aluminum die cast.
- IN-9000 - Precision aluminum extrusion, or die cast.
- Standard Baked Enamel Finishes available:
  AL - Painted Satin Aluminum
  BK - Painted Black Paint
  DU - Painted Storefront Bronze




Specify: Model Number and Finish

CENTER HUNG PIVOTS (Walking Beam Pivots)
For use with Aluminum Doors and Frames

500-PF - Frame Portion (Mounting Holes Drilled & Tapped)
500-PF-1 - Frame Portion (Mounting Holes Drilled & Countersunk)
500-PD - Door Portion (Mates to the Frame Portion)
500-PC - Dress Plate (For use with the 500-PF-1 only)

- Finishes available (Dress Plate Only) :
  AL - Satin Aluminum
  DU - Storefront Bronze



500-PF
500-PF-1

500-PD

500-PC

Specify: Part Number and Finish

COPYRIGHT CALIBRE DOOR CLOSERS, INC. 2026

FLUSHBOLTS

FL-1002 -Standard Flushbolt, 1/8" Offset for use on a non-weatherstripped door stile. Standard 5/8" throw when activated. (**GREEN DOT**)
FL-1004 -Standard Flushbolt, 1/4" Offset for use on a weatherstripped door stile. Standard 5/8" throw when activated.(**RED DOT**)
FL-1006 -Standard Flushbolt, 3/16" Offset for special application as required. Standard 5/8" throw when activated.
FL-2002 -Optional Flushbolt, 1/8" Offset for use on a non-weatherstripped door stile. Optional 7/8" throw when activated.
FL-2004 -Optional Flushbolt, 1/4" Offset for use on a weatherstripped door stile. Optional 7/8" throw when activated.
FL-3001 -Special Kawneer Type Flushbolt, 1/8" Offset for use on a non-weatherstripped door stile. No Flushbolt Guide.

- Radius Flushbolt Face measuring 15/16" x 4-1/4".
- Positive “U” joint actuator for secure locking.
- Flushbolt Rod length for 12" Centerline of face Installation.
- Square Nylon Rod Tip with beveled corners fits in 1/2" round hole.
- Includes FG-1000 Standard Flushbolt Guide and screws.
- Finishes available:
  AL - Baked Satin Aluminum Paint
  BK - Baked Black Paint
  DU - Baked Storefront Bronze Paint



FL-1002



FL-1004

Specify: Part Number and Finish


FLUSHBOLT GUIDES

FG-1000 - Standard Flushbolt Rod Guide (White)
FG-2000 - Extended Hole Flushbolt Rod Guide (Brown)

- For use with FL-1000 and FL-2000 Flushbolts.
- Includes installation screws.



FG-1000



FG-2000

Specify: Finish for Screws

SPECIAL FLUSHBOLT RODS

RF-2000-RM - Special Flushbolt Rod with 1/2" solid round steel rod tip,measuring 1/4-20x12"



CA/Hardware Series

DOOR FORCE MEASURING GAUGE

DFG-1000 - Door Force Gauge



As set forth in Appendix A to Part 1191-1: Americans with Disabilities Act 1990 (ADA) Accessibility Guidelines for Buildings and Facilities, and further referenced in text ANSI A117.1 from the American National Standards Institute, requires that both interior and exterior doors of a building be handicapped accessible.

> **4.13.11 Door Opening Force.** The maximum force for pushing or pulling open a door shall be as follows:
>
> (1) Fire doors shall have the minimum opening force allowable by the appropriate administrative authority.
>
> (2) Other doors
> (a). exterior hinged doors: (Reserved requirement)
> (b). interior hinged doors: 5 lbs. (22.2N)

These forces do not apply to the force required to retract latch bolts or to disengage other devices that may hold the door in a closed position.

Some State and local municipalities may enforce guidelines that differ from the Federal guidelines. Furthermore, Building Code inspectors may have a different enforcement agenda to that of Health Code inspectors, and the Fire Marshall's code requirements. Contacting your State, County, or City Building Code Enforcement will best determine which code requirement is most applicable to your specific circumstances.

- Measures Door Opening and Closing Forces 0-35 lbs.
- Easy to use and accurate to within 1/4 1b. when used properly and in accordance with ANSI force measuring standards.

This Space was left intentionally Blank

COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

STRIKE SETS

ST-1000 - Strike Set, used for the new installation of a LS-4000 Type Deadlatch Lock in an Offset Door and Frame.
ST-2000 - Strike Set, used when replacing a MS Type Lock with a LS-4000 Type Deadlatch Lock on an Offset Door and Frame.
ST-4000 - Strike Sets, used for the new installation of a
ST-4500 - LS-4000 Type Deadlatch Lock in a Center Hung Door and Frame.
ST-5000 - Standard Flat Strike as furnished with the LS-4000 Deadlatch Lock.



ST-1000



ST-2000



ST-4000
ST-4500


- Non-handed Stainless Steel Strike for Left or Right Hand installation.
- Dustbox, Back-up Plate, and installation screws included.
- ST-4000 for use on a 4" Door Jamb, and the ST-4500 for use on a 4-1/2" Door Jamb.

Specify: Part Number

UNIVERSAL PULL-HANDLE

UH-1200 - Universal Multi-sized Offset Pull Handle

- Standard 12” CTC Offset Pull Handle with Press Fitting End Brackets.
- On site adjustment (cutting of stanchion) to match any existing installation centerline hole dimensions from 12” CTC to 4” CTC.
- Stanchion Bar is 6063 T5 extruded aluminum with a Class 1 anodized electrolytic finish.
- Press fitting End Brackets are a 380 aluminum die cast alloy with a high quality thermosetting polyester powder coated finish.
- Universal 1/4-20 fasteners are included for Thru-Bolt, Concealed, and Back-to-Back installations. Includes 2 each countersunk Trim Washers.
- Finishes available:
  AL - Aluminum with Black End Brackets




Specify: Part Number and Finish

STOREFRONT DOOR MODIFICATION KIT

GKL-B1-KIT - Narrow Stile Deadlock/Deadlatch Lock Fill Plates

The GKL-B1-Kit is used for closing the prepared openings of the Lock, Faceplate, and Cylinder holes in the door stile when the lock is removed for the installation of auxiliary hardware.

- GKL-B1-KIT includes (3) bridge supports and spacers for securing the blank faceplate into place.
- The bridge supports can be used to re-secure the lock into place should the tapped holes in the door stile strip out.
- Two cylinder hole caps provided which can be installed individually allowing space inside stile for CVR rod mechanism, or cylinder caps can be installed using double-ended 10-32 screw. Spanner Key (P/N GKL-SK1) ordered separately.
- Finishes available:
  AL - Painted Satin Aluminum
  DU - Painted Storefront Bronze



Specify: Part Number and Finish

CA/Hardware Series

<< MISCELLANEOUS HARDWARE >>

LOCK INDICATOR SET

LO-1000 - Standard lock Indicator Set.



Specify: Part Number and Finish

- Designed for use with the LS-1000, LS-2000 and LS-3000 type Deadlocks.
- "OPEN" in green and "LOCKED" in red letters on a white background.
- Includes the adhesive backed SI-2000 Header Sign "THESE DOORS TO REMAIN UNLOCKED WHENEVER THE BUILDING IS OCCUPIED".
- Includes all installation hardware (screws and pins).
- Finishes available:

  AL - Painted Satin Aluminum
  BK - Painted Black
  DU - Painted Storefront Bronze

DEADLATCH CAM PLUG

CP-1000 - Standard Cam Plug



- For use with the LH-4000 Lever Handle and the PA-1000/2000 Paddle Handle when installing into the LS-4000 Deadlatch Lock.
- Cam Plug is non-handed, field reversible.

COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

KICK DOWN DOOR STOP



DH-40 - 4" Kick Down Door Holder

- Solid Cast Iron construction.
- Non-marring Rubber Shoe, with replacement Rubber shoes available.
- Finishes available:
  AL - Painted Aluminum
  DU - Painted Storefront Bronze

Specify: Part Number and Finish

PUSH DOWN DOOR HOLDER



DH-70 - European Plunger Type Door Holder

- Heavy Duty Zinc Die Cast construction.
- Convenient foot activated step-on to lock or release holder mechanism.
- Non-skid rubber pad to hold door firmly in the open position.
- Holder has 1-1/4" Throw to accommodate most bottom door clearances.
- Finishes Available:
  AL - Painted Satin Aluminum
  DU - Painted Storefront Bronze

Specify: Part Number and Finish

<< SIGNAGE >>

TRANSOM HEADER SIGNS

SI-1000 - For use on a single door opening.
SI-2000 - For use on a pair of doors.
SI-3000 - For use on a single door opening.



SI-1000



SI-2000



SI-3000

- General purpose use on transoms and door headers.
- Attractive one piece, self-adhesive decals.
- Printed Black lettering on an aluminum background.

Specify: Part Number

CA/Hardware Series

<< PUSH BARS and PULL HANDLES >>

OFFSET & STRAIGHT PULL HANDLES

PH-2000 - Offset Pull Handle
PH-2002 - Offset Pull Handle Set
PH-1000 - Straight Pull Handle
PH-1002 - Straight Pull Handle Set

SINGLE BEND & DOUBLE BEND PUSH BARS

PB-1000 - Single Bend Push Bar

PB-2000 - Double Bend Push Bar

- 1" Diameter solid round aluminum extrusion, precision formed and machined.
- High performance architectural Class 1 anodized finishes for abusive use and UV protection.
- Product meets or exceeds AAMA 611-98 specifications.
- Offset Pull Handles with 3-1/4" offset, 2-1/4" projection, and 2-1/4" door clearance.
- Straight Pull Handles with 3" projection, and 2" door clearance.
- Push Bars with 2-1/4" projection.
- **Push Bars can be ordered with Pull Handles for a Push/Pull Set.** Specify Push/Pull combination use when ordering for correct mounting hardware package.
- Mounting hardware included. Specify Thru-Bolt or Concealed fasteners for individual Pull Handles. Push Bars are Concealed at the Lock Jamb and Thru-Bolt at the free ends. Push/Pull Set is Back-to-Back at the meet and Thru-Bolt at the free ends.
- Pull Handles CTC 9", 10" and 12". Push Bars are CTC 33-1/16" (for a 36" Door) and CTC 45-1/16" (for a 48" door)
- Polished Brass (US3) solid bent rod and Stainless Steel (US32 & US32D) solid bent rod finishes are available by special order.
- Finishes available:
  - AL - Anodized Aluminum
  - BK - Anodized Black
  - DU - Anodized Storefront Bronze



PH-2000



PH-2002



PH-1000



PH-1002



PB-1000



PB-2000



PP-1000



PP-2000



T1-Thru Bolt



T6-Concealed



T5-Back to Back



Type 15
Glass Door Thru-Bolt



Type 13
Glass Door Back to Back

COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026


>>FEATURES

HD Series

Offset Pivots
Intermediate Pivots

- HD Series heavy duty pivots meet or exceed BHMA/ANSI Grade 1.
- Full mortise with Heavy Duty Needle Bearings standard.
- Cast Brass Material (HD1170 Cast Brass and Steel).
- HDE1900 is non-load bearing with non-separable leaves.
- Industry standard installation templating. Furnished with 1/4-20 x 5/8" Flat Head Machine Screws.
- Standard finishes available: US26, US26D, US3, US4, US10, US10B. Optional finishes by special order.

HD1800
- Top Pivot Set
- Non-handed
- 3/4" Offset



HD1950
- Bottom Pivot Set
- Handed Set (LH -or- RH)
- 3/16" Vertical Adjustment
- 3/4" Offset



HD1170
- Bottom Pivot Set
- Non-handed
- 3/4" Vertical Adjustment
- 3/4" Offset



HD1950S
- Top & Bottom Pivot Set
- Handed Set (LH -or- RH)
- Jamb Mounted
- BHMA/ANSI C07131/3520




HD1170S
- Top & Bottom Pivot Set
- Non-handed
- Floor Mounted
- BHMA/ANSI C07162/3530A



HD1900
- Intermediate Pivot Set
- Handed (LH -or- RH)
- 3/4" Offset
- BHMA/ANSI C07321/3625



HDE1900
- Electrified Intermediate Pivot Set
- Handed (LH -or- RH)
- 3/4" Offset
- UL Listed wire #28 AWG, Rated 24 volts



NDC FLOOR HINGE & OVERHEAD CONCEALED DOOR CLOSER DEACTIVATION KIT

- Offered in 3/4" offset
- Retrofit center-hung, offset floor closers, and overhead concealed closers

NDC100
- Center hung
- Floor Mounted
- Retrofit, Rixson, MAB, Pittco, Doromatic, Dorma



NDC101
- 3/4" Offset
- Handed (LH -or- RH)
- Floor Mounted
- Retrofit, Rixson, MAB, Pittco, Doromatic, Dorma



NDC102EL
- Overhead Concealed
- End load arm type
- Retrofit, Rixson, Kawneer, Pittco, Jackson, Dorma



NDC102SL
- Overhead Concealed
- Side load arm type
- Handed (LH -or- RH)
- Retrofit, Rixson, Kawneer, Pittco, Jackson, Dorma




CA/Hardware Series


<< CONTINUOUS GEARED HINGE HARDWARE >>

SELECT HINGES™


SL11
- Concealed Hinge
- Flush Mounted
- For 1-3/4" Doors




SL24
- Concealed Hinge
- Door Edge Protector
- 1/16" Door Inset
- For 1-3/4" Doors



SL21
- Full Surface Hinge
- Swing Clear Function
- 1/32" Door Inset



SL57
- Full Surface Hinge
- Narrow (7/8") Frame Face
- Center Pivot Application
- 1/16" Door Inset



FEATURES

- UL Listed, Certified ANSI A156.25-2006 Grade 1 (25 million cycles), and Certified to 90-minute Fire Rated Standards.
- Manufactured from 6063 T6 aluminum alloy with thermoplastic polyester self-lubricating bearings fro extended wear.
- Hinge leaves are Pair-Matched Numbered during manufacturing to assure smooth functioning, and are completely anodized after matching for additional wear resistance and architectural inventory appearance.
- Full-length gears and channel covers prevent tampering for added security. Templated screw hole patterns allow easy preparation for precise fit and interchange if required.
- Non-handed hinge design prevents installation mistakes, and keeps inventory to a minimum.
- Standard finishes available: **CL** - Aluminum / **DU** - Storefront Bronze. Optional finishes by special order.
- Standard Hinge lengths available: 83", 95", and 120" (with 120" generally available by special order).

COPYRIGHT CALIBRE DOOR CLOSERS, INC. 2026

Continuous Gear Hinges

Cross Reference Sheet

Hinge Series	Calibre Select	Pemko	Roton	ABH
Full Concealed, Flush Mount	SL11	FMSLF	780-112	A110
Full Concealed, 1/8" Door Inset	SL18	FMSLI	780-111	A111
Full Concealed, 1/16" Door Inset	SL24	FM	780-224	A240
Full Surface, 1/32" Door Inset (Swing Clear)	SL21	FS	780-210	A210
Full Surface, 1/16" Door Inset (Narrow Frame)	SL57	FSCP	780-157	A570

How to Order Calibre / Select Hinges:

Example: SL57-83-DU-SD


SL57	Hinge Series (Full Surface, 1/16" Door Inset
83	Hinge Length (83", 95", and 120")
DU	Hinge Finish (CL Clear Aluminum, DU = Dark Bronze)
SD	Hinge Type (SD Standard Duty, HD = Heavy Duty)

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Glass and Aluminum Storefront Door Hardware Product

CA/Exit Devices

<< PANIC EXIT DEVICE HARDWARE >>




FEATURES

- Underwriters' Laboratories Inc. Listed - Panic Hardware.
- For use with Narrow, Medium, and Wide Stile Aluminum Doors.
- Non-Handed for LHRB or RHRB doors.
- Dogging by Cylinder Key or by slotted Dogging Screw in bottom of each Pad Assembly.
- Unit uses standard Mortise Cylinder with MS type Cam and Cylinder Mounting Pad with Locking Ring.
- Fits doors up to 48" in width (cut Cross Bar to fit).
- Unit installs using (2) 1/4-20 concealed Shoulder Studs.
- Anodized Aluminum Cross Bar.
- Finishes Available:
  AL - Aluminum
  DU - Storefront Bronze

CA7085 SERIES PARTS and ACCESSORIES

Description	Part Number
CVR Panic Exit Device (AL or DU)	CA7085-48
CVR Device with Mortise Cylinder and Mounting Pad	CA7085-2-48
Cylinder Mounting Pad (AL or DU)	CA-MP-6182
Top Rod Guide	CA7085 TOP GUIDE
Bottom Rod Guide	CA7085 BOTTOM GUIDE
Top Rod Bolt	CA7085 BTM ROD BOLT
Bottom Rod Bolt	CA7085 TOP ROD BOLT
Top Rod Trip Set (AL or DU)	CA7085 TRIP
CVR Panic Rod Extender (12" OR 24")	CA-RE-9100

COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026



FEATURES

- Underwriters' Laboratories Inc Listed - Panic Hardware.
- For use with Narrow, Medium, and Wide Stile Aluminum Doors.
- Handed - Specify for LHRB or RHRB door.
- Dogging by Cylinder Key or by slotted Dogging Screw in bottom of each Pad Assembly.
- Unit uses standard Rim type Cylinder.
- Latch Bolt throw 1/2".
- Includes standard 612 Roller Strike.
- Fits doors up to 48" in width (cut Cross Bar to fit).
- Unit installs using (2) 1/4-20 concealed Shoulder Studs.
- Anodized Aluminum Cross Bar
- Finishes Available:

  AL - Aluminum
  DU - Storefront Bronze

CA7095 SERIES PARTS and ACCESSORIES

Description	Part Number
Rim Panic Exit Device (AL or DU) (LH or RH Reverse Bevel) 	CA7095-48
Rim Panic Exit Device with Rim Cylinder  	CA7095-2-48
Rim Cylinder 	CA-RM-1000
Standard Roller Strike 	CA-ST612
Optional Roller Strike 	CA-ST614
7085/7095 Mounting Plate Set (AL or DU) 	CA-MP-622

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE


Glass and Aluminum Storefront Door Hardware Product

CA/Exit Devices

<< PANIC EXIT DEVICE HARDWARE >>

FEATURES

- Underwriters' Laboratories Inc. Listed - Panic Hardware.
- Conforms to ANSI A156.3-2001 Grade 2 (250,000 cycles).
- Requires a 2" mounting surface for typical use on Narrow, Medium, and Wide Stile Aluminum Doors.
- Field Reversible - For easy change to either LHRB or RHRB door applications.
- 9100 Series internal Rod Mechanism provides hardened steel Top and Bottom Rod Bolts for secure tamper-proof locking.
- Push Bar and Casing are 6063 hardened anodized aluminum with a steel Back Plate base.
- Outside Unlatching and Dogging by Mortise Cylinder Key, or Dogging by Hex Key (furnished) in the Touch Bar.
- Specify for 36" or 48" door width.
- Finishes available:
  AL - Aluminum
  DU - Storefront Bronze



CA9100 SERIES PARTS and ACCESSORIES


Description	Part Number
CVR Panic Exit Device (36" or 48") (AL or DU)	CA9100
CVR Device with Mortise Cylinder and Mounting Pad	CA9100-2
Cylinder Mounting Pad (AL or DU)	CA-MP-6182
Top Rod Guide	CA9100 TOP GUIDE
Bottom Rod Guide	CA9100 BOTTOM GUIDE
Top and Bottom Rod Bolt Set	CA9100 ROD BOLT SET
Header Strike Set (AL or DU)	CA9100 STRIKE
Top Rod Trip Set (AL or DU)	CA9100 TRIP
Dogging Assembly	CA-DOGGING ASSEMBLY
CVR Panic Rod Extender (12" OR 24")	CA-RE-9100

COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

<< PANIC EXIT DEVICE HARDWARE >>

FEATURES

- Underwriters' Laboratories Inc. Listed - Panic Hardware.
- Conforms to ANSI A156.3-2001 Grade 2 (250,000 cycles) for excellent security and durability for busy traffic conditions.
- Requires a 2" mounting surface for typical use on Narrow, Medium, and Wide Stile Aluminum Doors, or for use on Hollow Metal and Wood Doors.
- Non-Handed - For use on either LHRB or RHRB door applications.
- 9300 Series utilizes a 1" forged steel Latch Bolt with a 5/8" throw to engage the frame mounted Roller Strike.
- Push Bar and Casing are 6063 hardened anodized aluminum with a steel Back Plate base, and the metal End Caps are coated for an attractive, long lasting finish.
- Dogging by Hex Dogging Key (furnished) in the touch bar. Outside unlatching with standard external key Rim Cylinder.
- Specify for 36" or 48" door width.
- Finishes available:
  AL - Aluminum
  DU - Storefront Bronze



CA9300 SERIES PARTS and ACCESSORIES

Description	Part Number
Rim Panic Exit Device	CA9300
Rim Panic Exit Device with Rim Cylinder	CA9300-2
Rim Cylinder	CA-RM-1000
Standard Roller Strike	CA-ST612
Optional Roller Strike	CA- ST614
Dogging Assembly	CA-DOGGING ASSEMBLY


CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE
1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Glass and Aluminum Storefront Door Hardware Product

CA/Exit Devices

<< PANIC EXIT DEVICE HARDWARE >>



FEATURES

- Underwriters' Laboratories Inc. Listed-Panic Hardware
- For use with Narrow, Medium and Wide Stile Aluminum doors.
- Standard dogging with hex key (furnished) in the Push Bar mechanism.
- Unit used standard 1" Mortise Keyed Cylinder with standard AR Type cam (ordered separately).
- Available in standard sizes to accommodate 36" and 48" wide doors. Device can be field cut for smaller opening widths.
- Standard unit can be installed with Push Bar height adjustable from 30" to 44"
- Finishes Available:


  AL - Aluminum
  DU - Storefront Bronze

CA8086 SERIES PARTS and ACCESSORIES


Description	Part Number
AR Type CVR, Exit Only (36" or 48") (AL or DU)	CA8086
CVR Device with Mortise Cylinder and Mounting Pad	CA8086-2
Top Bolt Latch Assembly	CA8086-TBL
Top Bolt Strike	CA8086-TBS
Bottom Bolt Strike Assembly	CA8086-BBS
Bottom Rod Guide	CA8086-BBG
Cylinder Mounting Pad (AL or DU)	CA8086-CMEP
Hinge Stile End Cap	CA8086-HSEC
Lock Stile End Cap	CA8086-LSEC
Dogging Mechanism	CA8086-DM
Hex Dogging Key	CA8086-KEY

COPYRIGHT CALIBRE® DOOR CLOSERS, INC. 2026

8088 SERIES
NARROW STILE
RIM EXIT DEVICE



8080 MO SERIES
DUMMY DEVICE



Part No. 8080-MO-AL/DU

Narrow stile Dummy Push Bar Device with Latch Mechanism that can be retrofitted with a single signal switch for activation of ancillary door locking hardware (alarms, monitors, and maglocks).

FEATURES

- Underwriters' Laboratories Inc Listed - Panic Hardware.
- For use with Narrow, Medium, and Wide Stile Aluminum Doors.
- The 8088 Series Device is non-handed for either LHR or RHR Door Applications.
- Standard dogging with hex key (furnished) in Push Bar mechanism.
- 8088 Series Device is also available as a Dummy Exit Device
- Unit uses a standard Rim Cylinder for key access (ordered separately).
- Available in standard sizes to accommodate 36" and 48" wide doors. Device can be field cut for smaller opening widths.
- Standard unit can be installed with Push Bar height adjustable from 30" to 44"
- The 8088 Series easily lends itself to being retrofitted for electric operation
- Finishes Available:

  AL - Aluminum
  DU - Storefront Bronze

CA8088 SERIES PARTS and ACCESSORIES

Description	Part Number
AR Type Rim Device, Exit Only (36" or 48") (AL or DU)	CA8088
Rim Panic Exit Device with Rim Cylinder	CA8088-2
Dummy Exit Device	CA8080-MO
Hinge Stile End Cap	CA8088-HSEC
Lock Stile End Cap	CA8088-LSEC
Standard Strike Set	CA8088-STD-ST
Dogging Mechanism	CA8088-DM
Rim Cylinder	CA-RM-1000

CALIBRE DOOR CLOSERS & STOREFRONT HARDWARE

1481 North Main Street Orange, CA 92867-3403 U.S.A.
TEL: 714/633-5100 • Toll Free: 800/560-0012 • FAX: 714/633-5102

CALIBRE DOOR CLOSERS
& STOREFRONT HARDWARE

Thank You
For
Choosing

Calibre Door Closers, Inc.
1481 North Main Street Orange,
CA 92867-3403

Tel: 800-560-0012
Tel: 714-633-5100
Fax:714-633-5102

We encourage you to give us a call
to ask any questions, or

Visit us at our website:
www.calibredoorclosers.com
www.calibredoorclosersgov.com

COPYRIGHT CALIBRE DOOR CLOSERS, INC. 2026