ACCESSORI





# CM-45/46

# 41/2" SQUARE ALL-ACTIVE SWITCHES






CM-45/2

### **FEATURES**

- LARGE, EASY TO OPERATE SWITCHES
- ALL-ACTIVE DESIGN REQUIRES MINIMAL **ACTUATION FORCE**
- MEETS ADA REQUIREMENTS
- DURABLE STAINLESS STEEL OR SOLID **BRASS CONSTRUCTION**
- FLUSH MOUNT OR SURFACE MOUNT
- UL/CSA APPROVED SWITCH, RATED 15 AMPS @ 30V DC
- VARIOUS LOGOS & MESSAGES
- ARCHITECTURAL FINISHES

# DESCRIPTION



Both series mount to standard single gang or double gang electrical boxes. CM-45 series is sold as a complete assembly, which is mounted to the in-wall box (or surface box) using Allen screws and a hex key (included with the switch). Access to the mounting screws is through small holes in the front of the faceplate. This provides for tamper resistance, while maintaining an attractive overall appearance.

CM-46 series is sold as a two part assembly. The rear assembly is mounted to the in-wall box (or surface box). The front faceplate is then screwed to the rear assembly using either standard or snake-eye security screws (included with kit). This configuration allows for fast and easy installation by all trades.

The SPDT (and optional DPDT) switches are UL/CSA approved, and rated 15 amps @ 30 VDC. The push switches are offered with different logos, and in various architectural finishes. Weather resistant, and water tight configurations are also available.



CM-45/3

CM-46/4

## APPLICATION

Camden all-active switches are designed for areas where an easy-to-activate, high visibility switch is desired. Ideal for high-traffic areas, hospitals, wheelchair access, seniors' residences, etc. They can be surface or flush mounted.

Camden all-active switches are designed to control electric strikes, electromagnetic locks and automatic doors. They may also be used for shunting, bypassing alarms, request to exit, timed functions, and many other applications.

The switches are made for high frequency usage, in both indoor and outdoor environments. Camden switches are versatile, and can be supplied in various configurations and finishes, to suit any commercial, industrial, or residential application.

# 41/2" SQUARE ALL-ACTIVE SWITCHES

#### ARCHITECTS / ENGINEERS SPECIFICATIONS

The switches to be used throughout the complex shall be CAMDEN DOOR CONTROLS CM-45 or CM-46 series all-active switches.

The switches shall be easy-to-activate, ADA compliant, 4 1/2" square. Switches shall be all-active, whereby pressing any part of the faceplate will activate the device. Faceplates shall be constructed of 18-gauge stainless steel or solid brass. Switches shall use plastic spacers and rubber dampers for noise reduction. Switches shall be rated at a minimum of 15 amps @ 30V DC.

#### ORDERING INFORMATION

All CM-45/46 series all-active switches are complete ready-to-install assemblies. CM-45 series are supplied with stainless steel Allen screws and an Allen wrench for mounting. CM-46 series are supplied with stainless steel tamperproof screws.

MODEL	DESCRIPTION
	41/2" SQUARE - CONCEALED MOUNTING HOLES
CM-45/1	SQUARE STAINLESS STEEL PLATE, NO EMBOSSING
CM-45/2	EMBOSSED WITH WHEELCHAIR LOGO IN BLUE
CM-45/3	EMBOSSED WITH PUSH TO OPEN LOGO IN BLACK
CM-45/4	EMBOSSED WITH WHEELCHAIR LOGO AND PUSH TO OPEN LOGOS IN BLUE
CM-45/5	WHEELCHAIR LOGO, POUSSEZ POUR OUVRIR
CM-45/C	CUSTOM ENGRAVING, PLEASE SPECIFY WHEN ORDERING
	41/2" SQUARE - EXPOSED MOUNTING HOLES
CM-46/1	Square stainless steel plate, no embossing
CM-46/2	EMBOSSED WITH WHEELCHAIR LOGO IN BLUE
CM-46/3	EMBOSSED WITH PUSH TO OPEN LOGO IN BLACK
CM-46/4	EMBOSSED WITH WHEELCHAIR LOGO AND PUSH TO OPEN LOGOS IN BLUE
CM-46/C	CUSTOM ENGRAVING, PLEASE SPECIFY WHEN ORDERING

# 3 <sup>3</sup>/<sub>4</sub>" (95mm) . **2"** - (51mm) 3" (76mm) 3 1/4" (83mm) 4 ½" (114mm) |----<del>|</del> MOUNTING FOR TYPICAL DOUBLE GANG ELECTRICAL MOUNTING FOR TYPICAL SINGLE GANG ELECTRICAL

3/4" (19mm)

1/2"

(13mm)

CM-45/46

CM-45/46

#### **OPTIONS/FINISHES:**

- DP Add DP to product # to order DPDT switch instead of SPDT switch
- WR Add WR to product # for weather resistant boot
- W/T Add WT to product # for boot and water tight coating
- AL Add AL to product # for arrow left
- AR Add AR to product # for arrow right
- Add AB to product # for antique brass finish (US5/C5) - AB
- Add PB to product # for polished brass finish (US3/C3) - PB
- SB Add SB to product # for satin brass finish (US4/C4)
- OB Add OB to product # for oil rub bronze finish (US10B/C10B)
- MS Add MS to product # for mirrored stainless steel finish (US32/C32)



