



MGFT1-E

15 Amp SmartlockPro® GFCI Receptacle/Outlet, Industrial Grade, Tamper-Resistant, Lev-Lok

Lev-Lok SmartlockPro GFCI Duplex Receptacle Outlet, Extra Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Power Indication, 15 Amp, 20 Amp Feed-Through, 125 Volt, Modular (line) and Back or Side Wire (load), NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Black **Mating Lev-Lok Wiring Module Required for Use**

[Lev-Lok Savings Calculator](#)

Color :  Black

UPC Code : 078477724620

Country Of Origin : China

NEMA :  5-15R

Available Colors :



Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Electrical Specifications

Amperage : 15 A & 20 A Feed-Through

Feed-Through Current : 20 Amp

Grounding : Self-Grounding

Pole : 2

Short Circuit Current Rating : 2kA

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -35C to +66C

Material Specifications

Body Material : Polycarbonate

Face Material : PBT

Ground Clips : Brass

Line Contacts : Brass

Shutter Mechanism : Delrin® Acetal

Strap Material : Galvanized Steel

Terminal Clamp : Brass

Terminal Screws : Plated Steel

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Termination : Modular (line) and Back or Side Wire (load)

Product Features

Brand : SmartlockPro Lev-Lok

Color : Black

Device Type : Duplex Receptacle Outlet

Feature : Tamper-Resistant|Power Indication

Function : GFCI

Trip Level : Class A, 5mA plus
or minus 1mA

Grade : Extra Heavy-Duty
Industrial Specification Grade

NEMA : 5-15R

Standards and Certifications

ANSI : C-73

Applicable Standards : UL
943, UL 498, CSA C22.2 No.
42 & 144, FedSpec W-C-596

NEMA : WD-1 & WD-6

Patents *

CA2621644	CA2677283
MX302458	MX308495
US7355117	US7357652
US7666010	US7697252
US7820909	US7868719
US8096818	US8242362
US8587914	US8599522
US9053886	

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.