



GUSB1-W

15A SmartlockPro® GFCI Combination 24W(4.8A) Type A USB In-Wall Charger Outlet

15 Amp, 125 Volt Receptacle/Outlet, 20 Amp Feed-Through, Tamper-Resistant, SmartlockPro® Self-Test GFCI Combination Type A USB In-Wall Charger, Wire Leads, NEMA 5-15R, 24W (4.8 Amps), Dual Type-A/A USB Chargers, screws and self-grounding clip included - White

DISCONTINUED

Suggested Replacement SKUs: :

- SAFE - Delivers continuous ground fault protection, automatically self-tests to ensure it can respond to a ground fault
- FAST CHARGING - Smart chip technology provides over 2X the charging power of other GFCI USB outlets for a faster charge
- CODE REQUIRED - Fulfill NEC® requirements anywhere GFCI protection is needed
- SIMPLE - Status indicator light provides simple, intuitive feedback
- INSTALL - Requires extra deep wallbox for installation

Color :  White

UPC Code : 078477999967

Country Of Origin : China

NEMA :  5-15R

Available Colors :



Black



Light Almond

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Dielectric Voltage :

Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Environmental Specifications

Flammability : UL94, 5VA

Operating Temperature : -10° C to 40°C

Electrical Specifications

Grounding : Self-Grounding

Ratings : 15A - 125V, 4.8A @ 5V

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Voltage : 125 VAC

Material Specifications

Body Material : Thermoplastic

Color : White

Cover Material : Thermoplastic

Face Material : Thermoplastic

Grade : Residential /Commercial Specification Grade

Line Contacts : Brass Double Wipe .031 Thick

Product ID : Stamped on Strap

Strap Material : Galvanized Steel

Terminal ID : Green lead -
GND. Line and load both have:
Black lead - Hot, White lead -
Neutral

Mechanical Specifications

Pole : 2
Tamper Resistant : Yes
Torque Range : 14-18 lbs.
Type : GFCI/USB Combination
Voltage : 125 VAC
Wire : 5

Product Features

Amperage : 15 A
At Rated Voltage : 1 HP
Brand : SmartlockPro
Color : White
Feature : Self-Test
Flammability : UL94, 5VA
Grade : Residential
/Commercial Specification
Grade
Grounding : Self-Grounding
Pole : 2
Product Type : GFCI/Outlet
/USB Combo
Tamper Resistant : Yes
Termination : Wire leads
(12AWG)
Trip Level : Class A, 5mA plus
or minus 1mA
Type : GFCI/USB Combination
Voltage : 125 VAC
Wallplate : Not Included
Warranty : 2-Year Limited
Wire : 5

Standards & Certifications

ANSI : Yes
CSA C22.2 No. 42 : Yes
CSA-C22.2 No. 144.1-06 : Yes
FCC Part 15 : Class B
Fed Spec WC-596 : No
Listed : cCSAus
NOM : Yes
UL 1310 : Yes
UL 498 : Yes
Warranty : 2-Year Limited

Patents *

CA2621644
CA2677283

CA2624409
CA2730014

MX302458	MX308495
MX344697	US10483066
US7355117	US7697252
US7820909	US7868719
US8242362	US8587914
US9053886	US9276393

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.