



Color :  Ivory

UPC Code : 078477434772

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :



T8280-I

15 Amp, 125 Volt, Duplex Receptacle Outlet, Tamper-Resistant, Heavy-Duty Hospital Grade

Decora Plus Surge Protective Duplex Receptacle Outlet, Heavy-Duty Hospital Grade, Tamper-Resistant, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Ivory

DISCONTINUED

Suggested Replacement SKUs: : 8280-I

Leviton's Surge Protection Devices can be used individually or as part of a coordinated application strategy, to protect sensitive electronic equipment, in industrial, commercial and residential locations, from the stress and degradation inflicted by voltage transients. Leviton Surge Protection Devices are compliant with UL 1449 Standards. Leviton's outstanding Surge Protection Devices divert damaging voltage transients, or surges, away from electronic equipment. Transients are diverted away from sensitive micro circuitry, providing protection against catastrophic failure, costly downtime and data disruptions.

Technical Information

Electrical Specifications

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Polycarbonate

Clamp Nuts : Zinc-Plated Steel

Face Material : Nylon

Ground Clips : Brass-Plated
Steel

Grounding Screw : Brass-
Plated Steel

Line Contacts : Brass Triple-
Wipe

Mechanical Specifications

Product ID : Ratings are
permanently marked on device

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Termination : Back or Side
Wire

Shutter Mechanism : Delrin®
Acetal

Terminal Screws : Brass-
Plated Steel

Yoke : Zinc-Plated Steel

Performance Data

Diagnostics : Indicator Light &
Audible Alarm

Joules Rating : 720

MCOV : 150V rms

**Maximum Surge Current, Per
Mode (Per Phase)** : 27kA (L-N:
18kA, L-G:9kA)

Noise Rejection : -30dB at
500kHz-30MHz

**Nominal Discharge Current
Rating** : 3kA

Short Circuit Current Rating :
5kA

VPR : L-N: 600V, L-G: 700V, N-
G: 600V

Product Features

Brand : Decora Plus

Color : Ivory

Device Type : Duplex
Receptacle Outlet

Feature : Tamper-Resistant

Function : Surge Protective

Grade : Heavy-Duty Hospital
Grade

NEMA : 5-15R

Standards and Certifications

ANSI : C-73

Agency Certifications : UL
498, UL 1449 3rd Edition Listed
and CSA C22.2 Certified Type 3

NEMA : WD-6


NOM : 057

Warranty

Warranty : 5-Year Limited

Wiring Diagram

Wiring Diagram



5-15R

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.