



LP815-5MC

150A Outdoor Meter Main Combo, 8 Spaces, Ringless with Lever Bypass, 5th Jaw Installed

Outdoor Meter Main Combo with 150A Main Circuit Breaker
Factory Installed, 8 Spaces, NEMA 3R Rated. Includes
Enclosure, Ringless Door, Feed-Thru Lugs, and Lever Bypass
with 5th Jaw Installed

DISCONTINUED

Suggested Replacement SKUs: : LS815-B5D

UPC Code : 078477822432

Country Of Origin : Mexico

- EASY – Leviton's revolutionary design allows the entire Load Center to be wired at rough-in without any circuit breakers present
- SUPERIOR CONDUCTIVITY – All Leviton Load Centers come standard equipped with tin plated copper bussing
- ORGANIZED – Notches stamped into the enclosure for cable ties promote secure and neat wiring
- UTILITY REQUIREMENT – Meter Equipment Group (MEG) Approved

**For applications up to 60A when using copper wire; or 50A when using aluminum wire *Designed for Leviton Circuit Breakers*

Technical Information

Electrical Specifications

Amperage : 150 A

Operating Temperature : -40C
to +70C

Short Circuit Current Rating :
22 KA

Spaces / Circuits : 8 / 8

Type of Load Center : Meter
Main

Voltage : 120/240 VAC

Environmental Specifications

NEMA Enclosure Type :
NEMA 3R Outdoor

Mechanical Specifications

Busbar Material : Copper,
Bright Tin-Plated

Busbar Rating : 225A

Dimensions : 36" H x 16.6" W
x 5.2" D

Enclosure Material :
Galvanized Steel, Gray Baked
Enamel

Ground Connection : 4 AWG -
2/0 AWG Cu/Al

Supply Connections : 6 AWG
– 350 MCM

Product Features

Color : Gray

Warranty : 10-Year Limited

Weight : 56.8 lbs

Standards & Certifications

UL 50 : Yes

UL 50E : Yes

UL 67 : Yes

UL 869A : Yes


Patents *

US11887798

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Dimensional Drawing

Cover Screw Dimensions



SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.