CL Series

Standard Duty Interconnected Lock Grade 2



pdqlocks.com

CL SERIES
Standard Duty Interconnected Lock Grade 2

Table of Contents

Product Specifications **3**

Lever Designs **4**

Finishes and Trim Designs **5**

Functions, Cross Reference, Handing **6**

How To Order **7**

Keyways, Keying **7**

Standard and High Security Cylinders/Cores **8**

Dimensions **8**

Strikes, Latchbolts, Deadbolts **9**

Specifications

CERTIFIED

ADA COMPLIANT

FOR DOORS:	• 1-3/8" and 1-3/4" thick
PREPARATION:	• ANSI/BHMA A156.115 for 4" and 5-1/2" hole centers, field selectable
DUST BOX:	•Included for Latchbolt and Deadbolt
LATCHBOLT BACKSET:	• 2-3/8" or 2-3/4" (Default). Specify when ordering
DEADBOLT BACKSET:	• Field adjustable for 2-3/8" and 2-3/4" (Default)
STRIKE:	• "T"-Strike (Default) • ASA or Full-Lip optional
LEVERS:	• Boston, Miami, Memphis, Orlando, Philadelphia
ROSE:	• 2-3/8" Round Rose, 2-15/16" Square Rose
INSIDE ESCUTCHEON:	• 3-3/4"W x 9-3/4"H (Wrought)
LATCHBOLT:	• 1/2" Throw
DEADBOLT:	• 1" Throw • Brass Bolt containing one 1/4" case-hardened Steel Roll Pin
HANDING:	• Non-handed (Except for Memphis Lever)
KEYS:	• Two (2) per Lock
KEYWAYS:	• SCC Default (Schlage C Compatible). For additional keyways, see Cylinders and Keying section
INTERCHANGEABLE CORE:	• 6-pin or 7-pin • Compatible with Best SFIC • Not available in high security
CONVENTIONAL KEY IN KNOB/ LEVER CYLINDER:	• 6-pin Cylinder keyed to 5-pins
KEYING:	• Options: MK, CMK, or GMK, Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) • Can be keyed into existing master key systems. See Keyways Section
FINISHES:	• 605 (US3), 613E, 622 (US19), 626 (US26D) (See Note)
CERTIFICATIONS, LISTINGS, COMPLIANCES:	• ANSI, Grade 2 • UL listed for 3 hrs, for single doors up to 4'0" x 8'0" • Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings • TAA compliant. Country of origin: KR
WARRANTY:	• Two (2) year Limited Warranty

NOTE: OTHER FINISHES AVAILABLE. CONTACT CUSTOMER SERVICE FOR QUOTE AND LEAD-TIME.



CL176 Privacy w/Indicator




Indicator Showing Unoccupied




Indicator Showing Occupied

Lever Designs

ALL LEVERS




MIAMI — MIA




MEMPHIS — MEM


(Specify handing)



PHILADELPHIA — PHL



ORLANDO — ORL



BOSTON — BSN


Trim Designs



ROUND ROSE



SQUARE ROSE



SQUARE ROSE DIMENSIONS

Finishes

605 (US3)
Bright Brass



613E
Dark Oxidized Satin
Bronze (Equivalent)








622 (US19)
Flat Black



626 (US26D)
Satin Chromium

PDQ Functions

FUNCTION	FUNCTION NUMBER	OUTSIDE | INSIDE	DESCRIPTION	ANSI NUMBER
Entry Single Cylinder Passage Lever	126		• Outside and Inside lever always free • Deadbolt projected or retracted by key outside or turnpiece inside • When deadbolt is projected, turning inside knob/lever retracts deadbolt and latchbolt simultaneously	F95
Storeroom Double Cylinder (See note) Passage Lever	115		• Deadlocking latch bolt is operated by key outside or inside lever • Key outside projects or retracts dead bolt. • Operating inside lever or keys outside retracts dead bolt and deadlocking latch.	F98
Entry Double Cylinder (See note) Privacy Lever	116		• Outside lever locked by turn button in inside knob/lever • Inside lever always free • Unlocking of outside lever requires use of key or manual return of inside turn button • Deadbolt is activated by key in outside deadlock or turnpiece inside • Turning inside lever retracts deadbolt and latchbolt simultaneously	F97
Classroom with Deadbolt Indicator	148		• Outside lever locked or unlocked from the outside • Inside lever always free • Indicator Outside • Thumbturn inside extends/retracts deadbolt • Emergrncy key outside retracts deadbolt • When deadbolt is projected, turning inside lever retracts deadbolt and latchbolt simultaneously	–
Privacy with Dead Bolt Indicator No Cylinder Passage Lever	176		• Outside and Inside lever always free • Indicator outside • Thumbturn inside extends/retracts deadbolt • Emergency key outside retracts deadbolt • When deadbolt is projected, turning inside lever retracts deadbolt and latchbolt simultaneously	–

NOTE: Memphis lever not available in Small Format Interchangeable Core.


Cross Reference

ANSI NUMBER / FUNCTION	PDQ	DORMA ARCHITECTURAL	FALCON	HAGER	SCHLAGE®	DORMA COMMERICAL
95 / ENTRY, SINGLE CYLINDER	CL 126	J310	–	3710	S210	QCI230
97 / ENTRY, DOUBLE CYLINDER	CL 116	J353	H2101	3753	S251	QCI250
98 / STOREROOM, DOUBLE CYLINDER	CL 115	–	–	–	S280	–
PRIVACY W/INDICATOR, NO CYLINDER	CL 176	J346	H2171	3796	–	–


Information on this sheet is compiled form public documents and third parties. As a result, PDQ makes no guarantees as to their accuracy, content, quality or availability. Comparisons were made using the technical features only and are not commercial comparisons. Final suitability should be determined by a professional hardware consultant.

Handing

In Swing Door



Out Swing Door



How To Order

QUANTITY	TYPE	FUNCTION	LEVER	ROSE	FINISH	BACKSET	HANDING	STRIKE	CYLINDER	KEYWAY	OPTION
6	CL	116	PHL	—	626	234	—	FL	D	SCC	—
			MIA — Miami **PHL** — Philadelphia **BSN** — Boston **MEM** — Memphis **ORL** — Orlando	**BLANK** — Round Rose (default) All Levers **SR** — Square Rose (Orlando Lever Only)	**605** **613E** **622** **626**	**238** — 2-3/8" **234** — 2-3/4"	**LH** — Left Hand **RH** — Right Hand	**ASA** — ASA **FL** — Full Lip **T** — "T" Strike (default)	**D** Default **L** Less Cylinder **SF6** Lock is SFIC prepped w/ 6 pin core **SF7** Lock is SFIC prepped w/ 7 pin core **SFL** Lock is SFIC prepped but less core **SFC** Lock is SFIC prepped w/ construction core **SFP** Lock is SFIC prepped w/ plastic construction core		**DB** — Dust Box

Notes: 1- Other finishes available. Contact Customer Service.
2 - Specify handing when ordering Memphis lever.
3 - Memphis lever not available in SFIC.

Keyways

CONVENTIONAL CYLINDER		SMALL FORMAT INTERCHANGEABLE CORE	
KEYWAY	PDQ KEYWAY DESIGNATOR	KEYWAY (BEST COMPATIBLE)	PDQ KEYWAY DESIGNATOR
Schlage C (Default)	**SCC**	BEST A (Default), B, C, D, E, F, G, H, J, K, L, M, Q, R, WA, WB, WG, WH, TB, TD, TE, R	A (Default), B, C, D, E, F, G, H, J, K, L, M, Q, R, WA, WB, WG, WH, TB, TD, TE, R
PDQ Restricted	**TA**		
Arrow AR1	AR1		
Corbin 59A1	CO59A1		
Corbin 60	CO6		
Corbin L4	CL4		
Russwin D1	RUD	PDQ Exclusive	PDQ1
Russwin 981	RUD981		PDQ2
Schlage E	SCE	PDQ Exclusive and Restricted	PDQ3
Schlage C	SCC		
Schlage C-K	SCC-K		
Sargent LA	SAL		
Sargent RA-RC	RA-RC		
Accentra (Yale) E1R	YA8		
Accentra (Yale) GA	GA		
Falcon E-R	FAL		
Kwikset	KW		

CYLINDER OPTIONS	ICON
D	
SFL	

Keying

DESCRIPTION	PDQ KEYING DESIGNATOR
Keyed Different (Default)	**KD**
Keyed Alike	**KA**
"O" Zero Bitted	**KO**
Master Keyed	**MK**
Construction Master Keyed	**CMK**
Grand Master Keyed	**GMK**

Cylinders/Cores

PDQ cylinders and cores are designed to interface with the keyways of most major lock manufacturers. Insert cylinders are designed to accept 6 pins and are combinated for 5 pins. These cylinders are shipped with two keys. Interchangeable core cylinders are available combinated or uncombinated for 6 and 7 pins and must be specified when ordering. Available in two finishes — 606 (US4) and 626 (US26D); specify when ordering separately.



Key in Knob/Lever Cylinder (Default)



Small Format Interchangeable Core.

Cylinders & Cores

DESCRIPTION		PINS	FINISHES 606	FINISHES 626
	Conventional Key In Knob/Lever Cylinder (Default)	6 Pin	V4802-8	V4802-7
	Small Format, Best® Compatible - Uncombinated	6 Pin 7 Pin	I5206 -8 I5207-8	I5206 -7 I5207-7
	Small Format, Best® Compatible - Combinated	6 Pin 7 Pin	I5206-1-8 I5207-1-8	I5206-1 -7 I5207-1 -7


NOTE: Part Numbers Listed For Default Keyway. For Other Keyways, See Keyways Section.


High Security Cylinders & Cores

DESCRIPTION		PINS	FINISHES 606	FINISHES 626
	Key in Knob/Lever Cylinder Key in Knob/Lever Cylinder - UL437	6 Pin 6 Pin	HSC125-8 HSC425-8	HSC125-7 HSC425-7
	Small Format, Best® Compatible - Combinated Small Format, Best® Compatible - Combinated	6 Pin 7 Pin	HSC806-8 HSC807-8	HSC806-7 HSC807-7

Dimensions

NOTE: Part Numbers Listed For Default Keyway. For Other Keyways, See Keyways Section.






Note: Dimensions in parenthesis in millimeters


Note: Fits ANSI/BHMA 156.115 door preparation for Interconnected Locks

Strikes


All PDQ series strikes are reversible and shipped with screws. Specify finish when ordering.




ASA ANSI Strike



"T" Strike Square Corners (Default)



FL Full Lip Strike



Deadbolt Strike Square Corners


NOTE: Dimensions in parenthesis in millimeters

Strikes


	CODE	DESCRIPTION	605	613E	622	630
	ASA	ASA Strike (any finish) 1-1/4" x 4-7/8"	V91900-5	V91900-6	V91900-H	V91900-7
	T	T-Strike (any finish) 1-1/8" x 2-3/4"	V91901-5	V91901-6	V91901-H	V91901-7
	FL	Full Lip Strike (any finish) 1-5/8" x 2-1/4"	V919010-5	V919010-6	V919010-H	V919010-7
	W	Deadbolt Strike	I4072-5	I4072-6	I4072-H	I4072-7

Latchbolts

BACKSET	TYPE	FACEPLATE	CORNERS	PDQ NUMBER
2-3/8"	SPRINGLATCH	2-1/4" X 1	SQUARE (DEFAULT)	V21900-722
		2-1/4" X 1-1/8"	SQUARE	V21900-724
		2-1/4" X 1	1/4" RADIUS	V21900-722R
	DEADLATCH	2-1/4" X 1	SQUARE (DEFAULT)	V21900-721
		2-1/4" X 1-1/8"	SQUARE	V21900-723
		2-1/4" X 1	1/4" RADIUS	V21900-721R
	ADJUSTABLE	2-1/4" X 1	SQUARE (DEFAULT)	I04507
		2-1/4" X 1	1/4" RADIUS	I04507R
2-3/4"	SPRINGLATCH	2-1/4" X 1	SQUARE	V21900-714
		2-1/4" X 1-1/8"	SQUARE (DEFAULT)	V21900-712
	DEADLATCH	2-1/4" X 1	SQUARE	V21900-711
		2-1/4" X 1-1/8"	SQUARE (DEFAULT)	V21900-713




Dead Latch



Springlatch

Deadbolts

BACKSET	TYPE	FACEPLATE	CORNERS	PDQ NUMBER
2-3/8" AND 2-3/4"	ADJUSTABLE	2-1/4" X 1	SQUARE (DEFAULT)	I04507
		2-1/4" X 1	1/4" RADIUS	I04507R
2-3/4" (DEFAULT)	FIXED	2-1/4" X 1-1/8"	SQUARE	I04510



Deadbolt

SECURING
CONFIDENCE
OPENING
POSSIBILITIES

Phone: 717.656.4281
Tech Support: 800.441.9692
Email: help@pdqlocks.com

Headquarters: 2230 Embassy Drive, Lancaster, PA 17603
P.O Box 6426, Lancaster, PA 17607

Regional Distribution Centers: Lancaster, PA | Norcrss, GA | Auburn, WA

Middle East Manufacturing: Dammam, Kingdom of Saudi Arabia