
GP SERIES

Grade 2 Heavy Duty Cylindrical Lock

Architectural Submittal Sheet

Typical Applications

- Government Facilities
- Healthcare
- Higher Education
- Hospitality
- Houses of Worship
- Industrial
- K-12 Education
- Multi-family
- Offices
- Public Buildings



Specifications





CERTIFIED | BHMA CERTIFIED | ADA COMPLIANT

FOR DOORS:	• 1-3/8" to 1-3/4" thick • Preset for 1-3/4" door
APPLICATION:	• Through door thru-bolting • Fits 160 and 161 Door prep
BACKSET:	• 2-3/4" standard • 2-3/8"
CHASSIS:	• Heavy duty diecast, investment cast, cold rolled steel, stainless steel mechanism
FRONT:	• 2-1/4" x 1-1/8" or 2-1/4" x 1" • Stainless Steel or Wrought Brass • Beveled 1/8" on 2"
STRIKE:	• ASA standard • Stainless Steel or Wrought Brass • T-Strike or Full Lip Strike optional
LEVERS:	Philadelphia (SFL and LFL), Boston (SFL), Miami (SFL)
ROSE:	• 3-3/8" DIA Wrought
LATCHBOLT:	• 1/2" Throw
HAND:	• Non-handed
TRIM:	• Solid diecast PHL, BSN or MIA Levers • 65° Lever Rotation • Wrought Brass Roses • Concealed Screws
KEYS:	• Two (2) per Lock
KEYWAYS:	• SCC standard (Schlage C Compatible) • Compatible with Best, Falcon and Arrow small format IC cores
INTERCHANGEABLE CORE:	• Available for all keyed functions • Large Format IC Core available for PHL Lever ONLY. • 6 or 7-pin • Compatible with Best, Falcon & Arrow
CYLINDER:	• 6-pin Brass Insert Cylinder keyed to 5-pins • Standard High Security Cylinders Available
KEYING:	• Options: MK, CMK or GMK • Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) Can be keyed into existing master key systems
FINISHES:	• 605 (US3), 606 (US4), 613E, 619 (US15), 622 (US19), 625 (US26), 626 (US26D) • Optional Antimicrobial Coating Available for 626 (USD26D) only • Optional Weatherized Finish for 626 (USD26D) only
CERTIFICATIONS, LISTINGS, COMPLIANCES:	• UL listed for 3 hrs, for single doors up to 4'0" x 8'0" • Certified to ANSI/BHMA 156.2, Grade 2 • Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings
WARRANTY:	• Eight (8) Year Limited Warranty
COUNTRY OF ORIGIN:	• Assembled in the U.S.A. with U.S. and foreign material. • Meets requirements of the Buy American Act as a COTS product manufactured in the United States.

‡ Available with antimicrobial coating, technology that is known to inhibit the growth of microbes.

GP Series

PDQ Functions

FUNCTION	FUNCTION NUMBER	INSIDE | OUTSIDE	DESCRIPTION	ANSI NUMBER
NON KEYED				
Communicating	GP125		• Latchbolt operated by inside lever • Blank plate outside • Minimum clearance of 1-1/2" between doors • Frame depth 7-1/8" • Deadlocking (guarded) latchbolt	—
Passage	GP126		• Latchbolt operated by lever from either side at all times	F75
Privacy Bedroom Bathroom	GP176		• Latchbolt operated by lever from either side or emergency release in outside lever • Outside lever locked by push button on inside • Outside lever unlocked by emergency release from outside, rotating inside lever, or closing door	F76
KEYED				
Storeroom	GP115		• Latchbolt operated by inside lever or key in outside lever • Outside lever always fixed	F86
Entrance	GP116		• Latchbolt operated by lever from either side or key in outside lever • Outside lever locked by push/turn button on inside • When outside lever is locked by push button on inside – key from outside, or rotating inside lever unlocks outside lever • When outside lever is locked by pushing and turning button on the inside, key from outside or rotating inside lever retracts latch but does not unlock outside lever	F109
Classroom	GP148		• Latchbolt operated by lever from either side • Outside lever locked by key from outside • Outside lever unlocked by key from outside • Inside lever always operates latch	F84
Exit or Twin Communicating	GP150		• Latchbolt operated by inside lever • Blank plate outside • Inside lever locked by key inside • Inside lever unlocked by key inside • Minimum clearance of 1-1/2" between doors • Use only in rooms with more than one exit • Frame depth 7-1/8"	—
Entry	GP182		• Latchbolt operated by lever from either side or key in outside lever • Outside lever locked by push button on inside • Outside lever unlocked by key from outside, and rotating inside lever	F82
DUMMY				
Double Dummy	GP205		• Pull lever both sides • No mechanical operation	—
Single Dummy	GP211		• Pull lever one side • No mechanical operation	—

 **INDICATES RIGID LEVER**

GP Series

Levers



Philadelphia



Boston



Miami

Finishes

605 (US3)
Bright Brass



606 (US4)
Satin Brass



613E
Dark Oxidized Satin Bronze (Equivalent)



619 (US15)
Satin Nickel



622 (US19)
Flat Black



625 (US26)
Bright Chromium



626 (US26D)
Satin Chromium

Options

CODE	DESCRIPTION
TC1IS	Tactile Abrasive Coating - Inside only
TC1OS	Tactile Abrasive Coating - Outside only
TC2	Tactile Abrasive Coating - Both Sides
SF	Split Finishes
LL	Lead-Lined Rose
DB	Dust Box
AM	Antimicrobial Coating, Lever Set Includes Inside and Outside Lever and Rose
W	Weatherized Finish (626 Only)

Accessories

DESCRIPTION
Electric Strike for GP Locks (U.L. Listed)