

STI WIRELESS TRANSMITTERS AND RECEIVERS

Home & Work Series



PRODUCT OVERVIEW

STI wireless sensors alert of a car entering or exiting a driveway, a door opening, a fire extinguisher being moved, or a person at the door. STI receivers monitor up to 4 different STI devices at a single, convenient location. When a transmitter is triggered, the receiver will chime or speak, alerting users to events happening at their monitored home or building.

HOW IT WORKS

Wireless Doorbell Button (STI-34601)

The weather resistant button, when pressed, transmits a wireless signal to an STI receiver (up to 500' line of sight).

Wireless Outdoor Motion Detector (STI-34752)

PIR detects movement in monitored area and transmits a signal to an STI receiver to alert of motion detected (up to 1000' line of sight).

Wireless Exit Stopper® (STI-6400WIR)

When contacts separate, the unit will sound its local siren. A signal transmits to an STI receiver to alert of activation (up to 1000' line of sight).

Wireless Fire Extinguisher Theft Stopper® (STI-6200WIR)

When the fire extinguisher is moved, the cable detaches from the alarm.

The unit will sound its local siren and transmit a signal to an STI receiver to alert (up to 1000' line of sight).

4-Channel Voice Receiver (STI-V34104)

Monitors up to 4 devices and offers 10 tones or 53 spoken words (English or Spanish). Receiver will illuminate amber if a zone is having trouble communicating or has a low battery. When acknowledge button is pressed it will announce a trouble message for that zone.

Single Channel Slave Receiver (STI-34098)

Receiver allows one device to be integrated into an existing panel/notification through its Form "C" output.

KEY FEATURES

General Information

- Monitor 4 devices at a single, convenient location.
- Supervised for low battery and signal reception.

Installation

- Easy installation.

Electronics

- Operates up to 1000' line of sight (STI-34601 up to 500' line of sight), 433MHz.
- Audible chime tone/voice.
- Devices can be latching or momentary by each zone.

Options

STI-V34104

- Monitors up to 4 devices.
- Ten tones/tunes or 53 selectable words (English or Spanish).
- Up to four words or tones can be programmed for each zone to create a custom message for each zone.
- Includes 12 volt power supply. STI-34098
- Allows transmitters to connect to control panel.
- Measures: 2 1/4 H x 1 1/2 W x 1/2" D.



STI WIRELESS TRANSMITTERS AND RECEIVERS

Dimensions and Technical Information

MODELS AVAILABLE

Receivers

STI-V34104	4-Channel Voice Receiver
STI-34098	Single Channel Slave Receiver

Sensors

STI-34601	Wireless Doorbell Button Alert Sensor
STI-34752	Wireless Indoor/Outdoor Motion Detector Alert Sensor
STI-6200WIR	Wireless Fire Extinguisher Theft Stopper® Sensor
STI-6400WIR	Wireless Exit Stopper® Door Alarm Sensor
STI-6517B	Wireless Stopper® Station Shield with Sound and Wireless Transmitter

APPROVALS

TESTING

- STI-V34104 FCC & IC Compliant

4-Channel Voice Receiver Kits

STI-V34600	Wireless Doorbell Button Alert
STI-V34760	Wireless Indoor/Outdoor Motion Detector Alert
STI-V6400WIR4	Wireless Indoor/Outdoor Motion Detector Alert
STI-V6200WIR4	Wireless Theft Stopper® Alarm

Single Channel Slave Receiver Kits

STI-34609	Wireless Doorbell Button Alert
STI-34759	Wireless Indoor/Outdoor Motion Detector Alert
STI-6400WIR9	Wireless Exit Stopper® Multifunction Door Alarm
STI-6200WIR9	Wireless Theft Stopper® Alarm



**Safety Technology
International**

2306 Airport Road info@sti-usa.com
Waterford, MI www.sti-global.com
48327, USA Tel: 248-673-9898

Taylor House info@sti-emea.com
34 Sherwood Rd., Bromsgrove, www.sti-global.com
Worcs., B60 3DR, England Tel: +44 (0) 1527 520 999

Unit 7A Lockheed Avenue
Airport Business Park
Waterford X91 HWF2 Ireland