



Schedule 80 PVC Product PVC Schedule 80 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

¹ Sized with Bushing

² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-020F ²	2	1	4	083	736.15
876-030F ²	3	1	4	083	927.76
876-040F ²	4	1	2	083	1684.78
876-060F ²	6	1	0	083	1969.22
876-080F ²	8	1	0	083	2346.18
876-100F ²	10	1	0	083	4180.67
876-120F ²	12	1	0	083	4609.34

For larger sizes please contact your Regional Spears® Distribution Center.

2-Fiberglass Reinforced



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

876-338	3X2	5	0	080	895.22
876-420F ²	4X2	1	2	083	1169.17
876-421F ²	4X2-1/2	1	2	083	1323.72
876-422F ²	4X3	1	2	083	1369.20
876-528F ²	6X2	1	2	083	1375.75
876-529F ²	6X2-1/2	1	2	083	1436.96
876-530F ²	6X3	1	2	083	1446.35
876-532F ²	6X4	1	0	083	1724.03
876-578F ²	8X2	1	2	083	1774.57
876-579F ²	8X2-1/2	1	2	083	1858.33
876-580F ²	8X3	1	0	083	1869.69
876-582F ²	8X4	1	0	083	1930.01
876-585F ²	8X6	1	0	083	2179.20
876-621F ²	10X2	1	0	083	2366.25
876-622F ²	10X2-1/2	1	0	083	2547.13
876-623F ²	10X3	1	0	083	2562.23
876-624F ²	10X4	1	0	083	2659.48
876-626F ²	10X6	1	0	083	2783.77
876-628F ²	10X8	1	0	083	3577.65
876-661F ²	12X2	1	0	083	2643.97
876-662F ²	12X2-1/2	1	0	083	2800.82
876-663F ²	12X3	1	0	083	2845.04
876-664F ²	12X4	1	0	083	3030.46
876-666F ²	12X6	1	0	083	3516.81
876-668F ²	12X8	1	0	083	4200.65
876-670F ²	12X10	1	0	083	4791.03

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union 2000 - Socket/FKM

Socket X Socket with FKM O-ring Seal



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8057-005	1/2	20	120	080	26.96
8057-007	3/4	20	80	080	34.29
8057-010	1	15	90	080	39.12
8057-012	1-1/4	10	0	080	77.67
8057-015	1-1/2	10	0	080	87.93
8057-020	2	5	0	080	119.23
8057-025	2-1/2	5	0	080	190.97
8057-030	3	5	0	080	222.03
8057-040	4	4	0	080	309.24
8057-060	6	1	0	080	687.31

Union 2000 - Socket/EPDM

Socket x Socket with EPDM O-ring Seal



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8097-005	1/2	20	120	080	26.57
8097-007	3/4	20	80	080	33.81
8097-010	1	15	90	080	38.75
8097-012	1-1/4	10	0	080	76.73
8097-015	1-1/2	10	0	080	86.85
8097-020	2	5	0	080	117.85
8097-025	2-1/2	5	0	080	187.33
8097-030	3	5	0	080	219.26
8097-040	4	4	0	080	303.29
8097-060	6	1	0	080	674.02

Union 2000 - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal



1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005	1/2	20	120	080	32.87
8059-007	3/4	20	80	080	45.96
8059-010	1	15	90	080	61.06
8059-012	1-1/4	10	0	080	116.71
8059-015	1-1/2	10	0	080	144.44
8059-020	2	5	0	080	222.39
8059-025	2-1/2	5	0	080	395.14

Schedule 80 PVC Product
PVC Schedule 80 Fittings



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Fipt/FKM (continued)

Socket x FiPT with FKM O-ring Seal

8059-030	3	5	0	080	524.81
8059-040	4	4	0	080	603.13
8059-060	6	1	0	080	800.59

Union 2000 - Socket/Fipt/EPDM

Socket x FiPT with EPDM O-ring Seal

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005	1/2	20	120	080	32.43
8099-007	3/4	20	80	080	45.36
8099-010	1	15	90	080	60.28
8099-012	1-1/4	10	0	080	115.31
8099-015	1-1/2	10	0	080	142.66
8099-020	2	5	0	080	219.58
8099-025	2-1/2	5	0	080	310.46
8099-030	3	5	0	080	518.20
8099-040	4	4	0	080	595.05
8099-060	6	1	0	080	761.01

Union 2000 - Socket/Spigot/FKM

Socket x Spigot with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8056-005	1/2	20	120	080	26.96
8056-007	3/4	20	160	080	34.29
8056-010	1	15	90	080	39.12
8056-012	1-1/4	10	0	080	77.67
8056-015	1-1/2	10	0	080	87.93
8056-020	2	5	0	080	119.23
8056-025	2-1/2	5	0	080	190.97
8056-030	3	5	0	080	222.03
8056-040	4	4	0	080	309.24
8056-060	6	1	0	080	687.31

Union 2000 - Socket/Spigot/EPDM

Socket x Spigot with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8096-005	1/2	20	160	080	26.57
8096-007	3/4	20	80	080	33.81
8096-010	1	15	90	080	38.75
8096-012	1-1/4	10	0	080	76.73
8096-015	1-1/2	10	0	080	86.85
8096-020	2	5	0	080	117.85
8096-025	2-1/2	5	0	080	187.33

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Spigot/EPDM (continued)

Socket x Spigot with EPDM O-ring Seal

8096-030	3	5	0	080	219.26
8096-040	4	4	0	080	303.29
8096-060	6	1	0	080	674.02

Union 2000 - FiPT/MiPT/FKM

FiPT x MiPT with FKM O-ring Seal

1/2" - 3" 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8053-005	1/2	20	120	080	26.96
8053-007	3/4	20	0	080	34.29
8053-010	1	15	90	080	39.12
8053-012	1-1/4	10	0	080	77.67
8053-015	1-1/2	10	0	080	87.93
8053-020	2	5	0	080	119.23
8053-030	3	5	0	080	222.03

Union 2000 - FiPT/MiPT/EPDM

FiPT x MiPT with EPDM O-ring Seal

1/2" - 3" 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8093-005	1/2	20	120	080	26.57
8093-007	3/4	20	0	080	33.81
8093-010	1	15	90	080	38.75
8093-012	1-1/4	10	0	080	76.73
8093-015	1-1/2	10	0	080	86.85
8093-020	2	5	0	080	117.85
8093-030	3	5	0	080	219.26

Union 2000 - FiPT/MiPT/FKM- Reducing

FiPT x MiPT with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8053-168	1-1/4X1	10	0	080	55.71
----------	---------	----	---	-----	-------

Union 2000 - FiPT/MiPT/EPDM- Reducing

FiPT x MiPT with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8093-168	1-1/4X1	10	0	080	54.32
----------	---------	----	---	-----	-------

Union 2000 - Socket/MiPT/FKM

Socket x MiPT with FKM O-ring Seal

1/2" - 3" 235 psi Max Int Pressure @ 73°F (23°C)

8054-005	1/2	20	120	080	26.96
----------	-----	----	-----	-----	-------



Schedule 80 PVC Product PVC Schedule 80 Fittings

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Union 2000 - Socket/Mipt/FKM (continued)					
Socket x Mipt with FKM O-ring Seal					
8054-007	3/4	20	0	080	34.29
8054-010	1	15	90	080	39.12
8054-012	1-1/4	10	0	080	77.67
8054-015	1-1/2	10	0	080	87.93
8054-020	2	5	0	080	119.23
8054-030	3	5	0	080	222.03

Union 2000 - Socket/Mipt/EPDM

Socket x Mipt with EPDM O-ring Seal

1/2" - 3" 235 psi Maximum Internal Pressure Rating
@ 73°F (23°C)

8094-005	1/2	20	120	080	26.57
8094-007	3/4	20	80	080	33.81
8094-010	1	15	90	080	38.75
8094-012	1-1/4	10	0	080	76.73
8094-015	1-1/2	10	0	080	86.85
8094-020	2	5	0	080	117.85
8094-030	3	5	0	080	219.26

Union 2000 - Socket/Mipt/FKM-Reducing

Socket x Mipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating
@ 73°F (23°C)

8054-168	1-1/4X1	10	0	080	55.71
----------	---------	----	---	-----	-------

Union 2000 - Socket/Mipt/EPDM- Reducing

Socket x Mipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating
@ 73°F (23°C)

8094-168	1-1/4X1	10	0	080	54.32
----------	---------	----	---	-----	-------

Union 2000 - Special Reinforced Fipt/Spigot/FKM

SR Fipt x Spigot with FKM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8055-005SR	1/2	20	160	086	49.54
8055-007SR	3/4	20	160	086	53.43
8055-010SR	1	15	90	086	65.66
8055-012SR	1-1/4	10	0	096	115.60
8055-015SR	1-1/2	10	0	086	140.43
8055-020SR	2	5	0	086	159.91
8055-025SR	2-1/2	5	0	086	313.78
8055-030SR	3	5	0	086	352.72
8055-040SR	4	4	0	086	400.04
8055-060SR	6	1	0	086	849.76

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/Spigot/EPDM

SR Fipt x Spigot with EPDM O-ring Seal

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8095-005SR	1/2	20	120	086	48.81
8095-007SR	3/4	20	160	086	51.99
8095-010SR	1	15	90	086	63.27
8095-012SR	1-1/4	10	0	086	107.08
8095-015SR	1-1/2	10	0	086	126.76
8095-020SR	2	5	0	086	144.25
8095-025SR	2-1/2	5	0	086	295.44
8095-030SR	3	5	0	086	335.67
8095-040SR	4	5	0	086	384.06
8095-060SR	6	1	0	086	806.12

Union 2000 - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005SR	1/2	20	120	086	18.33
8059-007SR	3/4	20	80	086	25.17
8059-010SR	1	15	90	086	32.72
8059-012SR	1-1/4	10	0	086	62.60
8059-015SR	1-1/2	10	0	086	77.18
8059-020SR	2	5	0	086	117.89
8059-025SR	2-1/2	5	0	086	253.36
8059-030SR	3	5	0	086	288.03
8059-040SR	4	4	0	086	330.74
8059-060SR	6	1	0	086	1317.47

Union 2000 - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005SR	1/2	20	120	086	17.59
8099-007SR	3/4	20	80	086	25.07
8099-010SR	1	15	90	086	32.34
8099-012SR	1-1/4	10	0	086	56.28
8099-015SR	1-1/2	10	0	086	72.91
8099-020SR	2	5	0	086	117.38
8099-025SR	2-1/2	5	0	086	251.04
8099-030SR	3	5	0	086	279.46
8099-040SR	4	4	0	086	318.94
8099-060SR	6	1	0	086	1282.32

Schedule 80 PVC Product
PVC Schedule 80 Fittings



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Fipt/FKM

Fipt x Fipt with FKM O-ring Seal

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005	1/2	20	120	080	31.27
8058-007	3/4	20	80	080	43.79
8058-010	1	15	90	080	58.24
8058-012	1-1/4	10	0	080	111.17
8058-015	1-1/2	10	0	080	137.64
8058-020	2	5	0	080	211.75
8058-025	2-1/2	5	0	080	358.17
8058-030	3	5	0	080	537.12
8058-040	4	4	0	080	631.26
8058-060	6	1	0	080	854.13



Union 2000 - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal

1/4" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005	1/2	20	240	080	30.88
8098-007	3/4	20	80	080	43.23
8098-010	1	15	90	080	57.57
8098-012	1-1/4	10	0	080	109.73
8098-015	1-1/2	10	0	080	135.87
8098-020	2	5	0	080	209.12
8098-025	2-1/2	5	0	080	280.01
8098-030	3	5	0	080	530.44
8098-040	4	4	0	080	620.41
8098-060	6	1	0	080	815.04



Union 2000 - Special Reinforced Fipt/FKM

SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005SR	1/2	20	120	086	18.83
8058-007SR	3/4	20	80	086	25.49
8058-010SR	1	15	90	086	34.09
8058-012SR	1-1/4	10	0	086	64.96
8058-015SR	1-1/2	10	0	086	79.93
8058-020SR	2	5	0	086	124.15
8058-025SR	2-1/2	5	0	086	259.60
8058-030SR	3	5	0	086	295.33
8058-040SR	4	4	0	086	347.64
8058-060SR	6	1	0	086	1198.02



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/EPDM

SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005SR	1/2	20	120	086	18.52
8098-007SR	3/4	20	80	086	25.23
8098-010SR	1	15	90	086	33.41
8098-012SR	1-1/4	10	0	086	62.19
8098-015SR	1-1/2	10	0	086	78.19
8098-020SR	2	5	0	086	122.86
8098-025SR	2-1/2	5	0	086	248.02
8098-030SR	3	5	0	086	292.46
8098-040SR	4	4	0	086	335.76
8098-060SR	6	1	0	086	1253.77



Union (Old Style) - Socket/FKM

Socket x Socket with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-002	1/4	25	150	080	50.42
857-003	3/8	25	150	080	50.42
857-005	1/2	15	90	080	26.96
857-007	3/4	10	60	080	34.29
857-010	1	10	40	080	39.12
857-012	1-1/4	5	20	080	77.67
857-015	1-1/2	5	0	080	87.93
857-020	2	5	0	080	119.23
857-025	2-1/2	5	0	080	190.97
857-030	3	5	0	080	222.03
857-040	4	4	0	080	309.24



Union (Old Style) - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-002	1/4	25	150	080	49.76
897-003	3/8	25	150	080	49.76
897-005	1/2	15	90	080	26.57
897-007	3/4	10	60	080	33.81
897-010	1	10	40	080	38.75
897-012	1-1/4	5	20	080	76.73
897-015	1-1/2	5	0	080	86.85
897-020	2	5	0	080	117.85
897-025	2-1/2	5	0	080	187.33
897-030	3	5	0	080	219.26
897-040	4	4	0	080	303.29





Schedule 80 PVC Product PVC Schedule 80 Fittings

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union (Old Style) - Socket/Fipt/FKM

Socket x Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002	1/4	25	150	080	54.25
859-003	3/8	25	150	080	54.25
859-005	1/2	15	90	080	32.87
859-007	3/4	10	60	080	45.96
859-010	1	10	40	080	61.06
859-012	1-1/4	5	20	080	116.71
859-015	1-1/2	5	0	080	144.44
859-020	2	5	0	080	222.39
859-025	2-1/2	5	0	080	395.14
859-030	3	5	0	080	524.81
859-040	4	4	0	080	603.13

Union (Old Style) - Socket/Fipt/EPDM

Socket x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002	1/4	25	150	080	53.65
899-003	3/8	25	150	080	53.65
899-005	1/2	15	90	080	32.43
899-007	3/4	10	60	080	45.36
899-010	1	10	40	080	60.28
899-012	1-1/4	5	20	080	115.31
899-015	1-1/2	5	0	080	142.66
899-020	2	5	0	080	219.58
899-025	2-1/2	5	0	080	310.46
899-030	3	5	0	080	518.20
899-040	4	4	0	080	595.05

Union (Old Style) - Special Reinforced Fipt/FKM

Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002SR	1/4	25	150	086	33.69
859-003SR	3/8	25	100	086	33.69
859-005SR	1/2	10	60	086	18.33
859-007SR	3/4	10	60	086	25.17
859-010SR	1	10	40	086	32.72
859-012SR	1-1/4	5	20	086	62.60
859-015SR	1-1/2	5	0	086	77.18
859-020SR	2	5	0	086	117.89
859-030SR	3	5	0	086	288.03
859-040SR	4	4	0	086	330.74



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union (Old Style) - Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002SR	1/4	25	150	086	33.27
899-003SR	3/8	25	100	086	33.27
899-005SR	1/2	10	60	086	17.59
899-007SR	3/4	10	40	086	25.07
899-010SR	1	10	40	086	32.34
899-012SR	1-1/4	5	20	086	56.28
899-015SR	1-1/2	5	0	086	72.91
899-020SR	2	5	0	086	117.38
899-030SR	3	5	0	086	279.46
899-040SR	4	4	0	086	318.94



Union - Socket/Brass Fipt/FKM

Socket x Fipt with Brass Thread Insert & FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005BR	1/2	10	60	086	76.49
859-007BR	3/4	10	40	086	117.01
859-010BR	1	10	0	086	144.38
859-012BR	1-1/4	5	20	086	249.19
859-015BR	1-1/2	5	0	086	329.80
859-020BR	2	5	0	086	438.32

Not intended to convey or dispense water for human consumption through drinking or cooking



Union - Socket/Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005BR	1/2	10	60	086	79.18
899-007BR	3/4	10	60	086	105.48
899-010BR	1	10	0	086	142.27
899-012BR	1-1/4	5	20	086	239.25
899-015BR	1-1/2	5	0	086	316.69
899-020BR	2	5	0	086	422.08

Not intended to convey or dispense water for human consumption through drinking or cooking



Union (Old Style) - Fipt/FKM

Fipt x Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-002	1/4	25	150	080	54.25
858-003	3/8	25	150	080	54.25
858-005	1/2	15	90	080	31.27
858-007	3/4	10	60	080	43.79
858-010	1	10	40	080	58.24
858-012	1-1/4	5	20	080	111.17



Schedule 80 PVC Product
PVC Schedule 80 Fittings



Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Union (Old Style) - Fipt/FKM (continued)					
Fipt x Fipt with FKM O-ring Seal					
858-015	1-1/2	5	0	080	137.64
858-020	2	5	0	080	211.75
858-025	2-1/2	5	0	080	358.17
858-030	3	5	0	080	537.12
858-040	4	4	0	080	631.26

Union (Old Style) - Fipt/EPDM

Fipt x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-002	1/4	25	150	080	53.65
898-003	3/8	25	150	080	53.65
898-005	1/2	15	90	080	30.88
898-007	3/4	10	60	080	43.23
898-010	1	10	40	080	57.57
898-012	1-1/4	5	20	080	109.73
898-015	1-1/2	5	0	080	135.87
898-020	2	5	0	080	209.12
898-025	2-1/2	5	0	080	280.01
898-030	3	5	0	080	530.44
898-040	4	4	0	080	620.41

Union -Transition JIS to ASTM/FKM

JIS (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8258-016	16 DN X 1/2	20	160	197	29.60
8258-020	20 DN X 3/4	20	80	197	41.35
8258-025	25 DN X 1	15	90	197	55.03
8258-030	30 DN X 1-1/4	10	0	197	105.06
8258-040	40 DN X 1-1/2	10	0	197	130.06
8258-075	75 DN X 3	5	0	197	472.29
8258-100	100 DN X 4	4	0	197	542.83

Union -Transition JIS to ASTM/EPDM

JIS (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8298-016	16 DN X 1/2	20	160	197	29.16
8298-020	20 DN X 3/4	20	80	197	40.83
8298-025	25 DN X 1	15	90	197	54.33
8298-030	30 DN X 1-1/4	10	0	197	103.24
8298-040	40 DN X 1-1/2	10	0	197	128.39
8298-050	50 DN X 2	5	0	197	197.64
8298-075	75 DN X 3	5	0	197	466.41
8298-100	100 DN X 4	4	0	197	535.51

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Transition BSP to ASTM/FKM

BSP Thread (in.) x ASTM (in.) Socket with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8359-005	1/2	20	160	197	29.60
8359-007	3/4	20	80	197	41.35
8359-010	1	15	90	197	55.03
8359-012	1-1/4	10	0	197	105.06
8359-015	1-1/2	10	0	197	130.06
8359-020	2	5	0	197	200.08
8359-030	3	5	0	197	472.29
8359-040	4	4	0	197	542.83

Union - Transition BSP to ASTM/EPDM

BSP Thread (in.) x ASTM (in.) Socket with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8399-005	1/2	10	60	197	29.16
8399-007	3/4	20	80	197	40.83
8399-010	1	15	90	197	54.33
8399-012	1-1/4	10	0	197	103.76
8399-015	1-1/2	10	0	197	128.39
8399-020	2	5	0	197	197.64
8399-030	3	5	0	197	466.41
8399-040	4	4	0	197	535.51

Union - Transition DIN to ASTM/FKM

DIN (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8657-020	20 d X 1/2	10	60	197	24.21
8657-025	25 d X 3/4	10	60	197	30.85
8657-032	32 d X 1	10	40	197	35.19
8657-040	40 d X 1-1/4	10	0	197	69.89
8657-050	50 d X 1-1/2	10	0	197	79.16
8657-063	63 d X 2	5	0	197	107.37
8657-090	90 d X 3	5	0	197	199.83
8657-110	110 d X 4	4	0	197	278.36

Union - Transition DIN to ASTM/EPDM

DIN (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8697-020	20 d X 1/2	20	240	197	23.89
8697-025	25 d X 3/4	10	60	197	30.46
8697-032	32 d X 1	15	90	197	34.83
8697-040	40 d X 1-1/4	10	0	197	69.07
8697-050	50 d X 1-1/2	10	0	197	78.19
8697-063	63 d X 2	5	0	197	106.06
8697-090	90 d X 3	5	0	197	197.35



Schedule 80 PVC Product
PVC Schedule 80 Fittings & Tank Adapters

Unions

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Transition DIN to ASTM/EPDM (continued)

DIN (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal

8697-110	110 d X 4	4	0	197	272.95
----------	-----------	---	---	-----	--------

Union - Transition DIN to ASTM/FKM

DIN (mm) Socket x ASTM (in.) Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8658-020	20 d X 1/2	10	60	197	29.60
8658-025	25 d X 3/4	20	80	197	41.35
8658-032	32 d X 1	15	90	197	55.03
8658-040	40 d X 1-1/4	10	0	197	105.06
8658-050	50 d X 1-1/2	10	0	197	130.06
8658-063	63 d X 2	5	0	197	200.08
8658-090	90 d X 3	5	0	197	472.29
8658-110	110 d X 4	4	0	197	542.83

Union - Transition DIN to ASTM/EPDM

DIN (mm) Socket x ASTM (in.) Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8698-020	20 d X 1/2	20	160	197	29.16
8698-025	25 d X 3/4	20	80	197	40.83
8698-032	32 d X 1	15	90	197	54.33
8698-040	40 d X 1-1/4	10	0	197	103.24
8698-050	50 d X 1-1/2	10	0	197	128.39
8698-063	63 d X 2	5	0	197	197.64
8698-090	90 d X 3	5	0	197	466.41
8698-110	110 d X 4	4	0	197	535.51

Union - Transition JIS to ASTM/FKM

JIS (mm) Socket x ASTM (in.) Socket with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8257-016	16 DN X 1/2	20	160	197	24.21
8257-020	20 DN X 3/4	10	60	197	30.85
8257-025	25 DN X 1	15	90	197	35.19
8257-030	30 DN X 1-1/4	10	0	197	69.89
8257-040	40 DN X 1-1/2	10	0	197	79.16
8257-050	50 DN X 2	5	0	197	107.37
8257-075	75 DN X 3	5	0	197	199.83
8257-100	100 DN X 4	4	0	197	278.36

Union - Transition JIS to ASTM/EPDM

JIS (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8297-016	16 DN X 1/2	20	160	197	23.89
8297-020	20 DN X 3/4	20	80	197	30.46

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Transition JIS to ASTM/EPDM (continued)

JIS (mm) Socket x ASTM (in.) Socket with EPDM O-ring Seal

8297-025	25 DN X 1	15	90	197	34.83
8297-030	30 DN X 1-1/4	10	0	197	69.07
8297-040	40 DN X 1-1/2	10	0	197	78.19
8297-050	50 DN X 2	5	0	197	106.06
8297-075	75 DN X 3	5	0	197	197.35
8297-100	100 DN X 4	4	0	197	272.95

Union - Transition BSP to ASTM/FKM

BSP Thread (in.) x ASTM (in.) Fipt with FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8358-005	1/2	20	160	197	28.20
8358-007	3/4	20	80	197	39.39
8358-010	1	15	90	197	52.42
8358-012	1-1/4	10	0	197	100.02
8358-015	1-1/2	10	0	197	123.86
8358-020	2	5	0	197	190.59
8358-030	3	5	0	197	483.43
8358-040	4	4	0	197	568.08

Union - Transition BSP to ASTM/EPDM

BSP Thread (in.) x ASTM (in.) Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8398-005	1/2	10	60	197	27.80
8398-007	3/4	10	60	197	38.87
8398-010	1	10	40	197	51.77
8398-012	1-1/4	5	20	197	98.81
8398-015	1-1/2	5	0	197	122.28
8398-020	2	5	0	197	196.49
8398-030	3	5	0	197	477.38
8398-040	4	4	0	197	558.35

Tank Adapters

Tank Adapters, PVC New Style Standard with Neoprene Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002	1/4	25	150	100	75.56
8170-003	3/8	25	150	100	75.56
8170-005	1/2	25	0	100	75.56
8170-007	3/4	25	0	100	86.11
8170-010	1	25	0	100	95.66
8170-012	1-1/4	20	0	100	115.26
8170-015	1-1/2	20	0	100	126.48
8170-020	2	15	0	100	187.46
8170-025	2-1/2	4	0	100	289.68
8170-030	3	4	0	100	344.84
8170-040	4	2	0	100	679.27

