



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

ORANGE WIRE CONNECTORS WIRE COMBINATIONS

Listed as a Pressure-Type Wire Connector on the following SOLID and/or STRANDED COPPER TO COPPER CONDUCTOR wire combinations:
For UL Listed and CSA Certified



Voltage Rating 600V Max:

1 or 2 #14	1 #16 w/1 or 2 #18	1 #18 w/2 to 4 #20
2 or 3 #16	1 #16 w/1 #18 w/1 #22	1 #18 w/3 or 4 #22
2 to 4 #18	1 #16 w/1 to 3 #20 or #22	1 or 2 #18 w/1 #20 w/1 #22
1 #14 w/1 #16	1 or 2 #16 w/1 #20 w/1 #22	2 #18 w/1 or 2 #20 or #22
1 #14 w/1 #16 w/1 #18	2 #16 w/1 #18	3 #18 w/1 #20 or #22
1 #14 w/1 or 2 #18	2 #16 w/1 or 2 #20	
1 #14 w/1 to 3 #20 or #22	2 #16 w/1 to 3 #22	

Voltage Rating 300V Max:

4 #16	1 #14 w/4 #20	1 #18 w/1 #20
5 #18	2 #14 w/1 #18	1 #18 w/5 #22
3 to 5 #20	2 #14 w/1 to 3 #20 or #22	2 #18 w/3 #22
5 #22 Sol	1 #16 w/4 #18	3 #18 w/2 #20 or #22
5 #22 Str	2 #16 w/2 or 3 #18	4 #18 w/1 #20 or #22
3 #22 Sol w/2 #22 Str	2 #16 w/3 #20	1 #20 w/4 #22
1 #14 w/1 #16 w/1 #18	3 #16 w/1 #18	2 #20 w/2 or 3 #22
1 #14 w/2 #16	3 #16 w/1 or 2 #20 or #22	3 #20 w/1 or 2 #22
1 #14 w/3 #18	4 #16 w/1 #20 or #22	4 #20 w/1 #22

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: f4p-usa.com

CUSTOMER SERVICE: 772-408-5211

DISCLAIMER

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies. No other warranties apply, including fitness for a particular purpose.