



WAC

MULTI STEALTH RECESSED

Delivering glare-free, high-lumen performance - the Multi Stealth Recessed offers 1500+ combinations of high-powered housings, bespoke trim or trimless options, precise optics and a variety of CCTs for seamless integration in architectural spaces.

DOWNLIGHT / ADJUSTABLE / WALL WASH

MULTI STEALTH RECESSED

Remodel and New Construction

- Housings (For Downlight and Wall Wash Trims)**
- Universal input 120-277V standard
 - New Construction and Remodel available
 - ELV, TRIAC, and 0-10V (100%-1%) dimming standard
 - Trimless spackle frame supplied with trimless housing

- Downlight Trim and Trimless**
- Stealth low glare performance with 40° cutoff angle
 - Available in 5 sizes
 - Lumen output up to 3590 lm
 - 2700K, 3000K, 3500K, 4000K color temperatures available in 90 CRI
 - Powder coated extruded aluminum heat sink and body
 - Push-in mechanism for trimless body installation and service


- Wall Wash Trim and Trimless**
- Low glare floor-to-ceiling wall washing
 - Available in 3 sizes
 - Lumen output up to 2290 lm
 - 2700K, 3000K, 3500K, 4000K color temperatures available in 90 CRI
 - Powder coated extruded aluminum heat sink and body
 - Push-in mechanism for trimless body installation and service

- Housings (For Adjustable Trims)**
- Universal input 120-277V standard
 - New Construction and Remodel available
 - ELV, TRIAC, and 0-10V (100%-1%) dimming standard
 - Trimless spackle frame supplied with trimless housing
 - Aperture sized to accommodate bi-directional adjustable trims


- Adjustable Trim and Trimless**
- Stealth low glare performance with 40° cutoff angle
 - Bi-directional +/-35° vertical aiming
 - Available in 5 sizes
 - Lumen output up to 3590 lm
 - 2700K, 3000K, 3500K, 4000K color temperatures available in 90 CRI
 - Powder coated extruded aluminum heat sink and body
 - Push-in mechanism for trimless body installation and service



BEVEL FINISHES
DOWNLIGHT AND ADJUSTABLE



BEVEL FINISHES
WALL WASH



MULTI STEALTH RECESSED



DOWNLIGHT TRIM	Model	Size	Max Lumens	Max CBCP	Beam	Color Temp	Finish	Bevel/Flange
	R1GDT Downlight	02 2 Cell (4")	580 lm	2445	S 16° N 32° F 45°	927 2700K 930 3000K 935 3500K 940 4000K	BK BK	Black/Black
		04 4 Cell (7")	1140 lm	5030			CH BK	Chrome/Black
		06 6 Cell (10")	1760 lm	7595			GL BK	Gold/Black
		08 8 Cell (13")	2390 lm	10600			HZ BK	Haze/Black
		12 12 Cell (19")	3590 lm	15055			WT BK	White/Black
							BK WT	Black/White
							GL WT	Gold/White
							HZ WT	Haze/White
							WT WT	White/White

Example: R1GDT08-S930-BKWT

DOWNLIGHT TRIMLESS	Model	Size	Max Lumens	Max CBCP	Beam	Color Temp	Finish	Bevel
	R1GDL Downlight	02 2 Cell (3")	580 lm	2445	S 16° N 32° F 45°	927 2700K 930 3000K 935 3500K 940 4000K	BK	Black
		04 4 Cell (6")	1140 lm	5030			CH	Chrome
		06 6 Cell (9")	1760 lm	7595			GL	Gold
		08 8 Cell (12")	2390 lm	10600			HZ	Haze
		12 12 Cell (18")	3590 lm	15055			WT	White

Example: R1GDL08-S930-HZ

DOWNLIGHT TRIM HOUSING	Model	Size	Power	Rating
	R1GRT Remodel	02 2 Cell	8W	Non-IC
		04 4 Cell	14W	
		06 6 Cell	20W	
		08 8 Cell	27W	
		12 12 Cell	38W	
	R1GNT New Construction Airtight	02 2 Cell	8W	IC IC IC IC Non-IC
		04 4 Cell	14W	
		06 6 Cell	20W	
		08 8 Cell	27W	
		12 12 Cell	38W	

Example: R1GNT08

DOWNLIGHT TRIMLESS HOUSING	Model	Size	Power	Rating
	R1GNL New Construction Airtight	02 2 Cell	8W	IC IC IC IC Non-IC
		04 4 Cell	14W	
		06 6 Cell	20W	
		08 8 Cell	27W	
		12 12 Cell	38W	

Example: R1GNL08

* Line drawings show 8 cell fixture. Refer to specification sheets for additional sizes.

MULTI STEALTH RECESSED

ADJUSTABLE TRIM	Model	Size	Max Lumens	Max CBCP	Beam	Color Temp	Finish	Bevel/Flange
	R1GAT +/- 35° Adjustable	02 2 Cell (4 3/4")	580 lm	2445	S 16° N 32° F 45°	927 2700K 930 3000K 935 3500K 940 4000K	BK CH GL HZ WT	Black/Black Chrome/Black Gold/Black Haze/Black White/Black Black/White Chrome/White Gold/White Haze/White White/White
		04 4 Cell (7 3/4")	1140 lm	5030				
		06 6 Cell (10 3/4")	1760 lm	7595				
		08 8 Cell (13 3/4")	2390 lm	10600				
		12 12 Cell (19 3/4")	3590 lm	15055				

Example: **R1GAT08-S930-BKWT**

ADJUSTABLE TRIMLESS	Model	Size	Max Lumens	Max CBCP	Beam	Color Temp	Finish	Bevel
	R1GAL +/- 35° Adjustable	02 2 Cell (3 3/4")	580 lm	2445	S 16° N 32° F 45°	927 2700K 930 3000K 935 3500K 940 4000K	BK CH GL HZ WT	Black Chrome Gold Haze White
		04 4 Cell (6 3/4")	1140 lm	5030				
		06 6 Cell (9 3/4")	1760 lm	7595				
		08 8 Cell (12 3/4")	2390 lm	10600				
		12 12 Cell (18 3/4")	3590 lm	15055				

Example: **R1GAL08-S930-GL**

ADJUSTABLE TRIM HOUSING	Model	Size	Power	Rating
	R1GRT Remodel	02 2 Cell	8W	Non-IC
		04 4 Cell	14W	
		06 6 Cell	20W	
		08 8 Cell	27W	
		12 12 Cell	38W	
	R1GNTA New Construction Airtight	02 2 Cell	8W	IC IC IC IC Non-IC
		04 4 Cell	14W	
		06 6 Cell	20W	
		08 8 Cell	27W	
		12 12 Cell	38W	

Example: **R1GNTA08**

ADJUSTABLE TRIMLESS HOUSING	Model	Size	Power	Rating
	R1GNLA New Construction Airtight	02 2 Cell	8W	IC IC IC IC Non-IC
		04 4 Cell	14W	
		06 6 Cell	20W	
		08 8 Cell	27W	
		12 12 Cell	38W	

Example: **R1GNLA08**

WALL WASH TRIM	Model	Size	Max Lumens	Max CBCP	Beam	Color Temp	Finish	Bevel/Flange
	R1GWT Wall Wash	04 4 Cell (7")	720 lm	N/A	A Asym	927 2700K 930 3000K 935 3500K 940 4000K	BK BK WT	Black/Black Black/White White/White
		08 8 Cell (13")	1480 lm					
		12 12 Cell (19")	2290 lm					

Example: **R1GWT08-A927-BKWT**

WALL WASH TRIMLESS	Model	Size	Max Lumens	Max CBCP	Beam	Color Temp	Finish	Bevel
	R1GWL Wall Wash	04 4 Cell (6")	720 lm	N/A	A Asym	927 2700K 930 3000K 935 3500K 940 4000K	BK WT	Black White
		08 8 Cell (12")	1480 lm					
		12 12 Cell (18")	2290 lm					

Example: **R1GWL08-A935-WT**

WALL WASH TRIM HOUSING	Model	Size	Power	Rating
	R1GRT Remodel	04 4 Cell	14W	Non-IC
		08 8 Cell	27W	
		12 12 Cell	38W	
	R1GNT New Construction Airtight	04 4 Cell	14W	IC IC Non-IC
		08 8 Cell	27W	
		12 12 Cell	38W	

Example: **R1GNT08**

WALL WASH TRIMLESS HOUSING	Model	Size	Power	Rating
	R1GNL New Construction Airtight	04 4 Cell	14W	IC IC Non-IC
		08 8 Cell	27W	
		12 12 Cell	38W	

Example: **R1GNL08**

* Line drawings show 8 cell fixture. Refer to specification sheets for additional sizes.

Consult the factory to take advantage of our custom capabilities in large quantities.

For up-to-date product specifications and assistance, please visit wacighting.com or call 1-800-526-2588

Copyright © 2022 by WAC. All rights reserved. This catalog is copyrighted, and WAC will use all measures available to it under the law against anyone who copies or derives from its copyrighted work. WAC retains the right to modify the design of our products at any time, as part of the company's continuous improvement program.